·GRAVELY.

2023 PRODUCT CATALOG

WE PUT SO IIII MUCHINTOOUR MOWERS. WHICH ISWHYYOUGET SO MUCH OUT

BLOOD, SWEAT & TEARS? SURE, THEY'RE IN THERE. HEART & SOUL? MAXED OUT. PRIDE? YOU'D BETTER BELIEVE IT. THEN, OF COURSE, THERE'S ALL THE SUPERIOR ENGINEERING, INNOVATION, AND ONLY THE BEST PARTS FROM THE SMALLEST **BOLT TO OUR HEAVIEST-GAUGE STEEL. SO,** IF YOU'RE WONDERING WHY YOU SHOULD CHOOSE GRAVELY, OUR ONLY QUESTION IS HOW LONG OF A LIST WOULD YOU LIKE?









MODEL - 991144

15.5 HP Kawasaki® FX481V Engine

44"

MODEL - 991145

19 HP Kawasaki® FX600V Engine

SMALLER FOOTPRINT

The Compact-Pro® easily passes through gates as narrow as 36 inches and nimbly maneuvers around common residential obstacles

FUEL TANK DESIGN Increases stability and improves machine handling and visibility.

KAWASAKI® FX ENGINE Powered by a Kawasaki® FX Engine that touts a heavy-duty canister air cleaner to optimize performance in all conditions and extend engine life.



MODEL - 991286

22 HP Kawasaki° FX691V Engine

52'

MODEL - 991288

22 HP Kawasaki° FX691V Engine

60"

MODEL - 991290

23.5 HP Kawasaki® FX730V Engine

AN AUTOMOTIVE-STYLE TUBULAR

FRAME It's unique to the mowing industry and increases durability by withstanding force from any direction. This high-strength, premium frame is positioned with a lower center of gravity to improve stability while mowing on hillsides.

ZT-3200® TRANSAXLES They're more heavy duty and can handle higher speeds. They're also commercial grade andserviceable for a longer life span.

X-FACTOR® 3 DECK The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

SUSPENSION FORKS Big impacts on rough terrain go virtually unnoticed by the operator. They also improve the overall ride and decrease driver fatigue.



MODEL - 991128

22 HP Kawasaki® FX691V Engine

MODEL - 991129

22 HP Kawasaki® FX691V Engine

MODEL - 991132

23 HP Kohler® ZT730 Engine

60"

MODEL - 991130

23.5 HP Kawasaki® FX730V Engine

MODEL - 991133

25 HP Kohler® EZT740 Engine

CBT SYSTEM Our Constant Belt Tension System (CBT) ensures that belt tension is constant, keeping the blade tip speed and cutting results consistent.

X-FACTOR® II DECK Fabricated from top to bottom, this 7-gauge steel deck provides industrial-strength peace of mind.

SEATING SYSTEM All-day comfort comes from the high-back suspension seat with improved lateral stability and added vibration control, along with a 4-inch seat slide, lumbar support, and padded armrest.





MODEL - 992520

22 HP Kawasaki® FX691V Engine

52"

MODEL - 992521

22 HP Kawasaki® FX691V Engine

60"

MODEL - 992522

23.5 HP Kawasaki® FX730V Engine

MODEL - 992524

25 HP Kohler® ZT740V Engine

MODEL - 992523

26 HP Kawasaki® FT730V-EFI Engine

MODEL - 992526

31 HP Kawasaki® FX921V

72'

MODEL - 992525

31 HP Kawasaki® FX921V Engine

COMFORTABLE SEAT High back seat has lumbar support and molded armrests. Its red double stitching gives a high-end look with black, dark grey, and red accents.

PARKER TRANSAXLES Parker HTJ transaxles deliver a stop speed of 11 mph and have 12cc pump. Filters are accessed from the rear for easy maintenance. It's one complete system, eliminating the need for additional parts



MODEL - 992515

31 HP Kawasaki® FX921V Engine



HIGH-VOLUME OUTPUT (HVO) DECK

The depth of this deck increases from its trim side to its discharge chute. That means it can handle a higher volume of clippings without clogging up.



TUNNEL CHAMBER An advanced cutting chamber is formed by setting the blades back four inches from the front of the deck for less clumping and even grass dispersion.



INTEGRATED SEAT ISOLATORS Bumps and engine vibration are smoothed out thanks to vibration-absorbing dampers.



MODEL - 992513

25 HP Kohler® ZT740 Engine

MODEL - 992510

27 HP Kawasaki® FX850V Engine, Air Ride

60"

MODEL - 992514

25 HP Kohler® ZT740 Engine

MODEL - 992516

29.5 HP Kawasaki® FX850V-EFI Engine

MODEL - 992511

31 HP Kawasaki* FX921V Engine, Air Ride

72'

MODEL - 992518

29.5 HP Kawasaki® FX850V-EFI Engine

MODEL - 992512

31 HP Kawasaki® FX921V Engine, Air Ride

COMFORTABLE SEAT High back seat has lumbar support and padded armrests, and its isolated mounting absorbs more shock.

FULLY WELDED TUBULAR FRAME

Strong and rugged, its wide front rail distributes weight for superior balance and supports the deck lift for easy engagement.

PARKER TRANSAXLES They deliver a top speed of 15mph and have a 16cc pump. Access filters from the rear for easy maintenance.



MODEL - 992500

27 HP Kawasaki° FX850V Engine

60"

MODEL - 992501

35 HP Kawasaki[®] FX1000V Engine

MODEL - 992503

38.5 HP Kawasaki® FX1000V-EFI Engine

72"

MODEL - 992502

35 HP Kawasaki° FX1000V Engine

MODEL - 992504

38.5 HP Kawasaki® FX1000V-EFI Engine



operator from the mower's bouncing and jostling. You'll feel like you're floating as you mow faster and more comfortably, without sacrificing control.

DIAL-A-HEIGHT This lets the operator easily adjust the deck height by quarter-inch increments.

X-FACTOR® 3 DECK The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.





SIDE DISCHARGE MODEL - 997005

4-16 KwH FusionCore Swappable Batteries

REAR DISCHARGE MODEL - 997008

4-16 KwH FusionCore Swappable Batteries

52"

SIDE DISCHARGE MODEL - 997006

4-16 KwH FusionCore Swappable Batteries

REAR DISCHARGE MODEL - 997009

4-16 KwH FusionCore Swappable Batteries

SIDE DISCHARGE MODEL - 997007

4-16 KwH FusionCore Swappable Batteries

REAR DISCHARGE MODEL - 997010

4-16 KwH FusionCore Swappable Batteries

FUSIONCORE QUICKSWAP BATTERIES

Batteries can be switched in seconds to ensure you and your crew can continue to cut all day and beyond.

X3 CONSTANT DRIVE SPINDLES Our proprietary spindles have a blade slip feature that prevents damage in the event of an impact. They also have a bottom bearing for easy serviceability for routine maintenance which avoids

NEXT-GEN WHEEL DRIVES Transaxles are driven with a brushless electricdrive motor coupled with a dualreduction planetary gearbox.



SIDE DISCHARGE MODEL - 998001

4-16 KwH FusionCore Swappable Batteries

REAR DISCHARGE MODEL - 998004

4-16 KwH FusionCore Swappable Batteries

SIDE DISCHARGE MODEL - 998002

4-16 KwH FusionCore Swappable Batteries

REAR DISCHARGE MODEL - 998005

4-16 KwH FusionCore Swappable Batteries

SIDE DISCHARGE MODEL - 998003

4-16 KwH FusionCore Swappable Batteries

REAR DISCHARGE MODEL - 998006

4-16 KwH FusionCore Swappable Batteries

QUICK BATTERY SWAP SYSTEMS

Gravely EV mowers include a quickswap battery system that allows you to run your mowers all day. No need to stop when the battery runs out. Just simply swap a new battery in and keep on mowing!

QUIET OPERATION Gas-powered lawn mowers are loud, especially in urban areas where the sound bounces off the structures. Electric mowers do not have the loud noises, or the vibrations mowers typically need to deal with when using gas. Lower noise pollution is a great.



MODEL - 994157

18.5 HP Kawasaki* FS600V Engine

36"

MODEL - 994149

18.5 HP Kawasaki® FS600V Engine

48"

MODEL - 994161

23.5 HP Kawasaki® FX730V Engine

52"

MODEL - 994162

23.5 HP Kawasaki® FX730V Engine

MODEL - 994163

26 HP Kawasaki® FT730V-EFI Engine

60"

MODEL - 994164

23.5 HP Kawasaki® FX730V Engine

MODEL - 994165

26 HP Kawasaki® FT730V-EFI Engine

DECK HEIGHT ADJUSTMENT The

dual height-adjustment system was designed with both a traditional hand lever and a foot lever to lift and adjust the deck. It's perfect for smaller operators who may struggle with traditional hand lever lifts.



MODEL - 994160

18.5 HP Kawasaki® FS600V Engine

MODEL - 994159

22 HP Kawasaki® FS651V Engine

52"

MODEL - 994158

22 HP Kawasaki® FS651V Engine

ADJUSTABLE CRUISE BAR Allows

the operator to limit and expand the unit's maximum speed in tight working environments.

THREE DECKS TO CHOOSE FROM 10

gauge 48" and 52" X-Factor III decks or 32" deck in 7 gauge for added weight.

HEIGHT-OF-CUT SYSTEM Simple lever control for fast adjustments

LOWERED CENTER OF GRAVITY

Reshaped geometry and redistributed weight provide increased hillside stability and confidence in your ride.



MODEL - 988184

14.5 HP Kawasaki® FS481V Engine

MODEL - 988185

18.5 HP Kawasaki® FS600V Engine

52"

MODEL - 988186

18.5 HP Kawasaki* FS600V Engine

MODEL - 988187

23 HP Kawasaki® FS691V Engine

SINGLE-POINT HEIGHT-OF-CUT

Provides optimal cutting performance in 1/4-inch increments.

WIDE WHEELBASE Delivers superior hillside stability.

INTUITIVE STEERING CONTROLS

Offers a shortened learning curve while providing precision handling.





MODEL - 918007

23 HP Kohler® KT730 Engine

MODEL - 918008

21.5 HP Kawasaki® FR651V Engine

48"

MODEL - 918009

21.5 HP Kawasaki® FR651V Engine

52"

MODEL - 918010

23 HP Kohler® KT730 Engine

MODEL - 918011

23 HP Kawasaki° FR691V Engine

HYDRO-GEAR® SERVICEABLE EZT®
TRANSAXLES Serviceable transaxles
have optimized cooling to ensure
smooth running for years to come. New

service ports allow oil changes to help extend the life of your machine.

NEW TALLER AND WIDER SEAT WITH MOLDED ARMRESTS Ready for the long mow! This seat is 22" tall to provide more back support and is mounted on a taller seat base to make it easier to stand up and sit down. Molded armrests give your arms rest too.

FULLY WELDED TUBULAR FRAME

This fully welded tubular frame is a professional-grade backbone tough enough to get the job done in your backyard.



42''

MODEL - 918012

21.5 HP Kawasaki® FR651V Engine

48"

MODEL - 918013

23 HP Kawasaki® FR691V Engine

52"

MODEL - 918015

23 HP Kawasaki® FR691V Engine

MODEL - 918014

25 HP Kohler® KT740 Engine

50"

MODEL - 918016

24 HP Kawasaki® FR730V Engine

HYDRO-GEAR® ZT-2800® TRANSAXLES

Serviceable transaxles have optimized cooling to ensure smooth running for years to come. Integrated service ports on the internal reservoirs and a replaceable filter allow fluid changes for easy maintenance.

RIDE LIKE A PRO The 22" high back seat delivers more back support and has padded armrests. It's mounted on vibration-absorbing dampers. They smooth out bumps and engine vibration for a more comfortable ride.



MODEL - 991266

21.5 HP Kawasaki® FR651V Engine

48"

MODEL - 991268

23 HP Kawasaki® FR691V Engine

MODEL - 991274

25 HP Kohler® KT740 Engine

52"

MODEL - 991270

23 HP Kawasaki® FR691V Engine

MODEL - 991276

25 HP Kohler® KT740 Engine

60'

MODEL - 991272

24 HP Kawasaki® FR730V Engine

MODEL - 991278

26 HP Kohler® KT745 Engine

HYDRO-GEAR® ZT-3100® TRANSAXLES

Reliable, commercial grade transaxles deliver the speed and torque to get your mowing done quickly. They're also easy to service for more longevity.

comfortable RIDE High back seat with padded armrests, mounted on vibration absorbing dampers smoothing out bumps and engine vibration making for a comfortable ride.







MAINTENANCE KITS

Gravely maintenance kits offer a complete service package, designed to protect your engine and promote optimal performance levels.



OEM OIL

Gravely Oils are specifically formulated to provide protection for your engine in the toughest of environments.



OEM BELTS

Designed to be a perfect fit for your machine, Gravely OEM belts provide the strength, longevity and quality needed to enhance performance and cut quality.



Separate cutting chambers for each blade produce smaller clippings for a professionally manicured appearance.

LASEREDGE BLADE

These self-sharpening blades last up to 5 times longer than standard blades,

helping to minimize downtime.



BAGGER SYSTEMS

Gravely's two- and three-bucket mesh bags provide superior airflow and venting.



Powered lift kits make cutting-height adjustments smooth and simple.



LIGHT KIT

The LED headlight kit will light your way and keep you cutting long after others call it a day.



REAR TWEEL

These airless, run-flat tires help to minimize your downtime and dampen the effect of uneven terrain.



HITCH KIT

Add a hitch kit to enjoy unmatched versatility with a variety of tow-behind options.





AMERICAN MADE IT STILL MEANS THE WORLD TO US

For over 100 years every Gravely that's come off our line has been built right here in the USA – and that's not changing any time soon. Because we believe in American ingenuity. We believe in the American work ethic. And just like the people who ride on a Gravely, we believe in doing the job right. That's not only the American way, that's the Gravely way.

COMPACT-PRO®	34	44			
MODEL NUMBER	991144	991145			
ENGINE	KAWASAKI® FX CC481V, HEAVY DUTY AIR CLEANER	KAWASAKI® FX600V			
HORSEPOWER	15.5 HP	19 HP			
DISPLACEMENT	603 CC	726 CC			
DRIVE SYSTEM	HYDRO-	GEAR* ZT-3100			
UEL CAPACITY	7	7.2 GAL			
GROUND SPEED (Forward/Reverse)	7 MF	PH / 3 MPH			
ECK					
ECK MATERIAL	10 GA. STEEL WITH 10 G	A. SPINDLE REINFORCEMENT			
ECK CONSTRUCTION	FAE	BRICATED			
IUMBER OF SPINDLES	2	3			
LADE TIP SPEED (FPM)		18,000			
PINDLE HOUSING MATERIAL	FORGE	D ALUMINUM			
PINDLE BEARINGS	BALL BEARING				
ECK ENGAGEMENT	OGURA® GT1.5				
ECK LIFT SYSTEM	FOOT OPERATED				
UTTING WIDTH	34 IN.	44 IN.			
UTTING HEIGHT	1.01	N 5.0 IN.			
UTTING POSITIONS		17			
/HEELS					
RONT AXLE		FIXED			
RONT	13 X 5 - 6 SM	100TH PNEUMATIC			
EAR	21 X 7-10 TURF	20.5 X 8-10 TURF			
EATURES					
EAT	HIGH BACK V	WITH SUSPENSION			
OLDABLE ROPS	OF	PTIONAL			
IACHINE					
VEIGHT	737 LBS.	789 LBS.			
ENGTH	75 IN.	75 IN.			
VIDTH (w/o CHUTE)	35.9 IN.	46.7 IN.			
VIDTH (w/ CHUTE)	48.3 IN.	56.9 IN.			
EIGHT	1	5.3 IN.			
VARRANTY					
NIT	4 YEAR / 750 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS - SEE YO	UR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE WARRANTY DETAILS			
ATTACHMENTS & ACCESSORIES					

MULCHING KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUNSHADE KIT, FOLDING ROPS KIT, GRASS CATCHER KIT, LEAF COLLECTOR KIT, WHEEL COVER KIT, LASEREDGE BLADES

PRO-TURN® ZX	48	52	60		
MODEL NUMBER	991286	991288	991290		
ENGINE	KAWASAKI° FX691V	KAWASAKI" FX691V	KAWASAKI° FX730V		
HORSEPOWER	22 HP	22 HP	23.5 HP		
ISPLACEMENT		726 CC			
DRIVE SYSTEM		HYDRO-GEAR® ZT-3200			
UEL CAPACITY		5.0 GAL			
ROUND SPEED (Forward/Reverse)		8.5 MPH / 4 MPH			
DECK					
DECK MATERIAL		10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT			
ECK CONSTRUCTION		FABRICATED X-FACTOR® 3			
IUMBER OF SPINDLES		3			
LADE TIP SPEED (FPM)		18,000			
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM				
SPINDLE BEARINGS	BALL BEARING				
DECK ENGAGEMENT		OGURA® GT1.5			
CUTTING WIDTH	48 IN.	52 IN.	60 IN.		
UTTING HEIGHTS		1.5 IN 5.0 IN.			
UTTING POSITIONS		15			
/HEELS					
RONT AXLE		SUSPENSION, GREASABLE CASTER FORK TUBES			
RONT		SMOOTH 13 X 6.50-6			
REAR	TURF 22 X 10-12	TURF 22 X 10.5-12	TURF 22 X 12-12		
EATURES					
EAT		HIGH BACK COMFORT W/ SUSPENSION & PADDED ARMRESTS			
FOLDABLE ROPS		STANDARD			
ACHINE					
VEIGHT	925 LBS.	931 LBS.	952 LBS.		
ENGTH	79 IN.	79 IN.	79 IN.		
VIDTH (w/o CHUTE)	50.8 IN.	56.2 IN.	63.7 IN.		
VIDTH (w/ CHUTE)	61.9 IN.	67.3 IN.	74.8 IN.		
IEIGHT (w/ ROPS EXT/DOWN)		72 IN. / 52 IN.			
VARRANTY					
INIT	4 YEAR / 750 HOUR LIN	MITED - SEE YOUR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE	WARRANTY DETAILS		

MULCHING KIT, OCDB KIT, TRAILER HITCH KIT, LED HEADLIGHT KIT, AGGRESSIVE REAR TIRE KIT, STRIPING KIT, SUNSHADE KIT, POWERED BAGGER KIT, REAR TWEEL KIT, SUSPENSION SEAT KIT, SEMI-PNEUMATIC FRONT TIRE KIT, WHEEL COVER KIT, LASEREDGE BLADES, TUNE UP KIT

PRO-TURN® 100	148	152	152	160	160		
MODEL NUMBER	991128	991129	991132	991130	991133		
ENGINE	KAWASAKI* FX691V	KAWASAKI° FX691V	KOHLER* ZT730	KAWASAKI*FX730V	KOHLER® ZT740		
HORSEPOWER	22 HP	22 HP	23 HP	23.5 HP	25 HP		
DISPLACEMENT	726 CC	726 CC	747 CC	726 CC	747 CC		
DRIVE SYSTEM			HYDRO-GEAR* ZT-3400				
FUEL CAPACITY			10 GAL				
GROUND SPEED (Forward/Reverse)			10 MPH / 5 MPH				
DECK							
DECK MATERIAL		7 G	A. STEEL W/ 1/4 IN. SPINDLE REINFORCEMI	ENT			
DECK CONSTRUCTION			FABRICATED				
NUMBER OF SPINDLES			3				
BLADE TIP SPEED (FPM)			18,000				
SPINDLE HOUSING MATERIAL		FORGED ALUMINUM					
SPINDLE BEARINGS		BALL BEARING					
DECK ENGAGEMENT			OGURA® GT 2.75				
CUTTING WIDTH	48 IN.	52 IN.	52 IN.	60 IN.	60 IN.		
CUTTING HEIGHTS		1.0 IN 5.0 IN.					
CUTTING POSITIONS			17				
WHEELS							
FRONT AXLE			FIXED, GREASEABLE CASTER FORK TUBES				
FRONT			SM00TH 13 X 6.50 - 6				
REAR			TURF 23 X 10.50 - 12				
FEATURES							
SEAT			SUSPENSION PLUSH SEAT WITH ARM REST:	5			
FOLDABLE ROPS			STANDARD				
MACHINE							
WEIGHT	1062 LBS.	1079 LBS.	1068 LBS.	1121 LBS.	1110 LBS.		
LENGTH	78.5 IN.	78.5 IN.	78.5 IN.	78.5 IN.	78.5 IN.		
WIDTH (w/o CHUTE)	50 IN.	55.5 IN	55.5 IN	63 IN.	63 IN.		
VIDTH (w/ CHUTE)	62 IN.	67.5 IN.	67.5 IN.	75 IN.	75 IN.		
HEIGHT (W/ ROPS EXT/DOWN)			68 IN. / 48 IN				
WARRANTY							
JNIT	5 YEAR / 1000	HOUR COMMERCIAL / NO HOUR LIMIT FIRE	ST 2 YEARS - SEE YOUR PROFESSIONAL GR	RAVELY® DEALER FOR COMPLETE WARR	ANTY DETAILS		
DECK SHELL & FRAME			LIMITED LIFETIME				

MULCHING KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUNSHADE KIT, BAGGER KIT, SEMI-PNEUMATIC FRONT TIRE KIT, WHEEL COVER KIT, RADIAL DRIVE CONVERSION KIT, OCDB KIT, LASEREDGE BLADES, TUNE UP KIT

PRO-TURN® 300	348	352	360	360	360	360	372
MODEL NUMBER	992520	992521	992522	992524	992523	992526	992525
ENGINE	KAWASAKI FX691V	KAWASAKI FX691V	KAWASAKI FX730V	KOHLER ZT740	KAWASAKI FT730 EFI	KAWASAKI FX921V	KAWASAKI FX92
HORSEPOWER	22 HP	22 HP	23.5 HP	25 HP	26 HP	31 HP	31 HP
DISPLACEMENT	726 CC	726 CC	726 CC	747 CC	726 CC	999 CC	999 CC
DRIVE SYSTEM				PARKER HTJ TRANSMISSION	'	'	
FUEL CAPACITY				12.5 GAL			
GROUND SPEED (Forward/Reverse)				11 MPH / 5 MPH			
DECK							
DECK MATERIAL			7 GA. STE	L WITH .25 IN. SPINDLE REINF	ORCEMENT		
DECK CONSTRUCTION				X-FACTOR® 3 DECK			
NUMBER OF SPINDLES				3			
BLADE TIP SPEED (FPM)				18,000			
SPINDLE HOUSING MATERIAL		FORGED ALUMINUM					
SPINDLE BEARINGS				BALL BEARING			
DECK ENGAGEMENT			OGURA GT2.75			OGURA	A GT3.5
CUTTING WIDTH	48 IN.	52 IN.	60 IN.	60 IN.	60 IN.	60 IN.	72 IN.
CUTTING HEIGHTS				1.0 IN 5.5 IN.			1
CUTTING POSITIONS				19			
WHEELS							
FRONT AXLE			FIXED	, GREASEABLE CASTER FORK	TUBES		
FRONT				SMOOTH 15 X 6-6 PNEUMATIC			
REAR				24 X 12-16 BIAS PLY TURF			
FEATURES	, 						
BEAT			SUSPE	NSION PLUSH SEAT WITH ARM	RESTS		
FOLDABLE ROPS				STANDARD			
MACHINE							
WEIGHT	1235 LBS.	1320 LBS.	1347 LBS.	1333 LBS.	1347 LBS.	1350 LBS.	1472 LBS.
LENGTH	84 IN.	84 IN.	84 IN.	84 IN.	84 IN.	84 IN.	86.2 IN.
WIDTH (w/o CHUTE)	51 IN.	55 IN.	63 IN.	63 IN.	63 IN.	63 IN.	75 IN.
WIDTH (w/ CHUTE)	63 IN.	67 IN.	75 IN.	75 IN.	75 IN.	75 IN.	87 IN.
HEIGHT (w/ ROPS EXT/DOWN)			1	76.0 IN. /47.8 IN.	1	1	
WARRANTY							
UNIT		5 YEAR/1250 HOUR COMME	RCIAL/NO HOUR LIMIT FIRST 2	YEARS- SEE YOUR PROFESSIO	NAL GRAVELY DEALER FOR CO	MPLETE WARRANTY DETAILS	
DECK SHELL & FRAME				LIMITED LIFETIME			

MULCHING KIT, ELECTRIC DECK LIFT KIT, TRAILER KIT KIT, LED HEADLIGHT KIT, POWERED BAGGER KIT, OCDC KIT, SUNSHADE KIT, REAR TWEEL KIT, RADIAL DRIVE CONVERSION KIT, WHEEL COVER KIT, LASEREDGE BLADE KIT, TUNE UP KIT

PRO-TURN® MACH ONE	60
MODEL NUMBER	992515
ENGINE	KAWASAKI® FX921V
HORSEPOWER	31 HP
DISPLACEMENT	999 CC
DRIVE SYSTEM	PARKER HTG TRANSMISSION
FUEL CAPACITY	12.5 GAL
GROUND SPEED (Forward/Reverse)	15 MPH/6 MPH
DECK	
DECK MATERIAL	7 GA. STEEL W/ .25 IN. SPINDLE REINFORCEMENT
DECK CONSTRUCTION	HIGH-VOLUME OUTPUT DECK
NUMBER OF SPINDLES	3
BLADE TIP SPEED (FPM)	18,000
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM
SPINDLE BEARINGS	BALL BEARING
DECK ENGAGEMENT	OGURA® GT3.5 ELECTRIC CLUTCH
CUTTING WIDTH	60 IN.
CUTTING HEIGHTS	1.5 IN 5.5 IN.
CUTTING POSITIONS	19
WHEELS	
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES
FRONT	SMOOTH 15 X 6-6 SEMI PNEUMATIC
REAR	26 X 12-16 RADIAL TURF
FEATURES	
SEAT	HIGH BACK COMFORT W/ FULL SUSPENSION AND PADDED ARMRESTS
FOLDABLE ROPS	STANDARD
MACHINE	
WEIGHT	1486 LBS.
LENGTH	86.2 IN.
WIDTH (W/ CHUTE UP/DOWN)	61 IN. / 74.6 IN.
HEIGHT (W/ ROPS EXT/DOWN)	75 IN. / 47.75 IN.
WARRANTY	
UNIT	5 YEAR / 1500 HOUR COMMERCIAL / NO HOUR LIMIT FIRST TWO YEARS - SEE YOUR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE WARRANTY DETAILS
ATTACHMENTS & ACCESSORIES	

MULCHING KIT, ELECTRIC DECK LIFT KIT, TRAILER KIT KIT, LED HEADLIGHT KIT, POWERED BAGGER KIT, OCDC KIT, SUNSHADE KIT, REAR TWEEL KIT, RADIAL DRIVE CONVERSION KIT, WHEEL COVER KIT, LASEREDGE BLADE KIT, TUNE UP KIT

PRO-TURN® 500	552	552	560	560	560	572	572	
MODEL NUMBER	992510	992513	992511	992514	992516	992518	992512	
ENGINE	KAWSAKI FX850V	KOHLER ZT740	KAWASAKI FX921V	KOHLER ZT740	KAWASAKI 850V EFI	KAWASAKI 850V EFI	KAWASAKI FX921	
HORSEPOWER	27 HP	25 HP	31 HP	25 HP	29.5 HP	29.5 HP	31 HP	
DISPLACEMENT	852 CC	747 CC	999 CC	747 CC	852 CC	852 CC	999 CC	
DRIVE SYSTEM				PARKER HTG TRANSMISSION				
FUEL CAPACITY				12.5 GAL				
GROUND SPEED (Forward/Reverse)				15 MPH / 6 MPH				
DECK								
DECK MATERIAL			7 GA. STEI	EL WITH .25 IN. SPINDLE REINF	DRCEMENT			
DECK CONSTRUCTION				X-FACTOR® 3 DECK				
NUMBER OF SPINDLES				3				
BLADE TIP SPEED (FPM)				18,000				
SPINDLE HOUSING MATERIAL		FORGED ALUMINUM						
SPINDLE BEARINGS		BALL BEARING						
DECK ENGAGEMENT				OGURA® GT3.5				
CUTTING WIDTH	52 IN.	52 IN.	60 IN.	60 IN.	60 IN.	72 IN.	72 IN.	
CUTTING HEIGHTS		'		1.0 IN 5.5 IN.		,		
CUTTING POSITIONS				19				
WHEELS								
FRONT AXLE			FIXE), GREASEABLE CASTER FORK	ΓUBES			
FRONT			S	MOOTH 15 X 6-6 SEMI PNEUMA	TIC			
REAR				26 X 12-16 RADIAL TURF				
FEATURES								
PLUSH SEAT WITH ARM RESTS	AIR RIDE	ISOLATED SUSPENSION	AIR RIDE	ISOLATED SUSPENSION	ISOLATED SUSPENSION	ISOLATED SUSPENSION	AIR RIDE	
FOLDABLE ROPS				STANDARD				
MACHINE								
WEIGHT	1447 LBS.	1423 LBS.	1487 LBS.	1463 LBS.	1477 LBS.	1580 LBS.	1580 LBS.	
LENGTH	84 IN.	84 IN.	84 IN.	84 IN.	86.2 IN.	86.2 IN.	86.2 IN.	
NIDTH (w/o CHUTE)	51 IN.	51 IN.	63 IN.	63 IN.	63 IN.	75 IN.	75 IN.	
VIDTH (w/ CHUTE)	63 IN.	63 IN.	75 IN.	75 IN.	75 IN.	87 IN.	87 IN.	
HEIGHT (w/ ROPS EXT/DOWN)				76.0 IN./47.8 IN.				
WARRANTY								
JNIT		5 YEAR/1500 HOUR COMMER	RCIAL/NO HOUR LIMIT FIRST 2	YEARS- SEE YOUR PROFESSIO	NAL GRAVELY DEALER FOR CO	MPLETE WARRANTY DETAILS		
DECK SHELL & FRAME				LIMITED LIFETIME				

MULCHING KIT, ELECTRIC DECK LIFT KIT, TRAILER KIT KIT, LED HEADLIGHT KIT, POWERED BAGGER KIT, OCDC KIT, SUNSHADE KIT, REAR TWEEL KIT, RADIAL DRIVE CONVERSION KIT, WHEEL COVER KIT, LASEREDGE BLADE KIT, TUNE UP KIT

PRO-TURN® 600	652	660	660	672	672		
MODEL NUMBER	992500	992501	992503	992502	992504		
ENGINE	KAWASAKI" FX850V	KAWASAKI° FX1000	KAWASAKI° FX1000V-EFI	KAWASAKI° FX1000	KAWASAKI° FX1000V-EFI		
ORSEPOWER	27 HP	35 HP	38.5 HP	35 HP	38.5 HP		
ISPLACEMENT	852 CC	999 CC	999 CC	999 CC	999 CC		
PRIVE SYSTEM			PARKER HTG TRANSMISSION				
UEL CAPACITY			12.5 GAL				
ROUND SPEED (Forward/Reverse)			15 MPH / 6 MPH				
DECK							
ECK MATERIAL		7 GA	A. STEEL WITH .25 IN. SPINDLE REINFORCEM	IENT			
ECK CONSTRUCTION			FABRICATED X-FACTOR III				
IUMBER OF SPINDLES			3				
LADE TIP SPEED (FPM)			18,000				
PINDLE HOUSING MATERIAL			FORGED ALUMINUM				
PINDLE BEARINGS		BALL BEARING					
ECK ENGAGEMENT		OGURA* GT3.5					
UTTING WIDTH	52 IN.	60 IN.	60 IN.	72 IN.	72 IN.		
UTTING HEIGHTS			1.0 IN 5.5 IN.				
UTTING POSITIONS			19				
VHEELS							
RONT AXLE			FIXED, GREASEABLE CASTER FORK TUBES				
RONT			SMOOTH 15 X 6-6 SEMI PNEUMATIC				
REAR			26 X 12-16 LOW PROFILE RADIAL TURF				
EATURES							
EAT		HIGH BACK BOI	STERED SEAT WITH OPERATOR POD SUSPE	NSION SYSTEM			
OLDABLE ROPS			STANDARD				
AACHINE							
VEIGHT	1535 LBS.	1586 LBS.	1601 LBS.	1646 LBS.	1661 LBS.		
.ENGTH	83 IN.	83 IN.	83 IN.	83 IN.	83 IN.		
/IDTH (w/o CHUTE)	55 IN.	63 IN.	63 IN.	75 IN.	75 IN.		
/IDTH (w/ CHUTE)	63 IN.	75 IN.	75 IN.	87 IN.	87 IN.		
EIGHT (w/ ROPS EXT/DOWN)			71.5 IN / 47.8 IN				
VARRANTY							
NIT	5 YEAR / 1500	HOUR COMMERCIAL / NO HOUR LIMIT FIRE	ST 2 YEARS - SEE YOUR PROFESSIONAL GR	RAVELY® DEALER FOR COMPLETE WARR	ANTY DETAILS		
PECK SHELL & FRAME			LIMITED LIFETIME				

MULCHING KIT, TRAILER HITCH KIT, LED HEADLIGHT KIT, STRIPING KIT, POWERED BAGGER KIT, OCDB KIT, SUNSHADE KIT, REAR TWEEL KIT, SEMI-PNEUMATIC FRONT TIRE KIT, RADIAL DRIVE CONVERSION KIT, WHEEL COVER KIT, AIR RIDE SEAT KIT, LASEREDGE BLADES, TUNE UP KIT, SUNSHADE KIT, REAR TWEEL KIT, SEMI-PNEUMATIC FRONT TIRE KIT, RADIAL DRIVE CONVERSION KIT, WHEEL COVER KIT, AIR RIDE SEAT KIT, LASEREDGE BLADES, TUNE UP KIT

EV 48 SD	EV 48 RD	EV 52 SD	EV 52 RD	EV 60 SD	EV 60 RD		
997005	997008	997006	997009	997007	997010		
		4 - 16 KWH FUSIO	N CORE LITHIUM ION				
		5 KW PI	ER MOTOR				
		3.5 KW F	PER MOTOR				
		PROPRIETARY ELE	ECTRIC TRANSAXLES				
		8 MPH / 4MPH (LOW SPEED) -	11 MPH / 5.5 MPH (HIGH SPEED)				
		7	GA.				
		X-FACTO	DR 3® DECK				
			3				
		18	,000				
	CAST ALUMINUM						
	SERVICEABLE BOTTOM BEARING						
		ELECTRIC DC BR	USHLESS MOTORS				
48 IN.	48 IN.	52IN.	52 IN.	60 IN.	60 IN.		
		1.5 IN	5.0 IN.				
			15				
		FIXED, GREASEABLE	CASTER FORK TUBES				
		SM00TH	I 13 X 6.5-6				
RADIAL TURF	= 22 X 10-12	RADIAL TUR	F 22 X 10.5-12	RADIAL TURF	= 22 X 12-12		
		HIGH BACK COMFO	RT WITH SUSPENSION				
		STAI	NDARD				
1261 LBS.	1286 LBS.	1284 LBS.	1301 LBS.	1312 LBS.	1326 LBS.		
83 IN.	83 IN.	83 IN.	83 IN.	83 IN.	83 IN.		
50 IN.	50 IN.	56 IN.	54 IN.	63 IN.	64 IN.		
62 IN.	50 IN.	67 IN.	54 IN.	75 IN.	62 IN.		
		72 IN	/ 49 IN.				
5 YEAR	/ 1500 HOUR COMMERCIAL / NO H	HOUR LIMIT FIRST 2 YEARS - SEE YO	UR PROFESSIONAL GRAVELY® DEA	LER FOR COMPLETE WARRANTY DE	TAILS		
	997005 48 IN. RADIAL TURI 1261 LBS. 83 IN. 50 IN. 62 IN.	997005 997008 48 IN. 48 IN. 48 IN. RADIAL TURF 22 X 10-12 1261 LBS. 1286 LBS. 83 IN. 83 IN. 50 IN. 50 IN. 50 IN. 50 IN.	997005 997008 4 - 16 KWH FUSIO 5 KW PI 3.5 KW FI PROPRIETARY ELE 8 MPH / 4MPH (LOW SPEED) — 7 X-FACTO 18 CAST A SERVICEABLE I ELECTRIC DC BR 48 IN. 48 IN. 52 IN. 1.5 IN FIXED, GREASEABLE SMOOTH RADIAL TURF 22 X 10-12 RADIAL TUR STAL 1261 LBS. 1286 LBS. 1286 LBS. 1284 LBS. 83 IN. 83 IN. 83 IN. 50 IN. 572 IN	977005 997008 997006 997009 4 - 16 KWH FUSION CORE LITHIUM ION 5 KW PER MOTOR 3.5 KW PER MOTOR PROPRIETARY ELECTRIC TRANSAXLES 8 MPH / 4MPH (LOW SPEED) - 11 MPH / 5.5 MPH (HIGH SPEED) 7 GA. X-FACTOR 3° DECK 3 18,000 CAST ALUMINUM SERVICEABLE BOTTOM BEARING ELECTRIC DC BUSHLESS MOTORS 48 IN. 48 IN. 52 IN. 52 IN. 1.5 IN 5.0 IN. 15 FIXED, GREASEABLE CASTER FORK TUBES SMOOTH 13 X 6.5 - 6 RADIAL TURF 22 X 10-12 RADIAL TURF 22 X 10-12 HIGH BACK COMFORT WITH SUSPENSION STANDARD 1261 LBS. 1286 LBS. 1284 LBS. 1301 LBS. 83 IN. 83 IN. 83 IN. 83 IN. 83 IN. 83 IN. 50 IN. 50 IN. 56 IN. 54 IN. 62 IN. 50 IN. 54 IN.	997005 997008 997006 997009 997007 4 - 16 KWH FUSION CORE LITHIUM ION 5 KW PER MOTOR 3.5 KW PER MOTOR PROPRIETARY ELECTRIC TRANSAXLES 8 MPH / 4MPH (LOW SPEED) - 11 MPH / 5.5 MPH (HIGH SPEED) 7 GA. X-FACTOR 3° DECK 3 18,000 CAST ALUMINUM SERVICEABLE BOTTOM BEARING ELECTRIC DE RUSHLESS MOTORS 48 IN. 48 IN. 52 IN. 60 IN. 1.5 IN 5.0 IN. 15 FIXED. GREASEABLE CASTER FORK TUBES SMOOTH 13 X 6.5-6 RADIAL TURE 22 X 10-12 RADIAL TURE HIGH BACK COMFORT WITH SUSPENSION STANDARD 1261 LBS. 1286 LBS. 1284 LBS. 1301 LBS. 1312 LBS. 83 IN. 65 I		

FUSIONCORE OFF BOARD PORTABLE CHARGER, REPLACEMENT BATTERIES, MULCHING KIT, LED HEADLIGHT KIT, BEACON LIGHT KIT, FAST CHARGE KIT WITH Y HARNESS, HIGH-LIFT BLADE KIT, OCDB KIT, FRONT CASTOR SUSPENSION FORKS, REAR TWEEL KIT, FRONT WEIGHT KIT

4850	48RD	5250	52RD	6050	60RD
998001	998004	998002	998005	998003	998006
		4 - 16 KWH FUSION	CORE LITHIUM ION		
		5 KW PE	R MOTOR		
		PROPRIETARY ELEC	CTRIC TRANSAXLES		
		8 MPH / 4MPH (LOW SPEED) - 1	1 MPH / 5.5 MPH (HIGH SPEED)		
		7 GA.	STEEL		
		X-FACTOR	R® 3 DECK		
			3		
		18,	000		
		CAST AL	UMINUM		
SERVICEABLE BOTTOM BEARING					
ELECTRIC DC BRUSHLESS MOTORS					
48	IN.	52	IN.	60) IN.
SIDE	REAR	SIDE	SIDE REAR		REAR
		1.5 IN.	- 5.0 IN.		
		1	5		
		FIXED, GREASABLE (CASTER FORK TUBES		
		SM00TH 13 X 6.5-6	SEMI-PNEUMATIC		
		20 X 10.	5-8 TURF		
1204 LBS.	1203 LBS.	1240 LBS.	1236 LBS.	1265 LBS .	1264 LBS.
74.5 IN.	74.5 IN.	74.5 IN.	74.5 IN.	74.5 IN.	74.5 IN.
50 IN.	50 IN.	56 IN.	54 IN.	63 IN.	62 IN.
62 IN.	50 IN.	67 IN.	54 IN.	75 IN.	62 IN.
		46.	D IN.		
	5 YEAR/1500 HOUR COMMERCI	AL/3 YEAR BATTERY- SEE YOUR PRO	FESSIONAL GRAVELY DEALER FOR	COMPLETE WARRANTY DETAILS	
	998001 48 SIDE 1204 LBS. 74.5 IN. 50 IN.	998001 998004 48 IN. SIDE REAR 1204 LBS. 1203 LBS. 74.5 IN. 74.5 IN. 50 IN. 50 IN. 62 IN. 50 IN.	998001 998004 998002 4 - 16 KWH FUSION 5 KW PE PROPRIETARY ELEC 8 MPH / 4MPH (LOW SPEED) - 1 7 GA. X-FACTOR 18, CAST AL SERVICEABLE B ELECTRIC DC BRL 48 IN. 52 SIDE REAR SIDE 1.5 IN. 1 FIXED, GREASABLE C SMOOTH 13 X 6.5-6 20 X 10.9 1204 LBS. 1203 LBS. 1240 LBS. 74.5 IN. 74.5 IN. 50 IN. 50 IN. 56 IN. 62 IN. 50 IN. 56 IN.	998001 998001 998002 998005 4 - 16 KWH FUSION CORE LITHIUM ION 5 KW PER MOTOR PROPRIETARY ELECTRIC TRANSAXLES 8 MPH / 4MPH (LOW SPEED) - 11 MPH / 5.5 MPH (HIGH SPEED) 7 GA. STEEL X.FACTOR* 3 DECK 3 18,000 CAST ALUMINUM SERVICEABLE BOTTOM BEARING ELECTRIC DC BRUSHLESS MOTORS 48 IN. 52 IN. SIDE REAR SIDE REAR 1.5 IN 5.0 IN. 15 FIXED, GREASABLE CASTER FORK TUBES SMOOTH 13 X 6.5-6 SEMI-PNEUMATIC 20 X 10.5-8 TURF 1204 LBS. 1203 LBS. 1204 LBS. 1204 LBS. 1236 LBS. 74.5 IN. 74.5 IN. 74.5 IN. 50 IN. 50 IN. 50 IN. 50 IN. 56 IN. 54 IN.	998001 998004 998002 998005 998003 4 - 1 6 KWH FUSION CORE LITHIUM ION 5 KW PER MOTOR PROPRIETARY ELECTRIC TRANSAXLES 8 MPH / 4MPH (LOW SPEED) - 11 MPH / 5.5 MPH (HIGH SPEED) 7 GA. STEEL X-FACTOR* 3 DECK 3 18,000 CAST ALUMINUM SERVICEABLE BOTTOM BEARING ELECTRIC DC BRUSHLESS MOTORS 48 IN. SZIN. 60 SIDE REAR SIDE REAR SIDE 1.5 IN 5.0 IN. 15 FIXED, GREASABLE CASTER FORK TUBES SMOOTH 13 X 6.5-6 SEMI-PNEUMATIC 20 X 10.5-8 TURF 1204 LBS. 1203 LBS. 1240 LBS. 1236 LBS. 1265 LBS. 74.5 IN. 74.5 IN. 74.5 IN. 50 IN. 50 IN. 56 IN. 54 IN. 63 IN.

MULCHING KIT, OCDB KIT, HEADLIGHT KIT, TRIMMER MOUNT KIT, PACK BLOWER MOUNT KIT, BUCKET MOUNT KIT, REAR TWEEL KIT, HIGH LIFT BLADES, BEACON LIGHT KIT, GRASS CATCHER

PRO-STANCE®	32	36	48	52	52	60	60
MODEL NUMBER	994157	994149	994161	994162	994163	994164	994165
ENGINE	KAWASAKI* FS600V	KAWASAKI° FS600V	KAWASAKI* FX730V	KAWASAKI* FX730V	KAWASAKI° FT730V-EFI	KAWASAKI* FX730V	KAWASAKI° FT730V-E
HORSEPOWER	18	3.5	23.5 HP	23.5 HP	26 HP	23.5 HP	26 HP
DISPLACEMENT	603	CC	726 CC	726 CC	726 CC	726 CC	726 CC
DRIVE SYSTEM	HYDRO-GEA	AR* ZT-3100			HYDRO-GEAR® ZT-3400		
FUEL CAPACITY	6 0	6AL			9 GAL		
GROUND SPEED (Forward/Reverse)	8 MPH	/ 3 MPH			9 MPH / 4 MPH		
DECK							
DECK MATERIAL				7 GA.			
DECK CONSTRUCTION				FABRICATED			
NUMBER OF SPINDLES		2			3		
BLADE TIP SPEED (FPM)	18,:	220			18,000		
SPINDLE HOUSING MATERIAL		FORGED ALUMINUM					
SPINDLE BEARINGS		BALL BEARING					
DECK ENGAGEMENT				OGURA 2.75 ELECTRIC CLUTC	Н		
DECK LIFT SYSTEM				MANUAL			
CUTTING WIDTH	32 IN.	36 IN.	48 IN.	52 IN.	52 IN.	60 IN.	60 IN.
CUTTING HEIGHTS				1.5 IN 5.0 IN.			
CUTTING POSITIONS				15			
WHEELS							
FRONT AXLE				RIGID			
FRONT	11 X 4.00-5 SE	MI-PNEUMATIC			13 X 6.50-6 SEMI-PNEUMATIC		
REAR	36": 18 X 8.5	50-8 RADIAL			20 X 10.50 - 8 RADIAL		
MACHINE							
WEIGHT	750 LBS.	784 LBS.	995 LBS.	1015 LBS.	1015 LBS.	1043 LBS.	1048 LBS.
LENGTH	59.5 IN.	59.5 IN.	60.63 IN.	60.63 IN.	60.63 IN.	62 IN.	62 IN.
WIDTH (w/o CHUTE)	33.5 IN.	36.5 IN.	50 IN.	55.5 IN.	55.5 IN.	63 IN.	63 IN.
WIDTH (w/ CHUTE)	49 IN.	49 IN.	62.25 IN.	67.75 IN.	67.75 IN.	75.25 IN.	75.25 IN.
HEIGHT				48 IN.			·
WARRANTY							
UNIT	5	YEAR / 1000 HOUR COMMERC	IAL / NO HOUR LIMIT FIRST 2 Y	EARS - SEE YOUR PROFESSIO	NAL GRAVELY® DEALER FOR C	OMPLETE WARRANTY DETA	ILS
DECK SHELL & FRAME				LIMITED LIFETIME			

MULCHING KIT, OCDB KIT, HEADLIGHT KIT, TRIMMER MOUNT KIT, PACK BLOWER MOUNT KIT, BUCKET MOUNT KIT, REAR TWEEL KIT, LASEREDGE BLADES, TUNE UP KIT

Z-STANCE®	32	48	52		
MODEL NUMBER	994160	994159	994158		
ENGINE	KAWASAKI® FS600V	KAWASAI	, KI® FS65 V		
HORSEPOWER	18.5 HP	22	HP		
DISPLACEMENT	603 CC	720	6 CC		
DRIVE SYSTEM		HYDRO-GEAR® ZT-3100			
FUEL CAPACITY		4.5 GAL.			
GROUND SPEED (Forward/Reverse)		7 MPH / 3 MPH			
DECK					
DECK MATERIAL	7 GA.	10	GA.		
DECK CONSTRUCTION	X-FACTOR® II	X-FAC	TOR® 3		
NUMBER OF SPINDLES	2	3			
BLADE TIP SPEED (FPM)	18,000	18,000	18,000		
SPINDLE HOUSING MATERIAL		FORGED ALUMINUM			
SPINDLE SHAFT	STEEL				
SPINDLE BEARINGS		BALL BEARING			
DECK ENGAGEMENT		ELECTRIC CLUTCH			
DECK LIFT SYSTEM		MANUAL			
CUTTING WIDTH	32 IN.	48 IN.	52 IN.		
CUTTING HEIGHTS	2.0 IN 5.0 IN.	1.5 IN.	- 5.0 IN.		
CUTTING POSITIONS	13	1	5		
WHEELS					
FRONT		11 X 5-6 PNEUMATIC			
REAR		20 X 6.50 - 8 TURF			
MACHINE					
WEIGHT	669 LBS.	744 LBS.	763 LBS.		
LENGTH	65.5 IN.	65.5 IN.	65.5 IN.		
WIDTH (w/o CHUTE)	32.8 IN.	49.5 IN.	55 IN.		
WIDTH (w/ CHUTE)	44.8 IN.	61 IN.	66.75 IN.		
HEIGHT		47.5 IN.			
WARRANTY					
UNIT		4 YEAR / 500 HOUR COMMERCIAL			
ATTACHMENTS & ACCESSORIES					

MULCHING KIT, OPERATOR CONTROLLED DISCHARGE BAFFLE, HEADLIGHT KIT, TWEEL KIT, BLADE KIT, GRASS CATCHER

PRO-WALK®	36	48	52	60		
MODEL NUMBER	988184	988185	988186	988187		
ENGINE	KAWASAKI° FS481V	KAWASAKI° FS600V	KAWASAKI° FS600V	KAWASAKI° FS691V		
HORSEPOWER	14.5 HP	18.5 HP	18.5 HP	23 HP		
DISPLACEMENT	603 CC	603 CC	603 CC	726 CC		
DRIVE SYSTEM		HYDRO-GE	AR° ZT-2800			
FUEL CAPACITY		5.8	GAL.			
GROUND SPEED (Forward/Reverse)		8 MPH .	3 MPH			
DECK						
DECK MATERIAL		10	GA.			
DECK CONSTRUCTION		FABRI	CATED			
NUMBER OF SPINDLES	2	3	3	3		
BLADE TIP SPEED (FPM)	18,000					
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM					
SPINDLE BEARINGS	BALL BEARING					
DECK ENGAGEMENT	OGURA GT1A CLUTCH					
DECK LIFT SYSTEM	MANUAL					
CUTTING WIDTH	36 IN	48 IN	52 IN.	60 IN.		
CUTTING HEIGHTS	1.5 IN - 4.5 IN	1.5 IN - 5.0 IN	1.5 IN - 5.0 IN	1.5 IN - 5.0 IN		
CUTTING POSITIONS (1/4 IN. Increments)	13	15	15	15		
WHEELS						
FRONT AXLE		N	/A			
FRONT WHEELS		11 X 4-5 SEM	-PNEUMATIC			
REAR WHEELS	21 X 7-10		20 X 8-10			
MACHINE						
WEIGHT	701 LBS	740 LBS	770 LBS	795 LBS		
LENGTH	64 IN	69 IN	71 IN	71.8 IN		
WIDTH (w/o CHUTE)	36.8 IN	50.1 IN	55.5 IN	63 IN		
WIDTH (w/ CHUTE)	48.3 IN	62.2 IN	67.6 IN	75.1 IN		
HEIGHT		45	IN			
WARRANTY						
UNIT		4 YEAR / 750 HOUR - NO H	OUR LIMIT FIRST 2 YEARS			
DECK SHELL & FRAME		N	'A			

MULCHING KIT, GRASS COLLECTOR, SINGLE WHEEL SULKY, TWO WHEEL SULKY, HEADLIGHT KIT, OCDB KIT, LASEREDGE BLADE KIT

ZT X	42	42	48	52	52		
MODEL NUMBER	918007	918008	918009	918010	918011		
ENGINE	KOHLER° KT730	KAWASAKI* FR651V	KAWASAKI* FR651V	KOHLER° KT730	KAWASAKI® FR691V		
HORSEPOWER	23 HP	21.5 HP	21.5 HP	23 HP	23 HP		
DISPLACEMENT	725 CC	726 CC	726 CC	725 CC	726 CC		
DRIVE SYSTEM		Н	YDRO-GEAR® SERVICEABLE EZT® TRANSAXL	ES			
FUEL CAPACITY		3.5 GAL					
GROUND SPEED (Forward/Reverse)			7 MPH / 3 MPH				
DECK	'						
DECK MATERIAL			11 GA. STEEL				
DECK CONSTRUCTION			FABRICATED X-FACTOR®				
NUMBER OF SPINDLES		3					
BLADE TIP SPEED (FPM)		18,000					
SPINDLE HOUSING MATERIAL		FORGED ALUMINUM					
DECK ENGAGEMENT		ELECTRIC WARNER					
DECK LIFT SYSTEM		FOOT OPERATED					
CUTTING WIDTH	42 IN.	42 IN.	48 IN.	52 IN.	52 IN.		
CUTTING HEIGHT			1.5 IN 4.5 IN.				
CUTTING POSITIONS		13					
WHEELS							
FRONT			11 X 6 - 5 SMOOTH PNEUMATIC				
REAR	20 X 8 - 8 K808 AGGRES	20 X 8 - 8 K808 AGGRESIVE TREAD TURF TIRES 20 X 10 - 8 K808 AGGRESIVE TREAD TURF TIRES					
FEATURES							
SEAT	22 IN. PLUSH HIGH BACK W/ARM RESTS & SEAT SLIDER STANDARD						
CONTROL ARMS	TOOLLESS QUICK ADJUST						
LIGHTING	DUAL HIGH INTENSITY LED						
USB PORT	DUAL USB-A						
FLOOR PLATE	TOOLLESS FLIP UP WITH ACCESSORY TRAY						
HOUR METER	STANDARD						
MACHINE	'						
WEIGHT	669 LBS.	667 LBS.	679 LBS.	691 LBS.	695 LBS.		
LENGTH	74.5 IN.	74.5 IN.	74.5 IN.	74.5 IN.	74.5 IN.		
WIDTH (w/o CHUTE)	45.1 IN.	45.1 IN.	51.1 IN.	55.6 IN.	55.6 IN.		
WIDTH (w/ CHUTE)	56.2 IN.	56.2 IN.	62.3 IN.	66.7 IN.	66.7 IN.		
HEIGHT		46 IN.					
WARRANTY							
UNIT		3 YEARS OR 300 HOURS - SEE YO	UR PROFESSIONAL GRAVELY® DEALER FOI	R COMPLETE WARRANTY DETAILS			
ATTACHMENTS & ACCESSORIES	·						

2-BUCKET NON-POWERED BAGGER, POWERED BAGGER CONVERSION KIT, MULCH KIT, SEAT ISOLATOR KIT, TRAILER HITCH KIT, LAWN STRIPING KIT, DECK LIFT SPRING ASSIST KIT, TRANSPORT LOCK KIT, TOOL HOLDER, KICK MAT, 8" WHEEL COVERS, EQUIPMENT COVER, SEAT COVER, CAMO SEAT COVER, LASEREDGE BLADE KIT, ENTRY ASSIST HANDLE KIT, KAWASAKI TUNE UP KIT, KOHLER TUNE UP KIT

ZT XL	42	48	52	52	60	
MODEL NUMBER	918012	918013	918014	918015	918016	
NGINE	KAWASAKI® FR651V	KAWASAKI® FR691V	KOHLER® KT740 SERIES	KAWASAKI® FR691V	KAWASAKI® FR730V	
IORSEPOWER	21.5 HP	23 HP	25 HP	23 HP	24 HP	
DISPLACEMENT	726 CC	726 CC	725 CC	726 CC	726 CC	
DRIVE SYSTEM	HYDRO-GEAR® ZT-2800® TRANSAXLES					
UEL CAPACITY	3.5 GAL					
GROUND SPEED (Forward/Reverse))			7 MPH / 3 MPH			
DECK						
DECK MATERIAL	11 GA. STEEL					
DECK CONSTRUCTION			FABRICATED X-FACTOR®			
IUMBER OF SPINDLES	3					
BLADE TIP SPEED (FPM)	18,000					
PINDLE HOUSING MATERIAL	FORGED ALUMINUM					
DECK ENGAGEMENT	ELECTRIC WARNER					
DECK LIFT SYSTEM	FOOT OPERATED					
CUTTING WIDTH	42 IN.	48 IN.	52 IN.	52 IN.	60 IN.	
CUTTING HEIGHT	1.5 IN 4.5 IN.					
CUTTING POSITIONS	13					
VHEELS						
RONT	11 X 6 - 5 SMOOTH PNEUMATIC					
REAR	20 X 8 - 8 K3012 AGGRESIVE TREAD TURF TIRES 20 X 10 - 8 K3012 AGGRESIVE TREAD TURF TIRES					
EATURES						
EAT	22 IN PLUSH HIGH BACK W/ PADDED ARM RESTS AND SEAT ISOLATION					
ONTROL ARMS	TOOL-LESS QUICK ADJUST					
IGHTING	DUAL HIGH INTENSITY LED					
JSB PORT	DUAL USB-A					
LOOR PLATE	TOOL- LESS FLIP UP WITH ACCESSORY TRAY					
IOUR METER	STANDARD					
MACHINE						
VEIGHT	675 LBS	689 LBS	701 LBS	705 LBS	725 LBS	
ENGTH	74.5 IN.	74.5 IN.	74.5 IN.	74.5 IN.	74.5 IN.	
VIDTH (w/o CHUTE)	45.1 IN.	51.1 IN.	55.6 IN.	55.6 IN.	63.1 IN.	
VIDTH (w/ CHUTE)	56.2 IN.	62.3 IN.	66.7 IN.	66.7 IN.	74.2 IN.	
IEIGHT	47 IN.					

ATTACHMENTS & ACCESSORIES

2-BUCKET NON-POWERED BAGGER, POWERED BAGGER CONVERSION KIT, MULCH KIT, SEAT ISOLATOR KIT, TRAILER HITCH KIT, LAWN STRIPING KIT, DECK LIFT SPRING ASSIST KIT, TRANSPORT LOCK KIT, TOOL HOLDER, KICK MAT, 8" WHEEL COVERS, EQUIPMENT COVER, SEAT COVER, CAMO SEAT COVER, LASEREDGE BLADE KIT, ENTRY ASSIST HANDLE KIT, KAWASAKI TUNE UP KIT, KOHLER TUNE UP KIT

ZT HD	44	48	48	52	52	60	60
MODEL NUMBER	991266	991268	991274	991270	991276	991272	991278
ENGINE	KAWASAKI° FR651V	KAWASAKI° FR691V	KOHLER® KT740	KAWASAKI* FR691V	KOHLER® KT740	KAWASAKI° FR730V	KOHLER® KT745
HORSEPOWER	21.5 HP	23 HP	25 HP	23 HP	25 HP	24 HP	26 HP
DISPLACEMENT	726 CC	726 CC	725 CC	726 CC	725 CC	726 CC	725 CC
DRIVE SYSTEM		HYDRO-GEAR* ZT-3100* TRANSAXLES					
FUEL CAPACITY		5.0 GAL.					
GROUND SPEED (Forward/Reverse)				8 MPH / 4 MPH			
DECK	'						
DECK MATERIAL		10 GA.					
DECK CONSTRUCTION				FABRICATED X-FACTOR® 3			
NUMBER OF SPINDLES		3					
BLADE TIP SPEED (FPM)	18,576	18,576	18,576	18,136	18,136	18,464	18,464
SPINDLE HOUSING MATERIAL		FORGED ALUMINUM					
SPINDLE BEARINGS		BALL BEARING					
DECK ENGAGEMENT		ELECTRIC WARNER					
DECK LIFT SYSTEM				FOOT OPERATED			
CUTTING WIDTH	44 IN.	48 IN.	48 IN.	52 IN.	52 IN.	60 IN.	60 IN.
CUTTING HEIGHT				1.5 IN 5.0 IN.			
CUTTING POSITIONS		15					
WHEELS							
FRONT				13 X 6.5-6 SMOOTH PNEUMATIO			
REAR		22 X 10-12 TURF 22 X 10.5-12 TURF 22 X 12-12 TURF				12 TURF	
FEATURES							
SEAT		HIGH BACK COMFORT W/ SEAT ISOLATION & PADDED ARM RESTS					
HOUR METER		STANDARD					
MACHINE							
WEIGHT	794 LBS.	802 LBS.	796 LBS.	817 LBS.	804 LBS.	841 LBS.	843 LBS.
LENGTH	79 IN.	79 IN.	79 IN.	79 IN.	79 IN.	79 IN.	79 IN.
WIDTH (w/o CHUTE)	47.6 IN.	50.8 IN.	50.8 IN.	56.2 IN.	56.2 IN.	63.7 IN.	63.7 IN.
WIDTH (w/ CHUTE)	58.8 IN.	61.9 IN.	61.9 IN.	67.3 IN.	67.3 IN.	74.8 IN.	74.8 IN.
HEIGHT		47 IN.					
WARRANTY							
UNIT		4 YEARS C	R 500 HOURS - SEE YOUR PRO	DFESSIONAL GRAVELY® DEALE	ER FOR COMPLETE WARRAN	TY DETAILS	
ATTACHMENTS & ACCESSORIES	'						

SEAT SPRING KIT, FOLDING ROPS KIT, TRAILER HITCH KIT, POWERED BAGGER KIT, LOWER ROPS BAGGER MOUNT, OCDB KIT, MULCHING KIT, HEADLIGHT KIT, STRIPING KIT, SUNSHADE KIT, SUSPENSION SEAT KIT, FRONT CASTOR SUSPENSION FORKS, REAR TWEEL KIT, SEMI-PNEUMATIC FRONT TIRE KIT, AGGRESSIVE TIRE KIT, WHEEL COVER KIT, LASEREDGE BLADES, TUNE UP KIT

ZT HD STEALTH®	52
MODEL NUMBER	991271
ENGINE	KAWASAKI* FR691V
HORSEPOWER	23 HP
DISPLACEMENT	726 CC
DRIVE SYSTEM	HYDRO-GEAR* ZT-3100* TRANSAXLES
FUEL CAPACITY	5.0 GAL.
GROUND SPEED (Forward/Reverse)	8 MPH / 4 MPH
DECK	
DECK MATERIAL	10 GA.
DECK CONSTRUCTION	FABRICATED X-FACTOR® 3
NUMBER OF SPINDLES	3
BLADE TIP SPEED (FPM)	18,136
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM
SPINDLE BEARINGS	BALL BEARING
DECK ENGAGEMENT	ELECTRIC WARNER
DECK LIFT SYSTEM	FOOT OPERATED
CUTTING WIDTH	52 IN.
CUTTING HEIGHT	1.5 IN 5.0 IN.
CUTTING POSITIONS	15
WHEELS	
FRONT	13 X 6.5-6 SMOOTH PNEUMATIC
REAR	22 X 11 - 10 KENDA 3012 AGGRESSIVE TREAD TURF
FEATURES	
SEAT	HIGH BACK, ONE OF A KIND SEAT BUILT FOR COMFORT INCLUDING SEAT ISOLATION AND PADDED ARM RESTS
HOUR METER	STANDARD
MACHINE	
WEIGHT	819 LBS.
LENGTH	79 IN.
WIDTH (w/o CHUTE)	56.2 IN.
WIDTH (w/ CHUTE)	67.3 IN.
HEIGHT	47 IN.
WARRANTY	
UNIT	4 YEARS OR 500 HOURS - SEE YOUR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE WARRANTY DETAILS
ATTACHMENTS & ACCESSORIES	

SEAT SPRING KIT, FOLDING ROPS KIT, TRAILER HITCH KIT, POWERED BAGGER KIT, LOWER ROPS BAGGER MOUNT, OCDB KIT, MULCHING KIT, HEADLIGHT KIT, STRIPING KIT, SUNSHADE KIT, SUSPENSION SEAT KIT, FRONT CASTOR SUSPENSION FORKS, REAR TWEEL KIT, SEMI-PNEUMATIC FRONT TIRE KIT, AGGRESSIVE TIRE KIT, WHEEL COVER KIT, LASEREDGE BLADES. TUNE UP KIT





VISIT US ONLINE AT GRAVELY.COM

Registered trademark and ™ trademark of AriensCo. Kohler', Kawasaki', Yamaha', Subaru' and Hydro-Gear' are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit www.gravely.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2023 AriensCo. All rights reserved. 2023

· GRAVELY:

