

**GRAVELY**

**PRO-TURN**

**600**

## MEET YOUR NEW EMPLOYEE OF THE MONTH.

When you add a Pro-Turn 600 to your crew,  
you cut faster and more efficiently,  
handling more work in less time.

**5YR**  
FIVE YEAR OR 1500 HOUR  
WARRANTY



### DIAL-A-HEIGHT

This lets the operator easily adjust  
the deck height by quarter-inch increments.

### PARKER HTG TRANSMISSION

Warranty that matches the machine warranty and allows up to 15 mph  
operation. Making the Pro-Turn 600 a very efficient mower for any crew  
trying to get work out of every daylight hour.

### X-FACTOR® 3 DECK

The deck has been completely redesigned for better grass dispersion.  
Its new look is constructed from 7-gauge steel to deliver years of  
solid performance.

### OPERATOR POD SYSTEM

Separates the operator from the mower's bouncing and jostling. You'll feel  
like you're floating as you mow faster and more comfortably,  
without sacrificing control.



**52"**

#### MODEL - 992505

350HP / Kawasaki® FX1000V Engine

**60"**

#### MODEL - 99201

35 HP / Kawasaki® FX1000V Engine

#### MODEL - 992503

38.5 HP / Kawasaki® FX1000V EFI Engine

**72"**

#### MODEL - 992502

35 HP / Kawasaki® FX1000V Engine

#### MODEL - 992504

38.5 HP / Kawasaki® FX1000V EFI Engine



**MADE  
IN THE**

**UNITED STATES**

WITH GLOBALLY SOURCED PARTS



# PRO-TURN® 600



See your professional Gravely® dealer for complete warranty details.

|                                                     | 652                                                                                                                               | 660               | 660                   | 672               | 672                   |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------|-----------------------|-------------------|-----------------------|
| MODEL NUMBER                                        | 992505                                                                                                                            | 992501            | 992503                | 992502            | 992504                |
| ENGINE                                              | KAWASAKI® FX1000V                                                                                                                 | KAWASAKI® FX1000V | KAWASAKI® FX1000V-EFI | KAWASAKI® FX1000V | KAWASAKI® FX1000V-EFI |
| HORSEPOWER                                          | 35 HP                                                                                                                             | 35 HP             | 38.5 HP               | 35 HP             | 38.5 HP               |
| DISPLACEMENT                                        | 999 CC                                                                                                                            | 999 CC            | 999 CC                | 999 CC            | 999 CC                |
| DRIVE SYSTEM                                        | PARKER HTG TRANSMISSION                                                                                                           |                   |                       |                   |                       |
| FUEL CAPACITY                                       | 12.7 GAL                                                                                                                          |                   |                       |                   |                       |
| GROUND SPEED<br>(APPROX. Mph) (Forward/<br>Reverse) | 15 MPH / 6 MPH                                                                                                                    |                   |                       |                   |                       |
| DECK                                                |                                                                                                                                   |                   |                       |                   |                       |
| DECK MATERIAL                                       | 7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT                                                                                    |                   |                       |                   |                       |
| DECK CONSTRUCTION                                   | X-FACTOR® 3 DECK                                                                                                                  |                   |                       |                   |                       |
| NUMBER OF SPINDLES                                  | 3                                                                                                                                 |                   |                       |                   |                       |
| BLADE TIP SPEED (FPM)                               | 18,000                                                                                                                            |                   |                       |                   |                       |
| SPINDLE HOUSING MATERIAL                            | LARGE SERVICEABLE FORGED ALUMINUM                                                                                                 |                   |                       |                   |                       |
| SPINDLE BEARINGS                                    | DOUBLE ROLLER BEARINGS                                                                                                            |                   |                       |                   |                       |
| DECK ENGAGEMENT                                     | OGURA® GT3.5 ELECTRIC CLUTCH                                                                                                      |                   |                       |                   |                       |
| CUTTING WIDTH                                       | 52 IN                                                                                                                             | 60 IN             | 60 IN                 | 72 IN             | 72 IN                 |
| CUTTING HEIGHTS                                     | 1.0 IN - 5.5 IN                                                                                                                   |                   |                       |                   |                       |
| CUTTING POSITIONS                                   | 19                                                                                                                                |                   |                       |                   |                       |
| WHEELS                                              |                                                                                                                                   |                   |                       |                   |                       |
| FRONT AXLE                                          | FIXED, GREASEABLE CASTER FORK TUBES                                                                                               |                   |                       |                   |                       |
| FRONT                                               | SMOOTH 15 X 6-6 SEMI PNEUMATIC                                                                                                    |                   |                       |                   |                       |
| REAR                                                | 26 X 12-16 <del>LOW-PROFILE</del> RADIAL TURF                                                                                     |                   |                       |                   |                       |
| FEATURES                                            |                                                                                                                                   |                   |                       |                   |                       |
| SEAT                                                | HIGH BACK BOLSTERED WITH SUSPENSION OPERATEOR POD SYSTEM                                                                          |                   |                       |                   |                       |
| FOLDABLE ROPS                                       | STANDARD                                                                                                                          |                   |                       |                   |                       |
| MACHINE                                             |                                                                                                                                   |                   |                       |                   |                       |
| WEIGHT                                              | <del>1535</del> LBS                                                                                                               | 1586 LBS          | 1601 LBS              | 1646 LBS          | 1661 LBS              |
| LENGTH                                              | 83 IN                                                                                                                             |                   |                       |                   |                       |
| WIDTH (w/o CHUTE)                                   | 55 IN                                                                                                                             | 63 IN             | 63 IN                 | 75 IN             | 75 IN                 |
| WIDTH (w/ CHUTE)                                    | 63 IN                                                                                                                             | 75 IN             | 75 IN                 | 87 IN             | 87 IN                 |
| HEIGHT (w/ ROPS EXT/DOWN)                           | 71.5 IN / 47.8 IN                                                                                                                 |                   |                       |                   |                       |
| WARRANTY                                            |                                                                                                                                   |                   |                       |                   |                       |
| UNIT                                                | 5 YEAR / 1500 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS - SEE YOUR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE WARRANTY DETAILS |                   |                       |                   |                       |
| DECK SHELL & FRAME                                  | LIMITED LIFETIME                                                                                                                  |                   |                       |                   |                       |

ATTACHMENTS & ACCESSORIES

- MULCHING KIT
- TRAILER HITCH KIT
- LED HEADLIGHT KIT
- STRIPING KIT
- POWERED BAGGER KIT
- OCDB KIT
- SUNSHADE KIT
- REAR TWEEL KIT
- RADIAL DRIVE CONVERSION KIT
- LASEREDGE BLADES
- TUNE UP KIT
- POLY SIDE GRASS CATCHER
- ELECTRIC DECK LIFT
- ENTRY ASSIST HANDLE
- FRONT TWEELS
- GRAVELY EQUIPMENT COVER
- FRONT WEIGHT KIT

