

PLATINUM SERIES



URNS BLANKETS OF SNOW INTO TATTERED RAGS.

When you get behind your Platinum, you'll want to keep going – driveway after driveway. These units were built for high-volume workloads, hence their standard hand-warmers and Super High Output (SHO) impellers. The Platinum Series is loaded with plenty of other features sure to fit your snow removal needs.

My favorite thing about my Ariens is the built-in handwarmers. I go up and down my entire block, the neighbors love me.

*– Michael H.
Superior, WI*

AUTO-TURN™ STEERING

Effortless, zero-degree turning radius.

AUGER

14" auger diameter.

ENGINE

Choose from 3 different types of Ariens engines.

SUPER HIGH OUTPUT IMPELLER (SHO)

Move through heavy, wet snow with ease with our exclusive SHO technology.

DUAL-BELT DRIVE

Exclusive to Ariens, delivers maximum power through tough conditions, plus extended belt life.

HAND WARMERS

Stay warm and comfortable with our premium hand warmers.

ELECTRIC CHUTE CONTROL AVAILABLE

A convenient thumb-controlled joystick makes chute turns quick and effortless with full rotations taking only 1.5 seconds.

EFI ENGINE AVAILABLE

Our Electronic Fuel Injection Engine is easy starting, less maintenance, improved efficiency making it ideal for high altitude snow removal.

3 YEAR
LTD. RESIDENTIAL
WARRANTY

90 DAY
LTD. COMMERCIAL
WARRANTY

PRODUCT SPECIFICATIONS

RAPIDTRAK



DESIGNATION	PLATINUM 24 SHO	PLATINUM 24 SHO EFI GREAT LAKES EDITION™	PLATINUM 30 SHO	PLATINUM 28 RAPIDTRAK®	PLATINUM 24 SHO 90TH ANNIVERSARY EDITION
MODEL #	921063	921066	921064	921057	921933
STAGE TYPE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE
ENGINE POWER	369CC (17 FT/LBS)	369CC EFI (17 FT/LBS)	414CC (20 FT/LBS)	369CC (17 FT/LBS)	369CC (17 FT/LBS)
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	TECUMSEH POWER SNOW KING
STARTING SYSTEM	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL
CLEARING WIDTH	24 IN (60.1 CM)	24 IN (60.1 CM)	30 IN (76.2 CM)	28 IN (71.2 CM)	24 IN (60.1 CM)
HOUSING HEIGHT	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)
THROWING DISTANCE	3 - 55 FT (.9 - 16.7 M)	3 - 55 FT (.9 - 16.7 M)	3 - 55 FT (.9 - 16.7 M)	3 - 55 FT (.9 - 16.7 M)	3 - 55 FT (.9 - 16.7 M)
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°
CHUTE ROTATION	QUICK TURN™	ELECTRIC JOYSTICK	QUICK TURN™	QUICK TURN™	QUICK TURN™
DEFLECTOR CONTROL	REMOTE	ELECTRIC	REMOTE	REMOTE	REMOTE
HEADLIGHT	LED	LED	LED	LED	LED
TIRE SIZE	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	5.5 IN WIDE TRACK (14 CM)	16 X 4.8 IN (41 X 12 CM)
TIRE TYPE	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TRACK	DIRECTIONAL SNOW TREAD
STEERING	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN
DRIVE TYPE	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC
SPEEDS	6 FORWARD 2 REVERSE	6 FORWARD 2 REVERSE	6 FORWARD 2 REVERSE	6 FORWARD 2 REVERSE	6 FORWARD 2 REVERSE
GEAR CASE	CAST IRON	CAST IRON	CAST IRON	CAST IRON	CAST IRON
GEAR CASE WARRANTY	5YR RES, 1YR COMM	5 YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER TYPE	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED
SKID SHOES	POLY REVERSIBLE	POLY REVERSIBLE	POLY REVERSIBLE	POLY REVERSIBLE	POLY REVERSIBLE
SCRAPER BAR	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM
LENGTH	58.3 IN (148.1 CM)	58.3 IN (148.1 CM)	58.3 IN (148.1 CM)	60.3 IN (153.2 CM)	58.3 IN (148.1 CM)
WIDTH	26.4 IN (67.1 CM)	26.4 IN (67.1 CM)	32.4 IN (82.3 CM)	30.2 IN (76.7 CM)	26.4 IN (67.1 CM)
HEIGHT	45.9 IN (116.6 CM)	45.9 IN (116.6 CM)	45.9 IN (116.6 CM)	46.6 IN (118.4 CM)	45.9 IN (116.6 CM)
WEIGHT	286 LBS (129.7 KG)	286 LBS (129.7 KG)	294 LBS (133.3 KG)	331 LBS (150.1 KG)	286 LBS (129.7 KG)
ACCESSORIES AT A GLANCE	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, DRIFT CUTTER KIT, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER	FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, DRIFT CUTTER KIT, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER



Registered trademark and ™ trademark of AriensCo. Kawasaki®, Kohler® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2021 AriensCo. All rights reserved. 0921

VISIT ARIENS.COM FOR DETAILS

AN **ARIENS|CO** BRAND