

# PROFESSIONAL 21

## SERIES



## JUST WHEN THE SNOW THOUGHT IT WAS DONE TRAVELING FOR THE DAY.

It's a rugged workhorse that is the perfect addition to any commercial snow-clearing fleet. This little beast has ingenious design elements. Like the smart lift handlebar system so you can slide it into your vehicle. Or its open engine for easy access to the oil fill, oil drain, and spark plug. A perfect marriage of form and function, blowing away your expectations along with tons and tons of snow.

When it snows, I'm driving to over 20 properties so my Ariens Professional's handlebar makes loading and unloading easy on my back.

— Shawn H.  
Holland, MI

### NO SWEAT START

Effortless, keyless start sequence featuring an on/off switch helps ensure a successful start in any weather condition.

### EASY OPERATION

Handlebar positions optimize system performance and user comfort.

### STRAIGHTFORWARD CLEARING

Spring-loaded, self-adjusting scraper bar follows the contours of the ground, while a high-wear paddle cleans to the surface.

### SIMPLE MAINTENANCE

Open engine design allows easy access to the oil fill, oil drain, recoil, and spark plug.

### SMART LIFT SYSTEM

Our exclusive handlebar system allows the machine to easily slide into your vehicle with minimal effort.

**3** YEAR  
LTD. RESIDENTIAL  
WARRANTY

**1** YEAR  
LTD. COMMERCIAL  
WARRANTY

## PRODUCT SPECIFICATIONS

DESIGNATION	PROFESSIONAL 21 SSR	PROFESSIONAL 21 SSRC
MODEL #	938024	938025
STAGE TYPE	SINGLE STAGE	SINGLE STAGE
ENGINE POWER	208CC (9.5 FT/LBS)	208CC (9.5 FT/LBS)
ENGINE BRAND	ARIENS AX	ARIENS AX
STARTING SYSTEM	RECOIL	RECOIL
CLEARING WIDTH	21 IN (53.3 CM)	21 IN (53.3 CM)
HOUSING HEIGHT	12.1 IN (30.7 CM)	12.1 IN (30.7 CM)
THROWING DISTANCE	3 - 35 FT (.9 - 10.7 M)	3 - 35 FT (.9 - 10.7 M)
CHUTE TURNING RADIUS	210°	210°
CHUTE ROTATION	MANUAL	REMOTE
DEFLECTOR CONTROL	MANUAL	MANUAL
TIRE SIZE	7.5 X 2 IN (19.1 X 5.1 CM)	7.5 X 2 IN (19.1 X 5.1 CM)
STEERING	SOLID UNLOCKED	SOLID UNLOCKED
DRIVE TYPE	AUGER PROPELLED	AUGER PROPELLED
SPEEDS	1 FORWARD	1 FORWARD
AUGER DIAMETER	8.375 IN (21.3 CM)	8.375 IN (21.3 CM)
AUGER TYPE	HIGH-WEAR REINFORCED RUBBER	HIGH-WEAR REINFORCED RUBBER
SCRAPER BAR	PIVOTING SELF-ADJUST	PIVOTING SELF-ADJUST
PRODUCT WARRANTY	3YR RES, 1YR COMM	3YR RES, 1YR COMM
LENGTH	50.8 IN (128.9 CM)	50.8 IN (128.9 CM)
WIDTH	21.2 IN (53.8 CM)	21.2 IN (53.8 CM)
HEIGHT	41.7 IN (105.9 CM)	41.7 IN (105.9 CM)
WEIGHT	87 LBS (39.46 KG)	89 LBS (39.46 KG)
ACCESSORIES AT A GLANCE	FLOOR MAT, SNO-THO COVER	FLOOR MAT, SNO-THO COVER



Registered trademark and ™ trademark of AriensCo. Kawasaki®, Kohler® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2021 AriensCo. All rights reserved. 0921