

PRO-TURN[®]

Z

PROOF THAT SUPERIOR CUT AND SUPERIOR COMFORT CAN COEXIST.

Performance and comfort don't need to be mutually exclusive. The Pro-Turn[®] Z has wrapped them both in a new, bolder look that's packed full of commercial-grade features. But the biggest surprise is it still maintains its attractive baseline price. All-day comfort, an unparalleled cut and Gravely's signature durability make the Pro-Turn Z a no-nonsense workhorse worthy of bearing the Gravely name.

4YR
FOUR YEAR OR 750 HOUR
WARRANTY



INCREASED COMFORT comes from its new high-back seat with more cushion and support.

AN IMPROVED RIDE, thanks to its seat isolation system. It removes the vibrations that can cause fatigue so you can mow in comfort further and longer.

BOLD NEW STYLING updated fenders and rear wrap capture the essence of the Gravely brand.

3100 TRANSAXLES are commercial grade and serviceable for a longer lifespan.

A FABRICATED 10-GAUGE DECK with a 5.5 inch reinforced leading edge to optimum airflow and cutting performance.

CONSTANT BELT TENSION SYSTEM (CBT) minimizes wear and heat while providing enhanced belt life with minimal adjustments.

SUSPENSION FORKS absorb those big impacts so your body doesn't, further improving the ride and decreasing fatigue.

26.5 HP GRAVELY ENGINE and two-stage canister filtration for longer engine life. It's backed by a 4-year, 750 hour warranty.



GRAVELY

	48	52	60
MODEL NUMBER	991254	991256	991258
ENGINE	GRAVELY [®] 764 PRO		
FILTRATION	HEAVY-DUTY AIR CLEANER		
HORSEPOWER	26.5 HP		
DISPLACEMENT	764 CC		
DRIVE SYSTEM	HYDRO-GEAR [®] ZT-3100 TRANSAXLES		
FUEL CAPACITY	5.0 GAL.		
GROUND SPEED (Approx. Mph) [Forward/Reverse]	8 MPH / 4 MPH		
DECK			
DECK MATERIAL	10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT		
DECK CONSTRUCTION	FABRICATED		
NUMBER OF SPINDLES	3		
BLADE TIP SPEED (FPM)	18,000		
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM		
SPINDLE BEARINGS	BALL BEARING		
DECK ENGAGEMENT	ELECTRIC CLUTCH OGURA [®] GT 1.5		
CUTTING WIDTH	48 IN.	52 IN.	60 IN.
CUTTING HEIGHTS	1.0 IN. - 5.0 IN.		
CUTTING POSITIONS	15		
WHEELS			
FRONT AXLE	SUSPENSION, GREASABLE CASTER FORK TUBES		
FRONT	SMOOTH 13 X 6.50-6		
REAR	TURF 22 X 10-12	TURF 22 X 10.5-12	TURF 22 X 12-12
FEATURES			
SAFETY	ANSI CERTIFIED		
SEAT	HIGH BACK COMFORT WITH ISOLATION AND PADDED ARMRESTS		
FOLDABLE ROPS	STANDARD		
MACHINE			
WEIGHT	925 LBS.	931 LBS.	952 LBS.
LENGTH	79 IN.		
WIDTH (W/O CHUTE)	51 IN. / 63 IN.	55 IN. / 67 IN.	63 IN. / 75 IN.
WIDTH (W/ CHUTE)	51 IN. / 63 IN.	55 IN. / 67 IN.	63 IN. / 75 IN.
HEIGHT (W/ ROPS EXT/DOWN)	72 IN. / 52 IN.		
WARRANTY			
UNIT	4 YEAR / 750 HOUR LIMITED		
ATTACHMENTS & ACCESSORIES			
MULCHING KIT, DISCHARGE COVER KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUN SHADE KIT, POWERED BAGGER KIT, OPERATOR CONTROLLED DISCHARGE CHUTE			

