

PRO-TURN[®] 600

**SURPASSING EXPECTATIONS WAS A GIVEN.
OUR GOAL WAS TO REDEFINE THEM.**

Introducing the New Pro-Turn[®] 600, the latest and greatest addition to our lineup of the world's greatest lawnmowers. We've pulled out all the stops to build a commercial machine focused on operator comfort without sacrificing its superior performance, and we wrapped it all up in a sleek new design. You'll cut more acreage faster yet feel less fatigued when you trailer-up for the night. Once you hop on board this new standard for commercial mowers you'll never look back.

5YR
FIVE YEAR OR 1500 HOUR
WARRANTY
NO HOUR LIMIT FOR THE FIRST TWO YEARS
LIMITED LIFETIME DECK SHELL & FRAME



A NEW SUSPENSION SYSTEM is designed to feel like you're part of the machine giving you more control and comfort by removing bumps and jolts, even while mowing at higher speeds. That means less fatigue by the end of the day. It's also specially designed to self-adjust for less maintenance.

A NEW DECK has been completely redesigned for better grass dispersion. Its new look is constructed from seven-gauge steel to deliver years of solid performance.

NEW STYLE has the Pro-Turn 600 looking just as good as the lawns it mows.

LARGE DIAMETER TIRES on both the front and rear provide a smoother ride and more traction on varying conditions.

DIAL-A-HEIGHT lets the operator easily adjust the deck height by quarter-inch increments.

AUTOMOTIVE-STYLE TUBULAR FRAME is unique to the mowing industry. It increases durability by withstanding force from any direction. This high-strength, premium frame is positioned with a lower center of gravity to improve stability while mowing on hillsides.



GRAVELY[®]

PRO-TURN® 600



	652	660	660	672	672
MODEL NUMBER	992500	992501	992503	992502	992504
ENGINE	KAWASAKI® FX850	KAWASAKI® FX1000	KAWASAKI® FX1000 EFI	KAWASAKI® FX1000	KAWASAKI® FX1000 EFI
HORSEPOWER	27 HP	35 HP	38.5 HP	35 HP	38.5 HP
DISPLACEMENT	852 CC	999 CC	999 CC	999 CC	999 CC
DRIVE SYSTEM	PARKER HTG TRANSMISSION				
FUEL CAPACITY	12.7 GAL.				
GROUND SPEED (Approx. Mph) (Forward/Reverse)	15 MPH / 7 MPH				
DECK					
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT				
DECK CONSTRUCTION	FABRICATED X-FACTOR III				
NUMBER OF SPINDLES	3				
BLADE TIP SPEED (FPM)	18,000				
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM				
SPINDLE BEARINGS	BALL BEARING				
DECK ENGAGEMENT	ELECTRIC CLUTCH OGURA® GT 3.5				
CUTTING WIDTH	52 IN.	60 IN.	60 IN.	72 IN.	72 IN.
CUTTING HEIGHTS	1.0 IN. - 5.5 IN.				
CUTTING POSITIONS	19				
WHEELS					
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES				
FRONT	SMOOTH 15 X 6-6 SEMI PNEUMATIC				
REAR	RADIAL TURF 26 X 12-16				
FEATURES					
SEAT	HIGH BACK BOLSTERED WITH SUSPENSION POD SYSTEM				
FOLDABLE ROPS	STANDARD				
MACHINE					
WEIGHT	1486 LBS.	1631 LBS.	1631 LBS.	1815 LBS.	1815 LBS.
LENGTH	83 IN.				
WIDTH (W/O CHUTE)	53 IN.	63 IN.	63 IN.	75 IN.	75 IN.
WIDTH (W/ CHUTE)	63 IN.	75 IN.	75 IN.	87 IN.	87 IN.
HEIGHT (W/ ROPS DOWN)	47.8 IN				
HEIGHT (W/ ROPS UP)	71.5 IN.				
WARRANTY					
UNIT	5 YEAR / 1500 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS				
DECK SHELL & FRAME	LIMITED LIFETIME				
ATTACHMENTS & ACCESSORIES					
MULCHING KIT, 3-BUCKET BAGGER, MULCHING KIT, OCDB KIT, TRAILER HITCH KIT, LED HEADLIGHT KIT, TWEEL TIRE KIT, LASEREDGE BLADE KITS, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, 3-BUCKET BAGGER (12BU.)					

