PRO-TURN®

ZX

BIG RETURNS ON A SMALL INVESTMENT.

The Pro-Turn® ZX is the mower that's cracked the code for delivering great performance at a great value. Its solid construction will tackle the toughest commercial jobs and leave a beautifully manicured lawn in its wake. Don't let its price-point fool you, this mower was built to not just exceed expectations but to redefine them.





INCREASED COMFORT comes from its new high-back seat that delivers more cushion and support.

UPDATED FENDERS and rear wrap give the HD a bold new style upgrade so it looks as great as it mows.

A FABRICATED 10-GAUGE DECK with a 5.5 inch reinforced leading edge to optimum airflow and cutting performance.

CONSTANT BELT TENSION SYSTEM (CBT)

minimizes wear and heat while providing enhanced belt life with minimal adjustments.

AAN AUTOMOTIVE-STYLE TUBULAR FRAME,

unique to the mowing industry, increases durability by withstanding force from any direction. This high-strength, premium frame is positioned with a lower center of gravity to improve stability while mowing on hillsides.

ROPS COMES STANDARD for increased operator safety.

SUSPENSION FORKS absorb those big impacts so your body doesn't, further improving the ride and decreasing fatigue.

3200 TRANSAXLES are more heavy-duty and can handle higher speeds. They're commercial grade and serviceable for a longer lifespan.







NGINE KAWASAKI® FX491V KAWASAKI® FX491V CREEPOWER 22 HP 22 HP 23.5 HP 25.6 CC 72.6 CC		48	52	60
SEPLOWER 22 HP 22 HP 23.5 HP	MODEL NUMBER	991260	991262	991264
SPLACEMENT 726 CC	ENGINE	KAWASAKI® FX691V	KAWASAKI® FX691V	KAWASAKI® FX730
NEW SYSTEM	IORSEPOWER	22 HP	22 HP	23.5 HP
SUBSTREED SUBPRISHING S	ISPLACEMENT	726 CC	726 CC	726 CC
ROUND SPEED Approx. Mphil [Forward/Reverse] ECK ECK ECK MATERIAL 10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT ECK CONSTRUCTION FABRICATED UMBER OF SPINDLES 3 LADE TIP SPEED (FPM) 18,000 PINDLE BEARINGS ECK ENGAGEMENT FORGED ALUMINUM PINDLE BEARINGS ECK ENGAGEMENT ELECTRIC CLUTCH OGURA® GT 1.5 UTTING WIDTH 48 IN. 52 IN. 60 IN. UTTING BEIGHTS 1.5 IN. − 5.0 IN. UTTING POSITIONS 15 FRONT SMOOTH 13 X 6.50 - 6 EAR TURF 22 X 10 - 12 TURF 22 X 10.5 - 12 TURF 22 X 10.5 - 12 EARTH SHOP STANDARD ACHINE EARTH PASS STANDARD ACHINE EEGHT 925 LBS. 931 LBS. 952 LBS. ENGIT 97 IN. ###################################	RIVE SYSTEM	HYDRO-GEAR® ZT-3200 TRANSAXLES		
	UEL CAPACITY	5.0 GAL.		
### ### ### ### ### ### ### ### ### ##	ROUND SPEED Approx. Mph] (Forward/Reverse)	8.5 MPH / 4 MPH		
ECK CONSTRUCTION FABRICATED UMBER OF SPINDLES 3 LADE TIP SPEED (FPM) 18,000 PINDLE BEARINGS BALL BEARING PINDLE BEARINGS BALL BEARING ECK ENGAGEMENT ELECTRIC CUTCH OGURA® GT 1.5 UTTING WIDTH 48 IN. 52 IN. 60 IN. UTTING WIDTH 48 IN. 52 IN. 60 IN. UTTING POSITIONS 15 THEELS PRONT AXLE SUSPENSION, GREASABLE CASTER FORK TUBES RRONT SMOOTH 13 X 6.50-6 EAR TURF 22 X 10-12 TURF 22 X 10.5-12 TURF 22 X 12-4 EATURES EAT HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMRESTS DIDABLE ROPS STANDARD LACHINE LEIGHT 925 LBS. 931 LBS. 952 LBS. LEIGHT 97 IN. LIDTH IW/O CHUTE] 51 IN. 55 IN. 63 IN. LIDTH IW/O CHUTE] 63 IN. 67 IN. TO SIN. 79 IN. LEIGHT (W, ROPS EXT/DOWN) 79 IN. 76 IN. LEIGHT (W, ROPS EXT/DOWN) 79 IN. 76 IN.	ECK			
Bubber of SPINDLES 3 LADE TIP SPEED (FPM) 18,000 PINDLE HOUSING MATERIAL FORGED ALUMINUM PINDLE BEARINGS BALL BEARING ECK ENGAGEMENT ELECTRIC CLUTCH OBURA* GT 1.5 UTTING WIDTH 48 IN. 52 IN. 60 IN. UTTING POSITIONS 15 15 IN 5.0 IN. UTTING POSITIONS 15 FRONT AXLE SUSPENSION, GREASABLE CASTER FORK TUBES FORM TURE 2X 10-12 TURF 22 X 10-5-12 TURF 22 X 12-12 EAR TURF 22 X 10-12 TURF 22 X 10-5-12 TURF 22 X 12-12 EAT HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMRESTS DID ALB PROPERTY OF THE PRO	ECK MATERIAL	10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT		
Table Pepel Pepe	ECK CONSTRUCTION	FABRICATED		
PINDLE HOUSING MATERIAL FORGED ALUMINUM PINDLE BEARINGS BALL BEARING ECK ENGAGEMENT ELECTRIC CLUTCH OGURA® GT 1.5 UTTING WIDTH 48 IN. 52 IN. 60 IN. UTTING POSITIONS 15 THEELS	UMBER OF SPINDLES	3		
PRINTE BEARINGS BALL BEARING	LADE TIP SPEED (FPM)	18,000		
ECK ENGAGEMENT ELECTRIC CLUTCH OGURA® GT 1.5 UTTING WIDTH 48 IN. 52 IN. 60 IN. UTTING HEIGHTS 1.5 IN 5.0 IN. UTTING POSITIONS THEELS SUSPENSION, GREASABLE CASTER FORK TUBES RONT SMOOTH 13 X 6.50-6 EAR TURF 22 X 10-12 TURF 22 X 10.5-12 TURF 22 X 12-2 EAT HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMESTS DIDABLE ROPS STANDARD IACHINE JEIGHT 925 LBS. 931 LBS. 952 LBS. ENGTH 79 IN. JOTH (W/O CHUTE) 51 IN. 55 IN. 63 IN. JOTH (W/ CHUTE) 63 IN. 67 IN. 75 IN. JEIGHT (W/ ROPS EXT/DOWN) 79 IN. / 49 IN.	PINDLE HOUSING MATERIAL	FORGED ALUMINUM		
UTING WIDTH 48 IN. 52 IN. 52 IN. 60 IN. UTING HEIGHTS 1.5 IN 5.0 IN. UTING POSITIONS 15 WHEELS RONT AXLE SUSPENSION, GREASABLE CASTER FORK TUBES RONT AXLE SUSPENSION, GREASABLE CASTER FORK TUBES RONT SMOOTH 13 X 6.50-6 EAR TURF 22 X 10-12 TURF 22 X 10.5-12 TURF 22 X 12-4 EATURES EAT HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMESTS DLDABLE ROPS STANDARD IACHINE FEIGHT 925 LBS. 931 LBS. 952 LBS. ENGTH 79 IN. INDIT (W/O CHUTE) 51 IN. 55 IN. 63 IN. INDIT (W/ CHUTE) 63 IN. 63 IN. INDIT (W/ CHUTE) 63 IN. 75 IN. EIGHT (W/ ROPS EXT/DOWN) 79 IN. / 49 IN. IACKRANTY	PINDLE BEARINGS	BALL BEARING		
UTING HEIGHTS 1.5 IN 5.0 IN. UTING POSITIONS 15 THEELS RONT AXLE SUSPENSION, GREASABLE CASTER FORK TUBES RONT SMOOTH 13 X 6.50-6 EAR TURF 22 X 10-12 TURF 22 X 10.5-12 TURF 22 X 12-4 EATURES EAT HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMRESTS DLDABLE ROPS STANDARD IACHINE FEIGHT 925 LBS. 931 LBS. 952 LBS. ENGTH 79 IN. INDIT (W/O CHUTE) 51 IN. 55 IN. 63 IN. INDIT (W/O CHUTE) 63 IN. 63 IN. INDIT (W/ CHUTE) 63 IN. 79 IN. / 49 IN. IACRANTY INDIT (W/ ROPS EXT/DOWN) 79 IN. / 49 IN.	ECK ENGAGEMENT		ELECTRIC CLUTCH OGURA® GT 1.5	
The positions 15	UTTING WIDTH	48 IN.	52 IN.	60 IN.
SUSPENSION, GREASABLE CASTER FORK TUBES	UTTING HEIGHTS		1.5 IN 5.0 IN.	
SUSPENSION, GREASABLE CASTER FORK TUBES	JTTING POSITIONS		15	
SMOOTH 13 X 6.50-6	HEELS			
EAR TURF 22 X 10-12 TURF 22 X 10.5-12 TURF 22 X 12-4 EAT HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMRESTS DIAGHINE ACHINE ACH	RONT AXLE		SUSPENSION, GREASABLE CASTER FORK TUBES	
### HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMRESTS DLDABLE ROPS	RONT	SMOOTH 13 X 6.50-6		
HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMRESTS	REAR	TURF 22 X 10-12	TURF 22 X 10.5-12	TURF 22 X 12-12
OLDABLE ROPS STANDARD IACHINE 791 LBS. 952 LBS. FEIGHT 79 IN. VIDTH (W/O CHUTE) 51 IN. 55 IN. 63 IN. VIDTH (W/ CHUTE) 63 IN. 67 IN. 75 IN. EIGHT (W/ ROPS EXT/DOWN) 79 IN. / 49 IN.	EATURES			
MACHINE	EAT	HIGH BACK COMFORT WITH SUSPENSION AND PADDED ARMRESTS		
/EIGHT 925 LBS. 931 LBS. 952 LBS. ENGTH 79 IN. 79 IN. /IDTH (W/O CHUTE) 51 IN. 55 IN. 63 IN. /IDTH (W/ CHUTE) 63 IN. 67 IN. 75 IN. EIGHT (W/ ROPS EXT/DOWN) 79 IN. / 49 IN.	OLDABLE ROPS	STANDARD		
## 79 IN. ## 70 IN.	MACHINE			
/IDTH (W/O CHUTE) 51 IN. 55 IN. 63 IN. /IDTH (W/ CHUTE) 63 IN. 67 IN. 75 IN. EIGHT (W/ ROPS EXT/DOWN) 79 IN. / 49 IN.	VEIGHT	925 LBS.	931 LBS.	952 LBS.
#IDTH (W/ CHUTE) 63 IN. 67 IN. 75 IN. #IGHT (W/ ROPS EXT/DOWN) 79 IN. / 49 IN. ###################################	ENGTH		79 IN.	
EIGHT (W/ ROPS EXT/DOWN) 79 IN. / 49 IN. JARRANTY	WIDTH (W/O CHUTE)	51 IN.	55 IN.	63 IN.
VARRANTY	VIDTH (W/ CHUTE)	63 IN.	67 IN.	75 IN.
	HEIGHT (W/ ROPS EXT/DOWN)		79 IN. / 49 IN.	
NIT 4 YEAR / 750 HOUR LIMITED	WARRANTY			
	JNIT		4 YEAR / 750 HOUR LIMITED	