

ZT XL

MOW WITH AUTHORITY.

Built for big jobs, the ZT-XL has been redesigned with vibration isolators and a high-back seat to combine professional cut quality with all-day comfort. Out-manuever any obstacle with more deck sizes to meet your demands.

4YR
FOUR YEAR OR 400 HOUR
WARRANTY



FULLY WELDED TUBULAR FRAME this fully fabricated tubular frame is welded into a single piece, providing a strong, stable backbone you won't get from a competitive bolted, multi-sectional frame.

COMMERCIAL ENGINE OPTIONS Kawasaki® provides the same power, durability and dependability trusted by professional cutters every day. Meanwhile, the Kohler® 7000 Series™ with Smart Choke™ technology is ready to run as soon as you turn the key.

11-GAUGE FABRICATED DECK drop this 11-gauge steel deck and it won't let you down. The 1/2-inch-deep design delivers adequate airflow to handle challenging mowing conditions, delivering professional-grade cut quality and durability.

HYDRO-GEAR ZT-2800 TRANSMISSION The Hydro-Gear® ZT-2800 transmission provides increased torque, a smoother ride and longer life.

SEATING COMFORT this plush high-back seat with seat isolation along with cut and sewn armrests ensures upgraded comfort for longer mowing sessions.

TIRES roll right by the competition with 20" drive tires and 11" x 6" front caster wheels – designed to provide better traction, control and handling.



GRAVELY

	42	42	48	52	52	60	60
MODEL NUMBER	915259	915262	915261	915258	915263	915260	915264
ENGINE	KOHLER® 7000 TWIN W/ SMART CHOKE™	KAWASAKI® FR651	KAWASAKI® FR691	KOHLER® 7000 TWIN W/ SMART CHOKE™	KAWASAKI® FR691	KOHLER® 7000 TWIN W/ SMART CHOKE™	KAWASAKI® FR730
HORSEPOWER	24 HP	21.5 HP	23 HP	25 HP	23 HP	26 HP	24 HP
DISPLACEMENT	725 CC	726 CC	726 CC	725 CC	726 CC	725 CC	726 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-2800 TRANSAXLES & 7 IN. FANS						
FUEL CAPACITY	2.8 GAL.						
GROUND SPEED (Approx. Mph) [Forward/Reverse]	7.5 MPH / 3 MPH						
DECK							
DECK MATERIAL	11 GA.						
DECK CONSTRUCTION	FABRICATED						
NUMBER OF SPINDLES	3						
BLADE TIP SPEED (FPM)	17,000						
SPINDLE MATERIAL	STEEL MACHINED						
SPINDLE BEARINGS	SEALED						
DECK ENGAGEMENT	ELECTRIC WARNER®						
DECK LIFT SYSTEM	FOOT OPERATED						
CUTTING WIDTH	42 IN.	42 IN.	48 IN.	52 IN.	52 IN.	60 IN.	60 IN.
CUTTING HEIGHT	1.5 IN. - 4.5 IN.						
CUTTING POSITIONS	13						
WHEELS							
FRONT	11 X 6-5						
REAR	20 X 8-10	20 X 8-10	20 X 10-10	20 X 10-10	20 X 10-10	20 X 12-10	20 X 12-10
FEATURES							
SEAT	18 IN. PLUSH HIGH BACK W/ PADDED ARM RESTS, SEAT ISOLATION STANDARD						
HOURLY METER	STANDARD						
MACHINE							
WEIGHT	615 LBS.	615 LBS.	621 LBS.	630 LBS.	630 LBS.	645 LBS.	645 LBS.
LENGTH	69 IN.						
WIDTH w/ chute	58 IN.	58 IN.	64 IN.	68 IN.	68 IN.	75 IN.	75 IN.
HEIGHT	42 IN.						
WARRANTY							
UNIT	4 YEARS OR 400 HOURS						
ATTACHMENTS & ACCESSORIES							
2-BAG POWERED BAGGER, BAGGER ADAPTER (60" MODEL ONLY), MULCH KIT, L.E.D. LIGHT KIT, FLEX-TEND® SHOULDER SUPPORT SYSTEM, CHROME FRONT WHEEL COVERS, CHROME REAR WHEEL COVERS, 48-IN PLUG AERATOR, 36-IN. POLY ROLLER, 48-IN. DETHATCHER, 15-GALLONSPRAYER, TOW-BEHIND SPREADER, TRAILER HITCH KIT							

