

# DRASTA C 1000



*Metalworking*



Cold quenching oil.

## UTILISATIONS

- Cold quenching oil for routine applications.
- Quenching of bulky, simple-shaped parts made of medium or high-alloy steels with good hardening capacity.
- Quenching of case-hardened or nitrided steels.
- Working temperature : 30°C to 80°C.
- All types of furnaces with separate or built-in tanks.

## ADVANTAGES

- Good resistance to oxidation and thermal changes owing to the use of solvent-refined base oils.
- High flash point to ensure risk-free operation in the utilisation temperature range.
- **DRASTA C 1000** is fully compatible with all quenching oils in the **TOTALFINAELF** product range.

TYPICAL CHARACTERISTICS	METHODS	UNITS	DRASTA C 1000
Density at 15°C	ISO 3675	kg/m <sup>3</sup>	871
Colour	Visual	-	2
Viscosity at 40°C	ISO 3104	mm <sup>2</sup> /s	16
Viscosity at 100°C	ISO 3104	mm <sup>2</sup> /s	4
Cleveland flash point	ISO 2792	°C	200
Neutralization index	ISO 6618	mgKOH/g	< 0.1

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS**  
**Industrie & Spécialités**

23 July 2001  
DRASTA C 1000

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser [www.quick-fds.com](http://www.quick-fds.com).

