


GRANITCUT 2424



Metalworking



Macro emulsion for granite cutting

PRODUCT PROFILE



Granitcut 2424 is a blend of refined hydrocarbons and non-ionic adjuvants. The superior wetting agent infusion helps in improving consistency in cutting time & faster settling of sawing sludge.

APPLICATIONS

- Granitcut 2424 is used during the cutting of granite having circular saw segments with diamond – tipped cutting teeth.

ADVANTAGES

- **Increases life of diamond cutting tool** due to its superior anti-weld characters.
- **Facilitates the settling of sawing sludge** due to the infusion of wetting agent
- **Render good emulsion stability over a long period of time** due to presence of non ionic additives.
- **Resist to bacterial attack** due to aerobic biocide infusion.
- Built in EP additive help in maintaining the cutting time and speed thus **reduces the overall coolant cost/sqm of slab**

Typical Characteristics	Reference Method	GRANITCUT 2424
Colour	ASTM D 1500	L 5.5
Density at 29.5°C	ASTM D 1298	0.878
Emulsion stability (0.5% Concentration)	IS 1115	Highly stable milky white emulsion
Total bacterial count	Internal	< 10 ⁷ /ml
Sludge settling	Internal	Passes

TOTAL LUBRICANTS INDIA LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6

Date 01/09

1/1

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be downloaded from www.quick-fds.com.