



LACTUCA 2614 CR



Metalworking

Premium grade rolling and forming fluid

PRODUCT PROFILE



Lactuca 2614 CR is a unique blend of refined synthetic hydrocarbon and carefully selected additives. The superior EP and boundary lubrication characteristics ensures minimal wear of roll and metal surfaces

APPLICATIONS

- Used for narrow width rolling and forming of steel sheets, coils and tubes
- Suitable for both ferrous and non ferrous material

ADVANTAGES

- Render zero residual formation due to its excellent thermal conductivity, which avoids thermal cracking and burning of oil.
- Enhances sump life due to minimal coalescence of emulsion
- Improves the productivity due to higher weld load, which in turn improves the lubrication at roll bite.
- Excellent emulsion stability due to its resistance to electrolytes.
- Provides superior corrosion inhibition property even at lower concentration
- Operator and environment friendly as it is chemically stable and non toxic

TOTAL LUBRICANTS INDIA LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6

Date 01/09

1/2

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from

www.quick-fds.com

Typical Characteristics	Reference Method	LACTUCA 2614 CR
Density at 29.5°C	ASTM D 1298	0.896
Flash point COC, °C	ASTM D 92	186
pH of 5 % soln	ASTM D 70	8.8
Emulsion stability	IS 1115	Passes
Cast iron corrosion test	IS 1115	0/0/0

TOTAL LUBRICANTS INDIA LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6

Date 01/09

2/2

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be downloaded from

www.quick-fds.com.