


OSYRIS 2609



Metalworking

Premium grade multi-utility long term rust preventive oil

PRODUCT PROFILE



Osyris 2609 is a unique blend of refined hydrocarbon, synthetic ester and film forming additives. Its unique property of non-emulsifying nature coupled with its excellent salt, acid resistance and dewatering ability making it versatile for varied application viz... in process as well as for final product protection.

APPLICATIONS

- For the protection of precious components, cold rolled sheets & coils from corrosion during the stay period, transits as well as at the customer premises for longer duration
- Best suitable for maritime transportation for export components
- Can be used for in process as well as for final product protection

ADVANTAGES

- Reduces rusting and rejection due to its excellent corrosion protection character in varied atmosphere.
- Eliminate dry patches and stains at the customer end.
- Versatile in humid atmosphere due to its non emulsifying nature meeting MIL C 22235 specification. (This specification is superior to IS 1154)
- Phosphating & painting operation is smooth & hassle free due to the excellent degreasability.
- Operator & environment friendly as it is chemically stable & non-toxic.
- Operational flexibility ; Applied by spray, circulation, dip and by brush

TOTAL LUBRICANTS INDIA LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6

Date 01/09

1/2

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be downloaded from

www.quick-fds.com

Typical Characteristics	Reference Method	OSYRIS 2609
Density at 29.5°C	ASTM D 1298	0.8280
Flash point PMCC, °C	ASTM D 93	40
Emulsification	IS 1154	Passes
Film thickness (microns)	IS 2079	5 - 7
Salt Spray /Rust protection	ASTM B 117 & Internal	> 70 hour , Passes
Cleanability with alkaline degreaser	Internal	Passes
Protection – Indoor Outdoor	Internal	> 12 month 4 months

TOTAL LUBRICANTS INDIA LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6

Date 01/09

2/2

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from

www.quick-fds.com.