Product Name	P1.25	P1.538	P1.86	P2	P2.5	P3	P4	P5	P6
Pixel Pitch	1.25 mm	1.538 mm	1.86 mm	2 mm	2.5 mm	3 mm	4 mm	5 mm	6 mm
Pixel density / ㎡	640,000	422,500	288,906	250,000	160,000	111,111	62,500	40,000	27,777
Module Resolution	256X128	208X104	172X86	160X80	128X64	64x64	80x40	64x32	32x32
Module Size(mm)	320X160	320X160	320X160	320X160	320X160	192x192	320x160	320x160	192x192
Cabinet Size(mm)	640x480	640x480	640x480	640x480	640x480	576x576	640x640	640x480	576x576
Cabinet Resolution(Pixels)	512*384	416*312	344*258	320*240	256*192	192x192	160x160	128x96	96x96
Color Temperature	9000±500k	9000±500k	9000±500k	9000±500k	9000±500k	9000±500k	9000±500k	9000±500k	9000±500k
Drive Mode	Constant current	Constant current	Constant current	Constant current	Constant current	Constant current	Constant current	Constant current	Constant current
Brightness	≥600 nits	≥600 nits	≥800 nits	≥800 nits	≥800 nits	≥1000 nits	≥1000 nits	≥800 nits	≥1000 nits
Environment	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor
Best Viewing Distance	≥1.25 mt	≥1.5 mt	≥1.8 mt	≥2 mt	≥2.5 mt	≥3 mt	≥4 mt	≥5 mt	≥6 mt
Refresh Rate	3840 Hz	3840 Hz	3840 Hz	3840 Hz	3840 Hz	1920/3840 Hz	1920/3840 Hz	1920/3840 Hz	1920/3840 Hz
Viewing Angle	≥160°	≥160°	≥160°	≥160°	≥160°	≥160°	≥160°	≥160°	≥160°
Grey Scale	≥12 Bit	≥12 Bit	≥12 Bit	≥12 Bit	≥12 Bit	≥12 Bit	≥12 Bit	≥12 Bit	≥12 Bit
Operating Voltage	DC5V±10%	DC5V±10%	DC5V±10%	DC5V±10%	DC5V±10%	DC5V±10%	DC5V±10%	DC5V±10%	DC5V±10%
Brightness Adjustable Range	0 to 255	0 to 255	0 to 255	0 to 255	0 to 255	0 to 255	0 to 255	0 to 255	0 to 255