

# USG RADAR™ BASIC ACOUSTICAL PANELS



USG Radar™ Basic Acoustical  
Panels/USG Donn® Brand DX®/  
USG Donn® Brand DXL™  
Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- Nondirectional pattern with a fresh, clean appearance offers fast, efficient installation.
- Economical, all-purpose ceiling pattern offered in many sizes.
- Optional Firecode® product designed to meet life-safety codes.
- USDA Certified Biobased Product.<sup>8</sup>

## APPLICATIONS

- Schools
- Corridors
- Offices
- Retail stores

## SUBSTRATE

- Wet-formed mineral fiber

Lightly Textured Panel



# USG RADAR™ BASIC ACOUSTICAL PANELS


ORDER SAMPLES/LITERATURE  
 USG: usg.com or samplitt@usg.com  
 CGC: contact Sales Representative

TECHNICAL SERVICES  
 800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE  
 TECHNICAL INFORMATION  
 AND LEED REPORT TOOL  
 usgdesignstudio.com  
 cgcdesignstudio.com



PRODUCT CERTIFIED  
 FOR LOW CHEMICAL  
 EMISSIONS:  
 UL/COM/GG  
 UL 2818




UL Classified

Edge	Panel Size Imperial Metric (mm)	Fire Rating <sup>2</sup>	Item No. Imperial Metric (mm)	NRC	CAC Min.	LR <sup>3</sup>	Color <sup>6</sup>	Grid Options	VOC Emissions	Recycled Content <sup>1</sup>	Panel Cost
<b>USG RADAR™ BASIC PANEL</b> 	2'x2'x5/8" 600x600x15		2110 ME2110	0.55	33	0.83	White	A,C	Low	24-25%	\$
	2'x2'x5/8"		2115	0.55	35	0.83	White	B	Low	48-49%	\$
	2'x4'x5/8" 600x1200x15		2310 ME2310	0.55	35	0.83	White	A,C	Low	24-25%	\$
	2'x4'x5/8"		2315	0.55	35	0.83	White	B	Low	48-49%	\$
	2'x5'x5/8"	Class A	2619	0.55	35	0.83	White	A,C	Low	24-25%	\$
	20"x60"x5/8" 500x1500x15	Class A	2617 ME2617	0.55	35	0.83	White	A,C	Low	24-25%	\$
	30"x60"x3/4"	Class A	2618	0.60	35	0.83	White	A,C	Low	24-25%	\$
<b>USG RADAR™ BASIC TILE<sup>4,5</sup></b> 	2'x2'x5/8" 600x600x15	Class A	2120 ME2120	0.55	33	0.83	White	D	Low	24-25%	\$
	2'x2'x5/8"		2125	0.55	35	0.83	White	E	Low	48-59%	\$
	2'x4'x5/8"		2320	0.55	35	0.83	White	D	Low	24-25%	\$
	20"x60"x5/8"	Class A	2627	0.55	35	0.83	White	D	Low	24-25%	\$
<b>USG RADAR™ ILLUSION BASIC TWO/24 PANEL</b> 	2'x2'x5/8"	Class A	2130	0.55	33	0.83	White	F,G,H,I	Low	24-25%	\$
<b>USG RADAR™ ILLUSION BASIC TWO/24 PANEL</b> 	12"x12"x5/8"	Class A	2990	0.50	40	0.83	White	J	Low	44%	\$\$\$
	2'x4'x3/4"	Class A	2742	0.55	35	0.83	White	D	Low	26-27%	\$\$

## PATTERNS

### Illusion™ Two/24



The look of 2'x2' panels

### Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

### High Recycled Content

USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

### Firecode®

## GRID PROFILE OPTIONS

A USG DX®	B USG DXL™	C USG DXW™	D USG DX®	E USG DXL™	F USG Centricitee™ DXT™	G USG Fineline® DXF™	H USG Fineline® 1/8 DXFF™	I USG Identitee® DXI™	J USG DX® Concealed

## PHYSICAL DATA/ FOOTNOTES

**Product literature**  
 Data sheet: SC2288

**ASTM E1264 classification**  
 Type III, Form 2, Pattern C, E  
 and C, E, K

**ASTM E84 and CAN/ULC S102  
 surface-burning characteristics**  
 Class A  
 Flame spread: 25 or less  
 Smoke developed: 50 or less

**UL Type**  
 FR-83

**Weight**  
 0.61-1.15 lb./sq. ft.

**Online tools**  
 usgdesignstudio.com or cgcdesignstudio.com

**Thermal resistance**  
 R-1.4 (Class A, 5/8" panels and tile)  
 R-1.7 (Class A, 3/4" panels)  
 R-1.4 (Class A, 15 mm panels)  
 R-1.6 (Firecode®, 5/8" panels)

**Maximum backloading**  
 See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum.

**Metric sizes available**  
 Contact sales for minimum quantities and lead times.

### Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- Fire-rated items: see UL design details.
- LR values are shown as averages.
- Contact USG for adhesive recommendation for 12"x12" glue-up applications.
- Not UL Classified for acoustics.
- No Flat Black or 'Deeptones' are available on any reveal edge or USG Radar™ Firecode® panel.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

**Notice**  
 The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2288/rev. 6-22  
 © 2022 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, FIRECODE, IDENTITEE, RADAR, IT'S YOUR WORLD, BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

