

Fissured
Mineral Fiber

Non-directional, sound-absorbing and blocking utilitarian panel with exceptional value.

APPLICATIONS

- Utility Areas
- Retail Warehouses
- Strip Malls
- Commercial Interior Spaces
- Offices
- Other Commercial Buildings / Space Applications



CUSTOMLINE 224



CUSTOMLINE 448




CUSTOMLINE 812


FEATURES AND BENEFITS

- Non-directional fissured pattern
- Three-dimensional face scoring available in 3 geometric designs with Customline options
- Environmental Product Declaration (EPD) available for this product
- Available in fire-rated (Protectone) version
- Health Product Declaration (HPD) available for this product


SUSPENSION SYSTEM OPTIONS




Trim
15/16 Grid



Reveal
Beveled
15/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid




Narrow Reveal
Beveled
9/16 Grid
(Customline)

CUSTOMLINE SCORING OPTIONS



24 x 48
224



24 x 48
448



24 x 48
812

LEED® v4

RECYCLED CONTENT

CLASS A	33%
PROTECTONE®	44%

<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input type="checkbox"/>	EQ: Acoustic Performance
<input type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials
<input checked="" type="checkbox"/>	EQ: Daylight
<input checked="" type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning



EPD Available



HPD Available



Recycled Content

Fissured
Mineral Fiber

All products in this line
feature these attributes:



LR
0.83



EPD
AVAILABLE



HPD
AVAILABLE



LOW
VOC
EMISSION
COMPLIANT
CERTIFIED



RECYCLED
CONTENT
33-44%

BAROQUE

	Format	Dimensions (in.)	NRC (UL Classified)	CAC (UL Classified)	Recycled Content	UL Fire-Rated	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet		
TRIM												
	NRC 55	BET-157	Panels	24 x 24 x 5/8	0.55	33	33%	—	16	64	45	20
		PBT-157	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	70	20
		BET-197	Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	45	20
		PBT-197	Panels	24 x 48 x 5/8	0.55	40	44%	Yes*	8	64	70	20
		BET-2067	Panels	20 x 60 x 5/8	0.55	35	33%	—	8	67	52	20

REVEAL

	NRC 55	BET-154	Panels	24 x 24 x 5/8	0.55	33	33%	—	16	64	45	20
		PBT-154	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	70	20
		BET-194	Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	45	20

NARROW REVEAL

	NRC 55	BET-150	Panels	24 x 24 x 5/8	0.55	33	33%	—	16	64	46	20
--	--------	---------	--------	---------------	------	----	-----	---	----	----	----	----

BAROQUE METRIC

	Format	Dimensions (mm)	NRC (UL Classified)	CAC (UL Classified)	Recycled Content	UL Fire-Rated	Pieces/ carton	Sq. m/ carton	Lbs./ carton	Cartons/ pallet		
METRIC TRIM												
	NRC 55	BET-2067M	Panels	500 x 1500 x 15	0.55	35	33%	—	8	6	52	20

BAROQUE CUSTOMLINE

	Format	Dimensions (in.)	NRC (UL Classified)	CAC (UL Classified)	Recycled Content	UL Fire-Rated	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet		
REVEAL												
	NRC 55	BQCL-224	Panels	24 x 48 x 3/4	0.55	35	33%	—	8	64	55	16
		BQCL-448	Panels	24 x 48 x 3/4	0.50	35	33%	—	8	64	55	16
	NRC 50	BQCL-812	Panels	24 x 48 x 3/4	0.50	35	33%	—	8	64	55	16
		PBQCL-224	Panels	24 x 48 x 3/4	0.50	40	44%	Yes*	8	64	75	16

NARROW REVEAL

	NRC 55	BQCLN-224	Panels	24 x 48 x 3/4	0.55	35	33%	—	8	64	55	16
		BQCLN-448	Panels	24 x 48 x 3/4	0.50	35	33%	—	8	64	55	16
	NRC 50	BQCLN-812	Panels	24 x 48 x 3/4	0.50	35	33%	—	8	64	55	16

* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL
Mineral Fiber

ASTM E1264 CLASSIFICATION
Type III, Form 2, Pattern C D - Baroque
Type III, Form 2, Pattern C D K - Customline

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment.

BAROQUE CUSTOMLINE WARRANTY
10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed Suspension Systems. Full warranty information can be found at certainteed.com/ceilings.

BAROQUE WARRANTY
1-year Limited Warranty