

SYMPHONY *m* HIGH NRC SYMPHONY *m* HIGH CAC SYMPHONY® *m*

MINERAL FIBER CEILINGS



The Symphony line provides a full range of ultra-durable acoustic solutions with a consistent, smooth visual, coupled with excellent durability.

FEATURES AND BENEFITS

- Excellent sound absorption (NRC 0.75-0.85) and sound blocking (CAC 33-42)
- Certified clean room component to ISO Class 4 (highest among comparable products)
- Tested to 1,000 wash cycles and compatible with most sanitizing solutions
- Exceeds FGI guidelines for cleanability and acoustic performance
- SmartFit panels available - fully fabricated off-the-shelf solution to accommodate linear lighting, ventilation and utility areas with standard components

ALL PRODUCTS IN THIS LINE FEATURE THESE ATTRIBUTES



NRC
UP TO 0.85



SAG RESISTANT



FIRE RATING:
CLASS A



BIOSHIELD®
MOLD/MILDEW
RESISTANT



LOW
VOC
EMISSION COMPLIANT
CERTIFIED



WASHABLE W/
SANITIZING
CHEMICALS



LR 0.90

CertaSize® Program
Non-standard sizes
made to order on select
products. Lead time
varies. Contact your
local sales rep or
Customer Support

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE



Declare®
Living Building Challenge Red List Free®
Declare® is a service mark of The
International Living Future Institute.

LEED® v4

RECYCLED CONTENT	62%	
	PRE: 60%	POST: 2%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the
U.S. Green Building Council.


ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

SYMPHONY *m* HIGH NRC | SYMPHONY *m* HIGH CAC

SYMPHONY® *m*

SYMPHONY *m* HIGH NRC

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM											
	NRC 85	1222-85-1	Panels	24 x 24 x 7/8	0.85	35	62%	14	56	64	16
		1220-85-1	Panels	24 x 48 x 7/8	0.85	35	62%	8	64	74	14
		1223-85-1	Panels	30 x 30 x 7/8	0.85	35	62%	8	50	58	28
		1221-85-1	Planks	24 x 60 x 7/8	0.85	35	62%	8	80	92	14
		1228-85-1	Planks	24 x 72 x 7/8	0.85	35	62%	8	96	110	14


REVEAL

	NRC 85	1222BB-85-1	Panels	24 x 24 x 7/8	0.85	35	62%	14	56	64	16
		1220BB-85-1	Panels	24 x 48 x 7/8	0.85	35	62%	8	64	74	14
		1221BB-85-1	Planks	24 x 60 x 7/8	0.85	35	62%	8	80	92	14
		1228BB-85-1	Planks	24 x 72 x 7/8	0.85	35	62%	8	96	110	14

NARROW REVEAL

	NRC 85	1222BF-85-1	Panels	24 x 24 x 7/8	0.85	35	62%	14	56	64	16
		1220BF-85-1	Panels	24 x 48 x 7/8	0.85	35	62%	8	64	74	14
		1221BF-85-1	Planks	24 x 60 x 7/8	0.85	35	62%	8	80	92	14
		1228BF-85-1	Planks	24 x 72 x 7/8	0.85	35	62%	8	96	110	14

SYMPHONY *m* HIGH CAC

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM											
	NRC 80	1222-80-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
		1220-80-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14
		1221-80-1	Planks	24 x 60 x 7/8	0.80	42	62%	8	80	92	14
		1228-80-1	Planks	24 x 72 x 7/8	0.80	42	62%	8	96	110	14
		1223-80-1	Panels	30 x 30 x 7x8	0.80	40	62%	8	50	58	28

REVEAL


	NRC 80	1222BB-80-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
		1220BB-80-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14
		1221BB-80-1	Planks	24 x 60 x 7/8	0.80	42	62%	8	80	92	14
		1228BB-80-1	Planks	24 x 72 x 7/8	0.80	42	62%	8	96	110	14


NARROW REVEAL

	NRC 80	1222BF-80-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
		1220BF-80-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14
		1221BF-80-1	Planks	24 x 60 x 7/8	0.80	42	62%	8	80	92	14
		1228BF-80-1	Planks	24 x 72 x 7/8	0.80	42	62%	8	96	110	14


SYMPHONY *m* HIGH NRC | SYMPHONY *m* HIGH CAC SYMPHONY® *m*

SYMPHONY *m*

TRIM		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
	NRC 75	1222-75-1	Panels	24 x 24 x 7/8	0.75	36	62%	14	56	56	16
		1220-75-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
		1223-75-1	Panels	30 x 30 x 3/4	0.75	36	62%	8	50	50	28
		1229-75-1	Panels	30 x 60 x 3/4	0.75	36	62%	8	100	100	16
		12220-60-75-1	Planks	20 x 60 x 3/4	0.75	36	62%	8	66	66	24
		1221-75-1	Planks	24 x 60 x 3/4	0.75	36	62%	8	80	80	16
		1228-75-1	Planks	24 x 72 x 3/4	0.75	36	62%	8	96	96	16
		12204-48-75-1	SmartFit	4 x 48 x 3/4	-	-	62%	48	64	64	16
		12206-48-75-1	SmartFit	6 x 48 x 3/4	-	-	62%	32	64	64	16
		12212-48-75-1	SmartFit	12 x 48 x 3/4	-	-	62%	16	64	64	16
		12212-60-75-1	SmartFit	12 x 60 x 3/4	-	-	62%	16	80	80	16




REVEAL		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
	NRC 75	1222BB-75-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	56	16
		1220BB-75-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
		12220-60BB-75-1	Planks	20 x 60 x 3/4	0.75	36	62%	8	66	66	24
		1221BB-75-1	Planks	24 x 60 x 3/4	0.75	36	62%	8	80	80	16
		1228BB-75-1	Planks	24 x 72 x 3/4	0.75	36	62%	8	96	96	16
		12204-48BB-75-1	SmartFit	4 x 48 x 3/4	-	-	62%	48	64	64	16
		12206-48BB-75-1	SmartFit	6 x 48 x 3/4	-	-	62%	32	64	64	16
		12212-24BB-75-1	SmartFit	12 x 24 x 3/4	-	-	62%	16	80	80	16
		12212-48BB-75-1	SmartFit	12 x 48 x 3/4	-	-	62%	16	64	64	16

NARROW REVEAL		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
	NRC 75	1222BF-75-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	56	16
		1220BF-75-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
		12220-60BF-75-1	Planks	20 x 60 x 3/4	0.75	36	62%	8	66	66	24
		1221BF-75-1	Planks	24 x 60 x 3/4	0.75	36	62%	8	80	80	16
		1228BF-75-1	Planks	24 x 72 x 3/4	0.75	36	62%	8	96	96	16
		12204-48BF-75-1	SmartFit	4 x 48 x 3/4	-	-	62%	48	64	64	16
		12206-48BF-75-1	SmartFit	6 x 48 x 3/4	-	-	62%	32	64	64	16
		12212-24BF-75-1	SmartFit	12 x 24 x 3/4	-	-	62%	16	80	80	16
		12212-48BF-75-1	SmartFit	12 x 48 x 3/4	-	-	62%	16	64	64	16


METRIC TRIM		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
	NRC 75	1220-60-75-1M	Panels	500 x 1500 x 19	0.75	36	62%	8	6	96	16
		1220-75-1M	Panels	600 x 1200 x 19	0.75	36	62%	8	5.8	49	32
		1222-75-1M	Panels	600 x 600 x 19	0.75	36	62%	14	5	55	16
		1229-75-1M	Panels	750 x 1500 x 19	0.75	36	62%	8	9	64	24
		1223-75-1M	Panels	750 x 750 x 19	0.75	36	62%	8	4.5	62	16

SYMPHONY *m* HIGH NRC | SYMPHONY *m* HIGH CAC SYMPHONY® *m*


ACCESSORIES

SYMPHONY <i>m</i> ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE
	1170-SEL-1 Mineral Fiber Edge Sealant	1	For re-sealing cut edges; 1 quart container
	STBAR-2 2' Stabilizer Bar	40	Recommended one pc/panel for all 2x5 and 2x6 narrow reveal installations
	STBAR-4 4' Stabilizer Bar	40	Recommended one pc spanning two panels in 2x5 and 2x6 narrow reveal installations


EDGE DETAILS




Trim
9/16 Grid




Trim
15/16 Grid




Reveal
Corner Bevel
15/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid Bolt Slot



Narrow Reveal
Corner Bevel
9/16 Grid Tear Drop

PHYSICAL DATA

MATERIAL

Mineral Fiber

FIRE CLASS

All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION

Type IV, Form 2, Pattern E

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

APPLICATION CONSIDERATIONS

Clean panel using a sponge/cloth dampened with water and mild liquid detergent solution. Do not soak panel. Cleanable with sanitizing chemicals.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

WARRANTY

10-year 10/4/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com/architectural