

Dimensions:

	Wood Stud		Steel Stud
R14 (RSI 2.47)	15.25" x 47" x 3.5" (387 mm x 1194 mm x 89 mm)	R10 (RSI 1.76)	16.25" x 48" x 2.5" (413 mm x 1219 mm x 64 mm)
	23" x 47" x 3.5" (584 mm x 1194 mm x 89 mm)		24.25" x 48" x 2.5" (616 mm x 1219 mm x 64 mm)
R22 (RSI 3.87)	15.25" x 47" x 5.5" (387 mm x 1194 mm x 140 mm)	R14 (RSI 2.47)	16.25" x 48" x 3.5" (413 mm x 1219 mm x 89 mm)
	23" x 47" x 5.5" (584 mm x 1194 mm x 140 mm)		24.25" x 48" x 3.5" (616 mm x 1219 mm x 89 mm)
R24 (RSI 4.23)	15" x 47" x 5.5" (381 mm x 1194 mm x 140 mm)	R22.5 (RSI 3.96)	16.25" x 48" x 6" (413 mm x 1219 mm x 152 mm)
	22.75" x 47" x 5.5" (578 mm x 1194 mm x 140 mm)		24.25" x 48" x 6" (616 mm x 1219 mm x 152 mm)
R28 (RSI 4.93)	15.25" x 47" x 7.25" (387 mm x 1194 mm x 184 mm)	R24 (RSI 4.23)	16.25" x 48" x 6" (413 mm x 1219 mm x 152 mm)
	23" x 47" x 7.25" (584 mm x 1194 mm x 184 mm)		24.25" x 48" x 6" (616 mm x 1219 mm x 152 mm)
R32 (RSI 5.64)	15.25" x 47" x 8" (387 mm x 1194 mm x 203 mm)		
	23" x 47" x 8" (584 mm x 1194 mm x 203 mm)		

This product has been specifically designed to meet your needs for wood stud and steel stud construction.

Density:

> 2 lb/ft³ (> 32 kg/m³)

Area Weight:

Thickness	Weight
2.5" (65 mm)	> 2.0 kg/m ²
3.5" (89 mm)	> 2.8 kg/m ²
5.5" (140 mm)	> 4.8 kg/m ²
6.0" (150 mm)	> 4.8 kg/m ²
7.25" (184 mm)	> 5.9 kg/m ²
8.0" (184 mm)	> 5.9 kg/m ²

Key Application Qualifiers:

- Easily cut
- Non-combustible
- Excellent sound absorbency
- Chemically inert
- Does not rot or sustain vermin
- Does not promote growth of fungi or mildew
- Low moisture sorption
- Water resistant
- CFC- and HCFC- free product and process
- Made from natural & recycled materials

Other ROXUL Products:

Please consult ROXUL for all your insulation needs. We have an extensive range of products for all applications from pipe insulation to commercial products to residential batts. ROXUL invites all inquiries and will act promptly to service all of your requirements.

Note: As ROXUL Inc. has no control over installation design and workmanship, accessory materials or application conditions, ROXUL Inc. does not warranty the performance or results of any installation containing ROXUL Inc's. products. ROXUL Inc's. overall liability and the remedies available are limited by the general terms and conditions of sale. This warranty is in lieu of all other warranties and conditions expressed or implied, including the warranties of merchantability and fitness for a particular purpose.