



# SAFETY CHECK AND REGISTRATION FORM

Safety Decal Serial Number \_\_\_\_\_

## Car Related Items

### Roll Cage

(Minimum 1" to drivers helmet) \_\_\_\_\_  
(DQ) Seat/Shoulder Belts \_\_\_\_\_  
Shoulder, Seat, & Crotch belt required \_\_\_\_\_

(4year maximum, SFI 16.1, Anti-Sub  
**Nerf Bars/Bumpers** \_\_\_\_\_  
(Minimum (2) 6/32 bolts, Grade 5 min.)

**Shoulder Bar** \_\_\_\_\_  
(Min.8/32 bolt at spud or clamp grade 5 min)  
(DQ)**Axles/Hubs** \_\_\_\_\_

(Axles not past wheels.)  
**Belly Pan** \_\_\_\_\_  
(Minimum gauge 0.040 AL, No open holes

**Fire Wall** \_\_\_\_\_  
(Minimum gauge 0.048 AL, No open holes  
(DQ)**Steering Wheel** \_\_\_\_\_  
(1" thick, 2" diameter pad, min.)

pan) \_\_\_\_\_

**Steering** \_\_\_\_\_  
(No over center, binds)  
inches)

**Ignition System** \_\_\_\_\_

### Brakes

(DQ)(Heel Stop, Metallic outer shield brake line) \_\_\_\_\_

**Fuel System** \_\_\_\_\_  
(Minimum quality wire tie clamp)  
Fuel Line - Rated for Gasoline or Methanol \_\_\_\_\_  
Fuel Sleeve - Fire Resistant Sleeve \_\_\_\_\_  
(DQ required on all fuel lines)  
Fuel Filter - Steel or Aluminum Only \_\_\_\_\_

(DQ)**Exhaust System** \_\_\_\_\_

**Throttle Cable** \_\_\_\_\_  
(No binding)

**Tail Cone** \_\_\_\_\_  
(Below top of bumper)

**Tires/Wheels** \_\_\_\_\_  
(Three lug nuts)

(DQ) **Oil Catch Can** \_\_\_\_\_  
(Located under tail)

(DQ) **Weights** \_\_\_\_\_  
(No weights fastened to side pod sheet metal, lead weights must be bolted and coated or wrapped, fender washers must be included if its bolted through belly

**Side Panels** L \_\_\_\_\_ R \_\_\_\_\_  
(2" hole for access to flywheel nut, (DQ)maximum 22

**Enclosed Nose Section** \_\_\_\_\_  
**DECALS** \_\_\_\_\_  
Hoosier, USAC, USAC.25

## Drivers Equipment

(DQ) **Helmet** \_\_\_\_\_  
(Snell SA 2005 (or higher)or SFI24.1 (or higher)

**Face Shield** \_\_\_\_\_  
(No cracks)  
(SFI 3.2 A/1 minimum)

(DQ) **Neck Collar** \_\_\_\_\_  
(Nomex or Equivalent or Head & Neck Restraint SFI 38.1 Certified)

Effective January 1, 2012, Head and Neck Restraint Systems shall be inspected for recertification every five years after the date of original certification. Product inspection, maintenance, and/or replacement procedure is per individual manufacturer. Inspection must be done by the original manufacturer only, and not their authorized resellers or dealers. When a unit is determined by the manufacturer to be acceptable for continued service and in compliance with the current version of the specification, the original manufacturer shall place on the product a new SFI 38.1 conformance label marked with the inspection date.

(DQ) **Gloves** \_\_\_\_\_  
(SFI 3.3/5, 1 layer)

(DQ) **Arm Restraints** \_\_\_\_\_  
(Worn close to wrist, not above elbow)

(DQ) **Suit 1 or 2 piece** \_\_\_\_\_  
(SFI 3.2A/1min. no jeans)

(DQ) **Shoes** \_\_\_\_\_  
(Completely cover fee, flat bottom

General Safety Condition: \_\_\_\_\_

Safety Director Signature: \_\_\_\_\_

## Registration

Date \_\_\_\_\_ Car # \_\_\_\_\_ Color \_\_\_\_\_

Class: Novice 120 160 Mod AA Animal W/F  
Division: Junior Senior Light Heavy Unrestricted

Drivers Name \_\_\_\_\_ DOB: \_\_\_\_\_ Age \_\_\_\_\_

Address \_\_\_\_\_ City, State, Zip \_\_\_\_\_

Handlers Name \_\_\_\_\_ Phone \_\_\_\_\_

Address \_\_\_\_\_ City, State, Zip \_\_\_\_\_

# \_\_\_\_\_ .25 Club \_\_\_\_\_ Drivers

I agree to assume all responsibility at this event and to abide by all .25 rules/procedures.

**Signature of Owner and/or Handler** \_\_\_\_\_

**NOTE:** (DQ is reference to item that is a Disqualifiable item from race or timing event.