



A001 : Seldur

high solids metallised polish

Description of product

A high solids metallised polish for extreme strength and durability coupled with ease of removability with a non-yellowing cross linked polymer film which will not discolour even the lightest floor. Produces a deep shine with excellent slip resistance and responds brilliantly to spray burnishing techniques. test

Product Uses


For all linoleum, P.V.C., rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors. N.B. Not suitable for unsealed wood, unsealed cork or laminate flooring.

Directions

Seldur must be applied to a clean grease free floor. Strip old polish with Seldate then rinse thoroughly with clean water, allow floor to dry. Apply a thin even film of Seldur using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 minutes). May be buffed as required to enhance gloss. COVERAGE: 60 square metres per litre. MAINTENANCE: Damp Mopping: As required using Lemon Gel or Seldlen. Spray cleaning/burnishing: Regular use of Selsheen will enhance appearance and life expectancy.

iN Insight Supported

iN Insight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>



iN Insight recommended product uses

Flooring - applying floor polish (mop application)

typical dilution

neat

Product Hazards and PPE Requirements

Contains : Benzisothiazolinone

Risk Phrases

Contains Benzisothiazolinone. May produce an allergic reaction.

Safety Phrases

Technical Data

A low viscosity, opaque, cream coloured liquid, which has a slight sweet odour. It is a blend of acrylic Composition and ethylene polymer dispersions, anionic and nonionic wetting agents, plasticisers, coalescents, humectants and a metal salt for crosslinking.

Appearance Translucent emulsion

Colour White

Viscosity <10 cps

Density 1.025

pH 8.0 – 8.2

Activity 18%

Fragrance Characteristic slightly sweet

Stability 2 years in unopened containers

Storage Protect from freezing

Environmental Profile

Biodegradability

All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter

- We set ourselves industry leading standards.
 - Selden minimises wastage, packaging and transportation.
 - If it can be recycled, it will be recycled.
 - Our chemicals policy exceeds regulatory requirements.
 - We don't expect other people to clean up after us.
 - Conserving energy, preserving resources.
 - By being innovative, we strive to do better.
 - We like to work in partnership with our clients.
- Visit our website for more information.

External Accreditations

9001 - Quality System
14001 - Environmental System
18001 - Health & Safety System
IPPC Certified Manufacturer

Sustainability

Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages



english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



UKAS
accredited testing
laboratory No. 4204



SELLEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

