



# K040 : SILICONE SPRAY

## Description of product

### Product Uses


As a release/antistick agent; used in plastic injection moulding, fibre glass moulding, footwear industry, ceramicware production, rubber articles, oven shelves not in excess of 315°C. Lubrication uses; for most plastic and synthetic/natural rubber or plastic bearings, textile fibres etc.

### Directions

Hold can as near upright as possible, approximately 20cm from the surface. Spray lightly over surface to achieve the required level of finish. Repeat this operation as required. Do not spray directly onto hot surfaces.

**iN Insight Supported**

iN Insight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>




**iN Insight recommended product uses**

Special - maintenance aerosols (lubrication/cleaning)

typical dilution n/a

**Product Hazards and PPE Requirements**

**Danger**



**Contains :**

**Risk Phrases**  
Extremely flammable aerosol. Pressurised container. May burst if heated.

**Safety Phrases**  
Keep out of reach of children. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

**Technical Data**

Composition	Pure silicone oil
Appearance	Clear spray
Colour	Colourless
Viscosity	350 Cps
Density	0.58
Fragrance	Odourless
Stability	Two years minimum
Storage	Pressurised container. Store out of direct sunlight. Temperature must not exceed 50oC

**Aerosol Information**

Propellant	Hydrocarbon
Pressure	60 psi
Spray Rate	0.9

**Environmental Profile**

**Biodegradability**

**Selden Environmental Charter**

- We set ourselves industry-leading standards.
- Selden minimises wastage, packaging and transportation.
- If it can be recycled, it will be recycled.
- Our chemicals policy exceeds regulatory requirements.
- We don't expect other people to clean up after us.
- Conserving energy, preserving resources.
- By being innovative, we strive to do better.
- We like to work in partnership with our clients.


Visit our website for more information.

**External Accreditations**

- 9001 - Quality System
- 14001 - Environmental System
- 18001 - Health & Safety System
- IPPC Certified Manufacturer

**Sustainability**

Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



**COSHH+ Supported**

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



**www.flagship-mcp.com**

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages

- english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



**UKAS**  
accredited testing  
laboratory No. 4204



**SELDEN**  
formulating  
testing  
manufacturing  
to  
the highest  
standards

**Selden Research Limited**

Staden Business Park, Staden Lane, Buxton  
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : [info@selden.co.uk](mailto:info@selden.co.uk) | web : [www.selden.co.uk](http://www.selden.co.uk)

