



HANGZHOU FOB ELECTRONIC CO.,LTD

Add:Jinqiu Village,Linglong Street,Linan,Hangzhou,China

Mobile:+86 13656645647 E-mail:kaka@fobelec.com Website: www.fobelec.com

Cable Type: RF 1/4" S Coaxial Cable 50 Ohm



Physical Dimensions

Construction	Detail Specification
Conductors	1.91 mm Bare Copper
Dielectric	5.00 mm Foamed PE
Braid	6.40 corrugated copper tube
Outer Jacket	7.60 mm PE

Minimum Bending Radius (mm)

Single Bending	25
Repeated Bending	30
Mobile Application	200

Electrical Characteristics

Characteristic Impedance	50±2 Ohm
Nominal Capacitance	79pF/m
Nominal Velocity of Propagation	84%
Jacket spark-test	4KV
Inner Conductor DC Resisitance \leq (Ω /KM) @20 °C	9.80
Outer Conductor DC Resisitance \leq (Ω /KM) @20 °C	6.50

Attenuation[@20°C]

Frequency (Mhz)	Maximum(dB/100Ft)	Maximum(dB/100M)
100	1.80	5.89
200	2.57	8.41
300	3.17	10.40
450	3.90	12.80
800	5.31	17.40
900	5.61	18.40
1000	5.98	19.60
1500	7.41	24.30
1800	8.20	26.90
2000	8.69	28.50
2500	9.79	32.10
3000	10.86	35.60