



HANGZHOU FOB ELECTRONIC CO.,LTD

Add:Jinqiu Village,Linglong Street,Linan,Hangzhou,China

Mobile:+86 13656645647 E-mail:kaka@fobelec.com Website: www.fobelec.com

Cable Type: RF 7/8" Coaxial Cable 50 Ohm



Physical Dimensions

Construction	Detail Specification
Conductors	9.05 mm Bare Copper
Dielectric	22.00 mm Foamed PE
Braid	24.90 corrugated copper tube
Outer Jacket	27.50 mm PE

Minimum Bending Radius (mm)

Single Bending	120
Repeated Bending	250
Mobile Application	500

Electrical Characteristics

Characteristic Impedance	50±2 Ohm
Nominal Capacitance	75pF/m
Nominal Velocity of Propagation	89%
Jacket spark-test	4KV
Inner Conductor DC Resisitance \leq (Ω /KM) @20 °C	1.05
Outer Conductor DC Resisitance \leq (Ω /KM) @20 °C	1.18

Attenuation[@20°C]

Frequency (Mhz)	Maximum(dB/100Ft)	Maximum(dB/100M)
100	0.36	1.19
200	0.52	1.72
300	0.65	2.13
450	0.81	2.65
800	1.11	3.63
900	1.18	3.88
1000	1.26	4.12
1500	1.58	5.18
1800	1.75	5.75
2000	1.86	6.11
2500	2.12	6.95
3000	2.37	7.76