



HANGZHOU FOB ELECTRONIC CO.,LTD

Add:Jinqiu Village,Linglong Street,Linan,Hangzhou,China

Mobile:+86 13656645647 E-mail:kaka@fobelec.com Website: www.fobelec.com

Cable Type:Tri-shield RG6 With Messenger Coaxial Cable 75 Ohm



Physical Dimensions

Construction	Detail Specification
Conductor	1.02mm Copper Covered Steel
Dielectric	4.57±0.15mm Foamed PE
Inner Shield	Bonded Aluminum/PET,100% coverage
Braid	Aluminum Alloy Braid,60% coverage
Tri-shield Shield	Aluminum/PET/Aluminum,100% coverage
Outer Jacket	7.06±0.02mm PVC
Messenger	1.3mm Steel

Electrical Characteristics

Characteristic Impedance	75±3 Ohm
Nominal Capacitance	53.5pF/m
Nominal Velocity of Propagation	85.00%
Jacket spark-test	4KV

Attenuation[@20°C]

Frequency (Mhz)	Maximum(dB/100Ft)	Maximum(dB/100M)
5	0.58	1.90
55	1.60	5.25
83	1.95	6.40
187	2.85	9.35
250	3.30	10.82
350	3.85	12.63
450	4.40	14.43
550	4.90	16.08
750	5.65	18.54
863	6.10	20.01
1000	6.55	21.50