




# HANGZHOU FOB ELECTRONIC CO.,LTD

Add:Jingju Village,Linglong Street,Linan,Hangzhou,China

Mobile:+86 13656645647 E-mail:kaka@fobelec.com Website: www.fobelec.com

**Cable Type:LAN CABLE UTP CAT6A**

## Product Structure



## Physical Dimensions

Construction	Detail Specification
Inner Conductor	0.57mm (23AWG) Bare Copper
Insulation	1.02+/-0.02mm HD PE
4 Pairs	1.(White)(Blue)/(Blue) 2.(White)(Green)/(Green) 3.(White)(Brown)/(Brown) 4.(White)(orange)/(Orange)
Separator	
Outer Jacket	6.9+0.1mm Jacket LSZH

## Electrical Characteristics

Characteristic Impedance (1~1000MHz)	100±15 Ohm
Delay Skew(ns/100m)	≤45
Transmission Speed	0.6C
Capacitance	≤5.6 nF/100m

Operating Temp range: -20℃ ~ +70℃

Frequency (MHz)	Return Loss dB/100m	Attenuation dB/100m	NEXT dB/100m	PHASE DELAY ns/100m	PSNEXT dB/100m	ELFEXT dB/100m	PSELFEXT dB/100m
1	20.0	2.1	74.3	570.0	72.3	67.8	64.8
4	23.0	3.8	65.3	552.0	63.3	55.8	52.8
8	24.5	5.3	60.8	546.7	48.8	49.7	46.7
10	25.0	5.9	59.3	545.4	57.3	47.8	44.8
16	25.0	7.5	56.2	543.0	54.2	43.7	40.7
20	25.0	8.4	54.8	542.1	52.8	41.8	38.8
25	24.3	9.4	53.3	541.2	41.3	39.8	36.8
31.25	23.6	10.5	51.9	540.4	49.9	37.9	34.9
62.5	21.5	15.0	47.4	538.6	45.4	31.9	28.9
100	20.1	19.1	44.3	537.6	42.3	27.8	24.8
200	18.0	27.6	39.8	536.5	37.8	21.8	18.8
250	17.3	31.1	38.3	536.3	36.3	19.8	16.8
300	16.8	34.3	37.1	536.1	35.1	18.3	15.3
500	15.2	45.3	33.8	535.6	31.8	13.8	10.8