



H Systems (Pty) Ltd

Aluminium Systems & Hardware Suppliers

www.hsystems.co.za

Johannesburg	011 748 2660
Nelspruit	013 752 7565
Pietermaritzburg	033 386 1422
Durban	031 569 2275
Cape Town	021 905 0005
Port Elizabeth	041 451 1642
Admin	033 386 1447

P O Box 28518, Hayfields, 3201
Reg No: 2005/009864/07 Vat No: 4140221898

H CLAD WARRANTY

H Systems provides a warranty for the period of 15 years on the H CLAD Kynar 500 PVDF coated composite panel from date of manufacture.

The H CLAD Kynar 500 PVDF coated Composite Panel will not peel or change colour, the panel is flat and straight without bubbles or wrinkles. The outer aluminium sheets will not delaminate from the fire resistant core. The quality of the H CLAD shall meet the GB/T17748-1999 and ASTM Standards.

The warranty includes the following additional conditions:

H CLAD is to be installed in normal climatic conditions which is exclusive of high pollution or chemical environments, in temperatures over 60 Degrees Celsius, high salt fog and radiation.

There is no contrived damage to the paint surface or panel, no error in processing or installation and no abuse of chemicals or touching up of the painted surface.

H CLAD shall be installed within 6 months of delivery to the customer's premises.

H CLAD shall be handled with care and stored flat on a pallet in a pollution and chemical free environment. Deformation, wear and paint damage caused by improper handling or storage is not included in the warrantee.

Damages due to outside force such as fire, explosion, frictional impact and all accidents, natural disasters and contrived malicious damages are not included in this warrantee.

Upon receipt of H CLAD Composite Panels supplied by H Systems, the customer shall immediately check the panels for abnormal conditions, and if found, shall be submitted to H Systems within 15 days of receipt of the panels. Concealed defects discovered on the removal of the protective film, shall be submitted immediately upon discovery.

H CLAD shall be maintained for the life of the panel and cleaned with a neutral cleaning agent. Care must be taken that the cleaning process does not impact, abrade or damage the surface and rinsed with clean water. Under normal climatic conditions, the panels must be cleaned every 6 months and every 3 months in coastal conditions.

If the customer finds that during the period of warranty, that the quality of the H CLAD does not meet the warranty standard, H Systems will compensate the customer in way of replacement of the defective panels at the cost of H Systems.

If a quality issue is found, the customer must inform H Systems in writing immediately.