



YOUR GATEWAY TO A BETTER VIEW

H SYSTEMS (PTY) LTD

Aluminium Systems & Hardware Suppliers

info@hsystems.co.za

NATIONAL FOOTPRINT:

Johannesburg, Cape Town, Durban, Port Elizabeth, Pietermaritzburg, Nelspruit

www.hsystems.co.za

Date: _____

LETTER OF GUARANTEE - OLV 77 CAULK & SEAL SEALANT

THIS LETTER SERVES TO CONFIRM THAT WE GUARANTEE THE OLV 77 CAULK & SEAL SEALANT,
FOR A PERIOD OF 5 YEARS UNDER NORMAL USE AND CORRECT MAINTENANCE.

DESCRIPTION:

OLV 77 Caulk & Seal Sealant is Acrylic Sealant for windows and doors is a one part, water based acrylic sealant that cures to a flexible and tough rubber with good adhesion to porous surface without primer. Suitable for sealing and filling gaps or joints where low demands of elongation are required.

MAIN PURPOSES:

- 1 Mainly for sealing the gaps or joints interior and exterior, such as doors and window frames, walls, window sills.
- 2 Can be used on most construction materials, such as brick, concrete, plasterwork, asbestos cement, wood, glass, ceramic tiles, metals, aluminum, zinc etc.
- 3 Acrylic sealant for windows and doors.

CHARACTERISTICS:

- 1 One part, water based acrylic sealant that cures to a flexible and tough rubber with good adhesion to porous surface without primer;
- 2 Suitable for sealing and filling gaps or joints where low demands of elongation are required.

THE WARRANTY BECOMES INVALID IF YOU DO NOT FOLLOW THE CORRECT
APPLICATION INSTRUCTIONS AS BELOW OR ON AN UNSUITABLE SURFACE

APPLICATION:

- 1 Clean with solvents such as toluene or acetone to keep the substrate surfaces completely clean and dry;
- 2 For better appearance cover outside of joint areas with masking taps before application;
- 3 Cut nozzle to desired size and extrudes sealant to joint areas;
- 4 Tool immediately after sealant application and remove masking tape before sealant skins.

LIMITATIONS:

- ① Unsuitable for permanently flexible sealing, for cars or spaces where wet conditions exist, e.g. aquaria, foundations and swimming pools;
- ② Do not apply at temperature below 0°C;
- ③ Not fit for continuous immersion in water;
- ④ Keep out of reach of children.

TIPS:

- ① The joint surfaces must be clean and free from dust, rust and grease. Tar and bitumen substrates reduce the bonding ability;
- ② In order to improve the bonding ability to strongly absorbing porous surfaces, such as stone, concrete, asbestos cement and plasterwork, these surfaces should first be primed with a diluted sealant (1 volume of Acrylic Sealant to 3-5 volumes of water) until the primer to dry completely.

SHELF LIFE:

Acrylic Sealant is sensitive to frost and must be kept in tightly closed packing in a frost-proof place. The shelf life is about 12 months when stored in a cool and dry place.

VOLUME: 310ml

TECHNOLOGY DATA IS AVAILABLE IF REQUIRED ON REQUEST.