



## YOUR GATEWAY TO A BETTER VIEW

**H SYSTEMS (PTY) LTD**

Aluminium Systems & Hardware Suppliers

info@hsystems.co.za

**NATIONAL FOOTPRINT:**

Johannesburg, Cape Town, Durban, Port Elizabeth, Pietermaritzburg, Nelspruit

[www.hsystems.co.za](http://www.hsystems.co.za)

Date: \_\_\_\_\_

### LETTER OF GUARANTEE – OLV 168 ACETIC SILICONE GLASS SEALANT

THIS LETTER SERVES TO CONFIRM THAT WE GUARANTEE THE OLV 168 ACETIC SILICONE GLASS SEALANT, FOR A PERIOD OF 5 YEARS UNDER NORMAL USE AND CORRECT MAINTENANCE.

#### DESCRIPTION:

OLV 168 Acetic Silicone Glass Sealant is one-part room temperature acetoxy silicone sealant. It has excellent weather ability, waterproof and good adhesion to most construction materials. It is suitable for sealing, glazing for window panels and other general building materials bonding.

#### MAIN PURPOSES:

- 1 | For sealing doors and windows.

#### CHARACTERISTICS:

- 1 | One-component, acetic cured, RTV, low-modulus.
- 2 | Easy to use, cures quickly, good weather ability.
- 3 | Good adhesion to many building materials.
- 4 | Colors include clear, white, grey and black, bronze.

**THE WARRANTY BECOMES INVALID IF YOU DO NOT FOLLOW THE CORRECT APPLICATION INSTRUCTIONS AS BELOW OR ON AN UNSUITABLE SURFACE**

#### APPLICATION:

- 1 | Clean with solvents such as toluene or acetone to keep the substrate surfaces completely clean and dry;
- 2 | For better appearance cover outside of joint areas with masking taps before application;
- 3 | Cut nozzle to desired size and extrudes sealant to joint areas;
- 4 | Tool immediately after sealant application and remove masking tape before sealant skins.

## LIMITATIONS:

---

- ① Unsuitable for curtain wall structural adhesive.
- ② Unsuitable for the airproof location, because it is required to absorb moisture in air to cure for the sealant.
- ③ Unsuitable for the frosty or moist surface.
- ④ Unsuitable for the continually damp places.
- ⑤ Can't be used if the temperature is below 4°C or above 50°C on the surface of the material.

## SHELF LIFE:

---

9 months if kept sealed correctly, and stored below 27°C in cool, dry place after the date of production.

**VOLUME:** 310ml

TECHNOLOGY DATA IS AVAILABLE IF REQUIRED ON REQUEST.