



YOUR GATEWAY TO A BETTER VIEW

H SYSTEMS (PTY) LTD

Aluminium Systems & Hardware Suppliers

info@hsystems.co.za

NATIONAL FOOTPRINT:

Johannesburg, Cape Town, Durban, Port Elizabeth, Pietermaritzburg, Nelspruit

www.hsystems.co.za

Date: _____

LETTER OF GUARANTEE - OLV 328 NEUTRAL/OXIME SILICONE SEALANT

THIS LETTER SERVES TO CONFIRM THAT WE GUARANTEE THE OLV 328 SILICONE,
FOR A PERIOD OF 5 YEARS UNDER NORMAL USE AND CORRECT MAINTENANCE.

DESCRIPTION:

OLV 328 Neutral Silicone Sealant is a one component, neutral curing, high performance neutral cure silicone sealant designed for a wide range of glazing, weatherproof seal on most common building materials (not including copper). It has excellent primerless adhesion to most construction materials and good compatibility with other neutral silicone sealants.

MAIN PURPOSES:

- 1 Designed for sealing non-structural curtain wall joints.
- 2 For marble, granite, concrete, ceramic, most plastics, tile & brick works.
- 3 Other general exterior wall gap-filling waterproof purpose.

CHARACTERISTICS:

- 1 One-component, neutral cured, excellent performance in sealing.
- 2 Excellent weatherability, anti-UV, anti-ozone and waterproofing.
- 3 On curing will form a strong bond to most common building components without the use of a primer.

THE WARRANTY BECOMES INVALID IF YOU DO NOT FOLLOW THE CORRECT
APPLICATION INSTRUCTIONS AS BELOW OR ON AN UNSUITABLE SURFACE

APPLICATION:

- 1 Clean with solvents such as toluene or acetone to keep the substrate surfaces completely clean and dry;
- 2 For better appearance cover outside of joint areas with masking taps before application;
- 3 Cut nozzle to desired size and extrudes sealant to joint areas;
- 4 Tool immediately after sealant application and remove masking tape before sealant skins.

LIMITATIONS:

- ① Unsuitable for curtain wall structural adhesive.
- ② Unsuitable for the airproof location, because it is required to absorb moisture in air to cure for the sealant.
- ③ Unsuitable for the frosty or moist surface.
- ④ Unsuitable for the continually damp places.
- ⑤ Can't be used if the temperature is below 4°C or above 50°C on the surface of the material.

SHELF LIFE:

9 months if kept sealed correctly, and stored below 27°C in cool, dry place after the date of production.

VOLUME: 310ml

TECHNOLOGY DATA IS AVAILABLE IF REQUIRED ON REQUEST.