

WETCHEM EMULSIFIED POLYMER #26E

DESCRIPTION

Emulsified Polymer acts as a flocculant agent which can increase the floc size of sludge particles and hence increase the precipitation rate. The floc is then separated by sedimentation and hydraulic separation.

APPLICATION PROCEDURE

- 1 Fill the chemical tank about half (1/2) full with Potable Water
- 2 Turn on the water valve and slowly adjust the dispenser to create suction
- 3 Place the funnel on top of the dispenser
- 4 Start the mixer
- 5 Slowly pour the 1.5L #26E into the funnel until the solution reaches the required level
- 6 Agitate the solution for 30 minutes or until the #26E is completely dissolved



CHEMICAL COMPOSITION

Anionic Polyacrylamide 0.5%



TECHNICAL PROPERTIES

Density : Approx. 750 kg/m³
pH : 7
Form : Emulsified Liquid
Solubility : Viscous Solution in Water



Emulsified Liquid



Packaging: 1.5L/bottle



IRRITANT



HEALTH HAZARD



CHEMICAL CONSUMPTION RATE (L/H) (1.5L POLYMER IN 500L WATER)

SS (ppm)	Flow Rate (m ³ /h)				
	10	20	40	60	80
2,000	4.55	9.15	18.25	27.40	36.55
3,000	4.55	9.15	18.25	27.40	36.55
4,000	4.55	9.15	18.25	27.40	36.55
5,000	6.85	13.70	27.40	41.10	54.80
6,000	6.85	13.70	27.40	41.10	54.80
10,000	9.15	18.25	36.55	54.80	73.05



+852 2602 0308



mail@wastech.com.hk



www.wetsep.com



Units 601-602, 6/F, Lakeside 2,
No. 10 Science Park West Avenue,
Hong Kong Science Park, Shatin,
Hong Kong



Scan to visit
our website