

TRAFFIC MONITORING

EVENT COVERAGE

CROWD-CONTROL

SITUATIONAL AWARENESS

## COMPATIBLE WITH OVER 20 COMMERCIAL DRONES



DJI Matrice 200



DJI Inspire 2



DJI Inspire 1



Acore Zoe



Yuneec H920



DJI M100

## PORTABLE CONTINUOUS POWER



60m

Lightweight,  
«Plug & Fly»



1.2 kW

Unlimited and secured  
power



200 Mbps

Fast data transfer  
Full Motion Video



Secured and  
unjammable  
communications



T-monitor  
Smart warning  
function



Multi-drone  
compatible:  
Inspire, Matrice, etc.



## TECHNICAL SPECIFICATIONS



### Characteristics

|                          |                                      |
|--------------------------|--------------------------------------|
| Length                   | 60 m                                 |
| Micro-tether weight      | 10.5 g/m                             |
| Output voltage           | 6S or 12S                            |
| Power (output)           | Up to 2500W (peak)                   |
| Safety Switch (onboard)  | Included                             |
| Power input              | 220 - 250 VAC, 50 - 60 Hz            |
| Data speed               | 200 Mb/s                             |
| Tensile strength         | 150 daN                              |
| Built-in protection      | Electronic crowbar / Circuit-breaker |
| Tether Management System | Compact vertical reel                |
| Total weight             | 12 kg                                |
| Dimensions               | 475 mm x 415 mm x 211 mm             |

### Data

|                          |                                      |
|--------------------------|--------------------------------------|
| Length                   | 60 m                                 |
| Micro-tether weight      | 10.5 g/m                             |
| Output voltage           | 6S or 12S                            |
| Power (output)           | Up to 2500W (peak)                   |
| Safety Switch (onboard)  | Included                             |
| Power input              | 220 - 250 VAC, 50 - 60 Hz            |
| Data speed               | 200 Mb/s                             |
| Tensile strength         | 150 daN                              |
| Built-in protection      | Electronic crowbar / Circuit-breaker |
| Tether Management System | Compact vertical reel                |
| Total weight             | 12 kg                                |
| Dimensions               | 475 mm x 415 mm x 211 mm             |