Date: October 2004 Coatings Product Data Sheet



PC MScoat - 31

A flammable spirit based refractory coating for manganese steel castings.

Product properties

PC MScoat – 31 Liquid is a ready-to-use, flammable IPA-based magnesite coating for manganese steel castings in silica sand moulds and cores. It ensures a smooth, defect-free finish by preventing metal–mould reactions, metal penetration, and sand burn-on. With quick drying, stable suspension, and easy application, it offers clean peel-off, reduced cleaning time, and consistent results for heavy-duty, automotive, railway, and industrial castings.

Typical Properties

1) Colour : Off White to Light Brown Liquid

2) Specific-Gravity : 1.40 (+/- 0.03) gms/cc

3) Baume : 40 deg (+/-3)

4) Application Viscosity : 14-18 seconds By B-4 cup.

Advantages

- 1) Imparts excellent casting finish, free from sand burns and fusions.
- 2) Coating inclusions are not caused.
- 3) Product is easily re-mixable due to better suspension properties and gives uniform coverage, which ensures a good casting finish, free from veining, fins, fusion and penetration and hence lowers the casting cleaning costs.

Storage & Handling

- o 6 months under normal conditions in original Bucket
- o Protect from frost and direct sunlight
- o 25 Kgs in Bucket