



REVIVE

Water-Based Coating

perkEpave REVIVE is the perfect solution for extending the life span of aging urethane bound stone and rubber poured in place surfaces. REVIVE is sold in 5 gallon (44 lb pails). The product can be applied by brush, roller or sprayer and a pail of REVIVE will cover approximately 400 sq ft. REVIVE can be purchased unpigmented or in the colors shown below.



1006 Maize Yellow



1012 Lemon Yellow



2010 Signal Orange



3005 Wine Red



3009 Oxide Red



4005 Blue Lilac



4008 Signal Violet



5003 Sapphire Blue



5010 Gentian Blue



5015 Sky Blue



6002 Leaf Green



6010 Grass Green



7015 Slate Grey



7037 Dusty Grey



7038 Agate Grey



9004 Signal Black

perkEpave LLC - perkepave.com

418 Wilson St Pottstown, PA 19464

(215) 316-6383



REVIVE

Industrial Grade Water-Based Coating

Application Details:

1. Blow off any loose particles with a power leaf blower.
2. Tape and cover adjacent areas, poles and supports that protrude through the surface.
3. Brush coat approximately 3 inches of the surface around supports or poles and perimeter edges with perkEpave Revive.
4. Spray application provides much better coating vs. roll coating
5. If roll coater is to be used, the nap must be suitable for the surface – highly porous surfaces will require a heavier nap e.g., > 1"
6. Two coats of perkEpave Revive are recommended for best results.
7. perkEpave Revive will dry to touch in approximately 25 minutes at 70 – 90 °F at 50 – 80% relative humidity.
8. [Graco Truecoat 360 airless sprayer](#) is a recommended sprayer for the application of perkEpave Revive