Himalayan Product Specifications

Engine

Type	Single Cylinder, 4 Stroke, Air Cooled
Displacement	411cc
Bore x Stroke	78 mm x 86 mm
Compression Ratio	9.5 : 1
Maximum Power	24.3 bhp @ 6500 rpm
Maximum Torque	23.6 ft/lbs @ 4000-4500 rpm
Ignition System	Electronic Fuel Injection (EFI)
Clutch	Wet, Multi-Plate
Gearbox	5 Speed, Constant Mesh
Lubrication	Wet Sump, Forced Lubrication
Engine Oil	Semi-Synthetic 15W-50 50 API, SL Grade & Aabove JASO MA 2
Fuel Supply	Electronic Fuel Injection
Air Cleaner	Paper Element
Engine Start	Electric

Chassis & Suspension

Type	Half-Duplex Split Cradle Frame
Front Suspension	Telescopic, 41mm Forks, 200mm Travel
Rear Suspension	Monoshock with Linkage, 180mm Wheel Travel

Dimensions

Wheelbase	58"
Ground Clearance	8.6"
Length	86"
Width	33" *(without mirrors)*
Height	53" *(with fly screen top)*
Seat Height	31.5"
Curb Weight	439 lbs *(with 90% fuel & oil)*
Fuel Capacity	4 gal

Brakes & Tires

Front Tire	90/90 - 21"
Rear Tire	120/90 - 17"
Front Brake	300 mm Disc, Twin Piston Floating Caliper
Rear Brake	240 mm Disc, Single Piston Floating Caliper
ABS	Dual Channel *(switchable to single channel)*

Electricals

Electrical System	12V - DC
Battery	12V, 8 AH, VRLA *(maintenance free)*
Head Lamp	12V, H4-60/55W
Tail Lamp	12V, 4/1W
Turn Signal Lamp	12V, 10W x 4 Nos.