

| | | |
|-------------------------------|---------------|-------------|
| Rating | Kva | 5 |
| | KW | 4 |
| Voltage | | 230/415 |
| Amps | SP | 20.83 |
| | TP | |
| | Model | JPS/05R |
| | Panel | Std/AMF |
| | Duty | Prime |
| | Cooling | Air |
| Dimesion (MM) | L | 1500 |
| | B | 850 |
| | H | 1250 |
| KG | Weight | 650 |
| Ltrs | Fuel tank | 50 |
| | Lube Oil | 5.0 |
| | Battery | 60/65 AH |
| | Make | Eicher |
| | Engine Model | 110A1-EG008 |
| | Cyl | 1 |
| | HP | 10.70 |
| | Aspiration | NA |
| | Dispalcement | 982 |
| | Compression | 17:5±0.5:1 |
| | Governing | Mechanical |
| | Class | G-2 |
| | Bore X Stroke | 100 x125 |
| Reference Standard | | BS-5514 |
| | | ISO-3046 |
| | | IS-10000 |
| | | ISO-8528 |

Warranty:-2 Years -5000 Hours

Warranty:-5 Years on 5C OR 5000 Hours whichever is earlier

Because of Continuos Improvements,products specification and features herein are subject to change without notice./DG Set Noise Level Conforms to CPCB Norms