

Safety Data Sheet

Clear matt sheen acrylic top coat

Safety Data Sheet dated 2/28/2013, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: Clear matt sheen acrylic top coat

Other means of identification:

Trade code: 6OPU79G10

Recommended use of the chemical and restrictions on use

Recommended use:

Surface coating

Restrictions on use:

None

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

SIRCA S.p.A.

Viale Roma, 85

35010 S.Dono di Massanzago (PD) - ITALY

Tel. +39 0499322311

Competent person responsible for the safety data sheet:

safety@sirca.it

Emergency phone number

SIRCA S.p.A.- Phone n. +39 499322311

2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Danger, Flam. Liq. 2, Highly flammable liquid and vapour.



Warning, Skin Irrit. 2, Causes skin irritation.



Warning, Eye Irrit. 2A, Causes serious eye irritation.



Warning, Skin Sens. 1, May cause an allergic skin reaction.



Danger, Repr. 1B, May damage fertility or the unborn child.



Warning, STOT SE 3, May cause drowsiness or dizziness.



Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Label elements

Symbols:

Safety Data Sheet

Clear matt sheen acrylic top coat



Danger

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H360 May damage fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water and soap.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER/doctor/... if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: use CO₂, Foam, Chemical powders to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Safety Data Sheet

Clear matt sheen acrylic top coat

Ingredient(s) with unknown acute toxicity:
None

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION		

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

25% - 48% n-butyl acetate

REACH No.: 01-2119485493-29-xxxx, Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1



B.6/3 Flam. Liq. 3 H226



A.8/3 STOT SE 3 H336

12.5% - 20% toluene

REACH No.: 01-2119471310-51-xxxx, Index number: 601-021-00-3, CAS: 108-88-3, EC: 203-625-9



B.6/2 Flam. Liq. 2 H225



A.7/2 Repr. 2 H361




A.10/1 Asp. Tox. 1 H304



A.9/2 STOT RE 2 H373

Safety Data Sheet

Clear matt sheen acrylic top coat

 A.2/2 Skin Irrit. 2 H315

 A.8/3 STOT SE 3 H336

9.9% - 12.5% butanone

REACH No.: 01-2119457290-43-xxxx, Index number: 606-002-00-3, CAS: 78-93-3, EC: 201-159-0

 B.6/2 Flam. Liq. 2 H225

 A.3/2A Eye Irrit. 2A H319

 A.8/3 STOT SE 3 H336

7% - 9.9% xylene [isomer mixture]

REACH No.: 01-2119488216-32-xxxx, Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7

 B.6/3 Flam. Liq. 3 H226

 A.10/1 Asp. Tox. 1 H304

 A.3/2A Eye Irrit. 2A H319

 A.8/3 STOT SE 3 H335

 A.9/2 STOT RE 2 H373

 A.2/2 Skin Irrit. 2 H315

 A.1/4/Dermal Acute Tox. 4 H312

 A.1/4/Inhal Acute Tox. 4 H332

3% - 5% 4-methylpentan-2-one

REACH No.: 01-2119473980-30-xxxx, Index number: 606-004-00-4, CAS: 108-10-1, EC: 203-550-1

 B.6/2 Flam. Liq. 2 H225

 A.3/2A Eye Irrit. 2A H319

 A.8/3 STOT SE 3 H335



 A.1/4/Inhal Acute Tox. 4 H332

1% - 2% ethylbenzene

Safety Data Sheet




Clear matt sheen acrylic top coat

REACH No.: 01-2119489370-35-xxxx, Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4

-  B.6/2 Flam. Liq. 2 H225
-  A.1/4/Inhal Acute Tox. 4 H332





1% - 2% ethyl acetate

REACH No.: 01-2119475103-46-xxxx, Index number: 607-022-00-5, CAS: 141-78-6, EC: 205-500-4

-  B.6/2 Flam. Liq. 2 H225
-  A.3/2A Eye Irrit. 2A H319
-  A.8/3 STOT SE 3 H336

0.5% - 1% methyl 2-methylprop-2-enoate

REACH No.: 01-2119452498-28-xxxx, Index number: 607-035-00-6, CAS: 80-62-6, EC: 201-297-1

-  B.6/2 Flam. Liq. 2 H225
-  A.8/3 STOT SE 3 H335
-  A.2/2 Skin Irrit. 2 H315
-  A.4.2/1 Skin Sens. 1 H317

0.2% - 0.25% dibutyltin dilaurate


REACH No.: 01-2119557828-21-xxxx, CAS: 77-58-7, EC: 201-039-8

-  A.2/1B Skin Corr. 1B H314
-  A.3/1 Eye Dam. 1 H318
-  A.8/1 STOT SE 1 H370
-  A.4.2/1 Skin Sens. 1 H317
-  A.9/1 STOT RE 1 H372
-  A.5/2 Muta. 2 H341
-  A.7/1B Repr. 1B H360
-  US-HAE/A1 Aquatic Acute 1 H400
-  US-HAE/C1 Aquatic Chronic 1 H410

Safety Data Sheet

Clear matt sheen acrylic top coat

0.1% - 0.2% 1-ethylpyrrolidin-2-one
REACH No.: 01-2119472138-36-xxxx, CAS: 2687-91-4, EC: 220-250-6

 A.3/1 Eye Dam. 1 H318

 A.7/2 Repr. 2 H361

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of ingestion:

Give nothing to eat or drink.

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use CO₂, Foam, Chemical powders

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.A.

Oxidizing properties: N.A.

Safety Data Sheet

Clear matt sheen acrylic top coat

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

n-butyl acetate - CAS: 123-86-4

TLV TWA - 150 ppm - 712,64 mg/m³

TLV STEL - 200 ppm - 950,18 mg/m³

Safety Data Sheet

Clear matt sheen acrylic top coat

toluene - CAS: 108-88-3
 OEL (IT) - LTE(8h): 192 mg/m³, 50 ppm - Behaviour: Binding - Notes: Skin
 EU - LTE(8h): 192 mg/m³, 50 ppm - STE: 384 mg/m³, 100 ppm - Notes: Skin
 ACGIH - LTE: 188.4 mg/m³, 50 ppm - Notes: A4 Skin

butanone - CAS: 78-93-3
 OEL (IT) - LTE(8h): 600 mg/m³, 200 ppm - STE: 900 mg/m³, 300 ppm - Behaviour: Binding
 EU - LTE(8h): 600 mg/m³, 200 ppm - STE: 900 mg/m³, 300 ppm
 ACGIH - LTE: 589.78 mg/m³, 200 ppm - STE: 884.66 mg/m³, 300 ppm

xylene [isomer mixture] - CAS: 1330-20-7
 OEL (IT) - LTE(8h): 221 mg/m³, 50 ppm - STE: 442 mg/m³, 100 ppm - Behaviour: Binding - Notes: Skin
 EU - LTE(8h): 221 mg/m³, 50 ppm - STE: 442 mg/m³, 100 ppm - Notes: skin
 ACGIH - LTE: 434.19 mg/m³, 100 ppm - STE: 651.29 mg/m³, 150 ppm - Notes: A4

4-methylpentan-2-one - CAS: 108-10-1
 OEL (IT) - LTE(8h): 83 mg/m³, 20 ppm - STE: 208 mg/m³, 50 ppm - Behaviour: Binding
 EU - LTE(8h): 83 mg/m³, 20 ppm - STE: 208 mg/m³, 50 ppm
 ACGIH - LTE: 204.83 mg/m³, 50 ppm - STE: 307.24 mg/m³, 75 ppm

ethylbenzene - CAS: 100-41-4
 OEL (IT) - LTE(8h): 442 mg/m³, 100 ppm - STE: 884 mg/m³, 200 ppm - Behaviour: Binding - Notes: Skin
 EU - LTE(8h): 442 mg/m³, 100 ppm - STE: 884 mg/m³, 200 ppm - Notes: Skin
 ACGIH - LTE: 434.19 mg/m³, 100 ppm - STE: 542.74 mg/m³, 125 ppm - Notes: A3

ethyl acetate - CAS: 141-78-6
 OEL (IT), 400 ppm
 TLV TWA - 400 ppm - 1441,31 mg/m³

methyl 2-methylprop-2-enoate - CAS: 80-62-6
 OEL (IT), 50 ppm, 100 ppm - Behaviour: Binding
 EU, 50 ppm, 100 ppm
 ACGIH, 50 ppm, 100 ppm

DNEL Exposure Limit Values
 n-butyl acetate - CAS: 123-86-4
 Worker Professional: 960 MG/M³ - Consumer: 859.7 MG/M³ - Exposure: Human
 Inhalation Short Term, systemic effects
 Worker Professional: 480 MG/M³ - Consumer: 102.34 MG/M³ - Exposure: Human
 Inhalation Long Term, systemic effects

PNEC Exposure Limit Values
 n-butyl acetate - CAS: 123-86-4
 Target: Fresh Water - Value: 0.18 mg/l
 Target: Marine water - Value: 0.018 mg/l
 Target: Freshwater sediments - Value: 0.981 mg/kg
 Target: Marine water sediments - Value: 0.0981 mg/kg
 Target: Soil (agricultural) - Value: 0.0903 mg/kg

Appropriate engineering controls:
 None

Individual protection measures
 Eye protection:
 Use close fitting safety goggles, don't use eye lens.

Safety Data Sheet

Clear matt sheen acrylic top coat

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	< 21 °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	0.945 Kg/l at 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Viscosity:	55 " Din cup # 4 (typical value)
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

No dangerous reaction if stored and used appropriately.

Conditions to avoid

Avoid accumulating electrostatic charge.

Vapours can form explosive mixtures with air.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

Safety Data Sheet

Clear matt sheen acrylic top coat

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 21 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat 14000 mg/kg

butanone - CAS: 78-93-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

b) skin corrosion/irritation:

Test: Skin Corrosive - Species: Rabbit - Notes: Slightly irritant

c) serious eye damage/irritation:

Test: Eye Irritant - Species: Rabbit - Notes: Highly irritant

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: Cavia porcellus - Notes: not sensitizing

e) germ cell mutagenicity:

Test: Genotoxicity - Species: Salmonella Typhimurium - Notes: not mutagen

xylene [isomer mixture] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Inhalation - Species: Rat = 27 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 12126 mg/kg

4-methylpentan-2-one - CAS: 108-10-1

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 23.29 g/m³

Test: LD50 - Route: Oral - Species: Rat = 2080 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 8.2 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 2000 mg/kg

ethyl acetate - CAS: 141-78-6

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit = 20000 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 5620 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 29.3 mg/l - Duration: 4h

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit Negative

e) germ cell mutagenicity:

Test: Genotoxicity Negative

methyl 2-methylprop-2-enoate - CAS: 80-62-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 7900 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 29.8 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 5000 mg/kg

toluene - CAS: 108-88-3

Safety Data Sheet

Clear matt sheen acrylic top coat

LD50 (RABBIT) SKIN: 14 G/KG (14000 MG/KG)
LD50 (RAT) YOUNG ADULTS ORAL: 5542 MG/KG BW
ethylbenzene - CAS: 100-41-4
LD50 (RAT) ORAL: 3500 MG/KG
LD50 (RAT) ORAL: 4710 MG/KG BW
dibutyltin dilaurate - CAS: 77-58-7
LD50 (RAT) ORAL:> 500 MG/KG

Substance(s) listed on the NTP report on Carcinogens:
None

Substance(s) listed on the IARC Monographs:
Ethylbenzene – Group 2B
4-methylpentan-2-one – Group 2B
Xylene [isomer mixture] – Group 3
Toluene – Group 3
Methyl 2-methylprop-2-enoate – Group 3

Substance(s) listed as OSHA Carcinogen(s):
None

Substance(s) listed as NIOSH Carcinogen(s):
None

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 64 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia = 73 mg/l - Duration h: 24

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

ethyl acetate - CAS: 141-78-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 454.7 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 154 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3300 mg/l - Duration h: 48

methyl 2-methylprop-2-enoate - CAS: 80-62-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 191 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 69 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 110 mg/l - Duration h: 72

dibutyltin dilaurate - CAS: 77-58-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.0 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 0.66 mg/l - Duration h: 48

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Safety Data Sheet

Clear matt sheen acrylic top coat

Other adverse effects
None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number

ADR-UN Number:	1263
DOT-UN Number:	1263
IATA-UN Number:	1263
IMDG-UN Number:	1263

UN proper shipping name

ADR-Shipping Name:	Paint Related material
DOT-Shipping Name:	Paint Related material
IATA-Shipping Name:	Paint Related material
IMDG-Shipping Name:	Paint Related material

Transport hazard class(es)

ADR-Class:	3
DOT-Class:	3
IATA-Class:	3
IMDG-Class:	3

Packing group

ADR-Packing Group: II
DOT-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II

Environmental hazards

ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
No

Special precautions

ADR-Tunnel Restriction Code:	D/E
DOT-Special provisions:	149, B52, IB2, T4, TP1, TP8, TP28
IATA-Passenger Aircraft:	353
IATA-Cargo Aircraft:	364
IATA-S.P.:	A72
IATA-ERG:	8L
IMDG-EmS:	F-E, S-E
IMDG-Storage category:	B
IMDG-Storage notes:	None

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act



Safety Data Sheet

Clear matt sheen acrylic top coat

TSCA inventory: all the components are listed on the TSCA inventory

TSCA listed substances:

Toluene is listed in TSCA Section 8A CAIR

Ethylbenzene is listed in TSCA Section 4

n-butyl acetate is listed in TSCA Section 4, Section 12b

Methyl 2-methylprop-2-enoate is listed in TSCA Section 4

4-methylpentan-2-one is listed in TSCA Section 4

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed

Section 304 – Hazardous substances: no substances listed

Section 313 – Toxic chemical list: Xylene [isomer mixture], Ethylbenzene, Toluene, Methyl 2-methylprop-2-enoate, 4-methylpentan-2-one

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

Xylene [isomer mixture] – Reportable quantity: 100 pounds

Toluene – Reportable quantity: 1000 pounds

Ethylbenzene – Reportable quantity: 1000 pounds

n-butyl acetate – Reportable quantity: 5000 pounds

Methyl 2-methylprop-2-enoate – Reportable quantity: 1000 pounds

Butanone – Reportable quantity: 5000 pounds

4-methylpentan-2-one – Reportable quantity: 5000 pounds

Ethyl acetate – Reportable quantity: 5000 pounds

CAA - Clean Air Act

CAA listed substances:

Xylene [isomer mixture] is listed in CAA Section 111, Section 112(b) – HAP, Section 112(b) – HON

Toluene is listed in CAA Section 111, Section 112(b) – HAP, Section 112(b) – HON

Ethylbenzene is listed in CAA Section 111, Section 112(b) – HAP, Section 112(b) – HON

n-butyl acetate is listed in CAA Section 111

Methyl 2-methylprop-2-enoate is listed in CAA Section 111, Section 112(b) – HAP, Section 112(b) – HON

Butanone is listed in CAA Section 111, Section 112(b) – HAP, Section 112(b) – HON

4-methylpentan-2-one is listed in CAA Section 111, Section 112(b) – HAP, Section 112(b) – HON

Ethyl acetate is listed in CAA Section 111

CWA - Clean Water Act

CWA listed substances:

Xylene [isomer mixture] is listed in CWA Section 304, Section 311

Toluene is listed in CWA Section 304, Section 307, Section 311

Ethylbenzene is listed in CWA Section 304, Section 307, Section 311

n-butyl acetate is listed in CWA Section 304, Section 311

Methyl 2-methylprop-2-enoate is listed in CWA Section 311

4-methylpentan-2-one is listed in CWA Section 304

Ethyl acetate is listed in CWA Section 304

USA - State specific regulations

Safety Data Sheet

Clear matt sheen acrylic top coat

California Proposition 65

Substance(s) listed under California Proposition 65:

Toluene – Listed as reproductive toxicant

Ethylbenzene – Listed as carcinogen

4-methylpentan-2-one – Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Xylene [isomer mixture]

Toluene

Ethylbenzene

Ethyl acetate

n-butyl acetate

Methyl 2-methylprop-2-enoate

Butanone

4-methylpentan-2-one

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Xylene [isomer mixture]

Toluene

Ethylbenzene

Ethyl acetate

n-butyl acetate

Methyl 2-methylprop-2-enoate

Butanone

4-methylpentan-2-one

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Xylene [isomer mixture]

Toluene

Ethylbenzene

Ethyl acetate

n-butyl acetate

Methyl 2-methylprop-2-enoate

Butanone

4-methylpentan-2-one

16. OTHER INFORMATION

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H225 Highly flammable liquid and vapour.

H361 Suspected of damaging fertility or the unborn child.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.



Safety Data Sheet

Clear matt sheen acrylic top coat

- H317 May cause an allergic skin reaction.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H341 Suspected of causing genetic defects.
- H360 May damage fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Safety Data Sheet dated 2/28/2013, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.



Safety Data Sheet

Clear matt sheen acrylic top coat

STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).