



INDUSTRIAL
ADHESIVES
of Indiana

8202 Indy Lane
Indianapolis, IN 46214

Product Data 5460

5460 is a premium quality general purpose adhesive that may be used in many different applications. It performs exceptionally well in edge glue operations, assembly, face glue operations, finger joint, and other types of glue operations. It contains a high solids content and ease of application. This product contains no fillers or extenders such as clay. This product is available with a "UV" detection.

Physical Properties

Poly Vinyl Acetate Based Adhesive

Yellow, Light Cream or Brown in Color

Stable Freeze/Thaw

Weight per Gallon 9.5 lbs.

Viscosity 4000-4500

Solids 48%-53%

Shear Strength 3900 kgs.

Wood Failure Ave. 93.94%

Available Blends Yellow

Chalk Temperature 51 degrees F

Non Staining on Oak Yes

Set Time 25-35 minutes @ 72 degrees F

Fixture Time 60-75 minutes @ 72 degrees F

The information reflects the latest information and characteristics concerning this product. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purpose price of the product, without regard to whether such a claim is based on breach of warranty or tort.