

# Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Ethanol Spec IND PM 3224 190 Proof

Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Manufacturer or supplier's details

Company : Nexeo Solutions, LLC.

Address 3 Waterway Square Place Suite 1000

The Woodlands, TX. 77380 United States of America

**Emergency telephone number:** 

Health North America: 1-855-NEXEO4U (1-855-639-3648) Health International: 1-855-NEXEO4U (1-855-639-3648) Transport North America: CHEMTREC (1-800-424-9300)

Additional Information: : Responsible Party: Product Safety Group

E-Mail: msds@nexeosolutions.com SDS Requests: 1-855-429-2661 SDS Requests Fax: 1-281-500-2370 Website: www.nexeosolutions.com

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

: Category 2 (Central nervous system, Eyes)

**GHS** label elements

Hazard pictograms







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H371 May cause damage to organs (Central nervous system,

Eyes).

Precautionary statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

SDS Number: 100000032157 1 / 13 Ethanol Spec IND PM 3224 190 Proof



# Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/ eye protection/ face protection.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P311 IF exposed or concerned: Call a POISON

CENTER or doctor/ physician.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

| CAS-No.  | Chemical name          | Weight percent |
|----------|------------------------|----------------|
| 64-17-5  | Ethanol                | 70 - 90        |
| 67-56-1  | Methanol               | 3 - 5          |
| 141-78-6 | Ethyl acetate          | 1 - 5          |
| 108-10-1 | Methyl isobutyl ketone | 0.1 - 1        |

Any Concentration shown as a range is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

SDS Number: 100000032157 2 / 13 Ethanol Spec IND PM 3224 190 Proof



# Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

: Carbon oxides formaldehyde

toxic fumes

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

SDS Number: 100000032157 3 / 13 Ethanol Spec IND PM 3224 190 Proof



# Safety Data Sheet Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

 Do not spray on a naked flame or any incandescent material.
 Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

| CAS-No. | Components | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|---------|------------|-------------------------------------|--|-----------|
| 64-17-5 | Ethanol    | TWA                                 | 1,000 ppm                                      | ACGIH     |
|         |            | TWA                                 | 1,000 ppm<br>1,900 mg/m3                       | NIOSH REL |
|         |            | TWA                                 | 1,000 ppm<br>1,900 mg/m3                       | OSHA Z-1  |

SDS Number: 100000032157 4 / 13 Ethanol Spec IND PM 3224 190 Proof



# Safety Data Sheet Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

|          |                        | TWA  | 1,000 ppm<br>1,900 mg/m3 | OSHA P0   |
|----------|------------------------|------|--------------------------|-----------|
|          |                        | STEL | 1,000 ppm                | ACGIH     |
| 67-56-1  | Methanol               | TWA  | 200 ppm                  | ACGIH     |
|          |                        | STEL | 250 ppm                  | ACGIH     |
|          |                        | TWA  | 200 ppm<br>260 mg/m3     | NIOSH REL |
|          |                        | ST   | 250 ppm<br>325 mg/m3     | NIOSH REL |
|          |                        | TWA  | 200 ppm<br>260 mg/m3     | OSHA Z-1  |
|          |                        | STEL | 250 ppm<br>325 mg/m3     | OSHA P0   |
|          |                        | TWA  | 200 ppm<br>260 mg/m3     | OSHA P0   |
| 141-78-6 | Ethyl acetate          | TWA  | 400 ppm                  | ACGIH     |
|          |                        | TWA  | 400 ppm<br>1,400 mg/m3   | NIOSH REL |
|          |                        | TWA  | 400 ppm<br>1,400 mg/m3   | OSHA Z-1  |
|          |                        | TWA  | 400 ppm<br>1,400 mg/m3   | OSHA P0   |
| 108-10-1 | Methyl isobutyl ketone | TWA  | 20 ppm                   | ACGIH     |
|          |                        | STEL | 75 ppm                   | ACGIH     |
|          |                        | TWA  | 50 ppm<br>205 mg/m3      | NIOSH REL |
|          |                        | ST   | 75 ppm<br>300 mg/m3      | NIOSH REL |
|          |                        | TWA  | 100 ppm<br>410 mg/m3     | OSHA Z-1  |
|          |                        | TWA  | 50 ppm<br>205 mg/m3      | OSHA P0   |
|          |                        | STEL | 75 ppm<br>300 mg/m3      | OSHA P0   |

### Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

SDS Number: 100000032157 5 / 13 Ethanol Spec IND PM 3224 190 Proof



# Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : Clear, Colorless

Odour : alcohol-like

Odour Threshold : No data available

pH : No data available

Freezing Point : No data available

Boiling Point : No data available

Flash point : 13.88 °C (56.98 °F)

Evaporation rate : 1.7

(Butyl Acetate = 1)

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : 1.6(Air = 1.0)

Relative density : 0.806 @ 25 °C (77 °F)

Reference substance: (water = 1)

Density : 0.806 g/cm3 @ 20 °C (68 °F)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

SDS Number: 100000032157 6 / 13 Ethanol Spec IND PM 3224 190 Proof



# Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

Auto-ignition temperature : No data available

Thermal decomposition : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Vapours may form explosive mixture with air.

Conditions to avoid : Keep away from heat, flame, sparks and other ignition

sources.

Incompatible materials : Acids

Alkali metals aluminum Ammonia Bases

lithium aluminum hydride

nitrates

Oxidizing agents Reducing agents

Peroxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 2,190 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

**Components:** 

67-56-1:

Acute oral toxicity : LDLo (Humans): 143 mg/kg

Assessment: The component/mixture is toxic after single in-

gestion.

SDS Number: 100000032157 7 / 13 Ethanol Spec IND PM 3224 190 Proof



# Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term

inhalation.

Remarks: Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry leaders and the EU

Harmonized Classification (Annex VII).

Acute dermal toxicity : LDLo (Monkey): 393 mg/kg

Assessment: The component/mixture is toxic after single con-

tact with skin.

108-10-1:

Acute inhalation toxicity : LC50 (Rat): 11.6 mg/l

Exposure time: 4 h Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after

short term inhalation.

### Serious eye damage/eye irritation

### **Components:**

64-17-5:

Species: Rabbit

Result: Irritating to eyes.

141-78-6:

Species: Rabbit

Result: Irritating to eyes.

108-10-1:

Species: Rabbit

Result: Irritating to eyes.

Carcinogenicity

IARC Group 2B: Possibly carcinogenic to humans

108-10-1 Methyl isobutyl ketone

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

### STOT - single exposure

#### Components:

67-56-1:

Target Organs: Eyes, Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

posure, category 1.

SDS Number: 100000032157 8 / 13 Ethanol Spec IND PM 3224 190 Proof



# Safety Data Sheet Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

141-78-6:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as

specific target organ toxicant, single exposure, category 3 with narcotic effects.

108-10-1:

Target Organs: Respiratory system

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

posure, category 3 with respiratory tract irritation.

**Further information** 

**Product:** 

Remarks: Solvents may degrease the skin.

### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

Persistence and degradability

No data available

**Bioaccumulative potential** 

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

SDS Number: 100000032157 9 / 13 Ethanol Spec IND PM 3224 190 Proof



# Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### SECTION 14. TRANSPORT INFORMATION

### **DOT (Department of Transportation):**

UN1987, ALCOHOLS, N.O.S., 3, II

### IATA (International Air Transport Association):

UN1987, ALCOHOLS, N.O.S., 3, II

#### **IMDG** (International Maritime Dangerous Goods):

UN1987, ALCOHOLS, N.O.S., 3, II, Flash Point:13.88 °C(56.98 °F)

#### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know Act**

### **CERCLA Reportable Quantity**

| Components    | CAS-No.  | Component RQ (lbs) | Calculated product RQ (lbs) |
|---------------|----------|--------------------|-----------------------------|
| Methanol      | 67-56-1  | 5000               | *                           |
| Ethyl acetate | 141-78-6 | 5000               | *                           |

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting re-

quirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

67-56-1 Methanol

Clean Air Act



## Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

67-56-1 Methanol

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

64-17-5 Ethanol 67-56-1 Methanol 141-78-6 Ethyl acetate

### **Clean Water Act**

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

75-07-0 Acetaldehyde 108-88-3 \*\*Toluene 71-43-2 \*\*Benzene 100-41-4 \*\*Ethylbenzene 91-20-3 \*\*Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

75-07-0 Acetaldehyde 108-88-3 \*\*Toluene 71-43-2 \*\*Benzene 100-41-4 \*\*Ethylbenzene 91-20-3 \*\*Naphthalene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

### **Massachusetts Right To Know**

| 64-17-5  | Ethanol       |
|----------|---------------|
| 67-56-1  | Methanol      |
| 141-78-6 | Ethyl acetate |
| 75-07-0  | Acetaldehyde  |

### Pennsylvania Right To Know

64-17-5 Ethanol 7732-18-5 Water 67-56-1 Methanol 141-78-6 Ethyl acetate

108-10-1 Methyl isobutyl ketone

75-07-0 Acetaldehyde

### California Prop 65

WARNING: This product can expose you to chemicals including Methyl isobutyl ketone, Acetaldehyde, \*\*Cumene, \*\*Benzene, \*\*Ethylbenzene, \*\*Naphthalene, which is/are known to the State of California to cause cancer, and Methanol, Methyl isobutyl ketone, \*\*Toluene, \*\*Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : Not in compliance with the inventory

SDS Number: 100000032157 11 / 13 Ethanol Spec IND PM 3224 190 Proof



# Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

NZIoC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI: Not in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory


IECSC : Not in compliance with the inventory

**Special Notes:** : \*\* Other substances in the product which may present a

health or environmental hazard.

### **SECTION16. OTHER INFORMATION**

#### NFPA:



Special hazard.

#### HMIS III:

| HEALTH          | 2 |
|-----------------|---|
| FLAMMABILITY    | 3 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

Revision Date : 08/28/2018

### Material number:

16118994, 16097562, 16045950, 743915, 622762, 160166, 117872, 160518, 132622, 132015, 131724, 117199, 145990, 20467

| Key or legend to abbreviations and acronyms used in the safety data sheet |   |       |                                      |
|---|---|-------|--------------------------------------|
| ACGIH   | American Conference of Government Industrial Hygienists | LD50  | Lethal Dose 50%                      |
| AICS  | Australia, Inventory of Chemical Substances             | LOAEL | Lowest Observed Adverse Effect Level |
| DSL   | Canada, Domestic Substances<br>List                     | NFPA  | National Fire Protection Agency      |

SDS Number: 100000032157 12 / 13 Ethanol Spec IND PM 3224 190 Proof



SDS Number: 100000032157

# Safety Data Sheet Ethanol Spec IND PM 3224 190 Proof

Version 1.1 Revision Date: 08/28/2018

| NDSL   | Canada, Non-Domestic Sub-                                | NIOSH        | National Institute for Occupational Safety   |
|--------|--|--------------|--|
|        | stances List   |              | & Health   |
| CNS    | Central Nervous System                                   | NTP          | National Toxicology Program  |
| CAS    | Chemical Abstract Service                                | NZIoC        | New Zealand Inventory of Chemicals   |
| EC50   | Effective Concentration                                  | NOAEL        | No Observable Adverse Effect Level   |
| EC50   | Effective Concentration 50%                              | NOEC         | No Observed Effect Concentration   |
| EGEST  | EOSCA Generic Exposure Scenario Tool                     | OSHA         | Occupational Safety & Health Administration  |
| EOSCA  | European Oilfield Specialty Chemicals Association        | PEL          | Permissible Exposure Limit   |
| EINECS | European Inventory of Existing Chemical Substances       | PICCS        | Philippines Inventory of Commercial Chemical Substances                              |
| MAK    | Germany Maximum Concentration Values                     | PRNT         | Presumed Not Toxic   |
| GHS    | Globally Harmonized System                               | RCRA         | Resource Conservation Recovery Act   |
| >=     | Greater Than or Equal To                                 | STEL         | Short-term Exposure Limit  |
| IC50   | Inhibition Concentration 50%                             | SARA         | Superfund Amendments and Reauthorization Act.  |
| IARC   | International Agency for Research on Cancer              | TLV          | Threshold Limit Value  |
| IECSC  | Inventory of Existing Chemical Substances in China       | TWA          | Time Weighted Average  |
| ENCS   | Japan, Inventory of Existing and New Chemical Substances | TSCA         | Toxic Substance Control Act  |
| KECI   | Korea, Existing Chemical Inventory                       | UVCB         | Unknown or Variable Composition, Complex Reaction Products, and Biological Materials |
| <=     | Less Than or Equal To                                    | WHMIS        | Workplace Hazardous Materials Information System                                     |
| LC50   |  | Lethal Conce | entration 50%  |