

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: #3914
Product Name: ESPRESSO
Revision Date: Jul 22, 2019 **Date Printed:** Jul 22, 2019
Version: 2.0 **Supersedes Date:** Oct 10, 2016
Manufacturer's Name: Repcolite Paints, Inc.
Address: 473 West 17th Street Holland, MI, US, 49423
Emergency Phone: 800-535-5053
Information Phone Number: 616-396-1275
Fax: 616-396-9654

SECTION 2) HAZARDS IDENTIFICATION

Classification

Acute aquatic toxicity - Category 3
 Acute toxicity Oral - Category 5
 Aspiration Hazard - Category 1
 Carcinogenicity - Category 1B
 Chronic aquatic toxicity - Category 2
 Flammable Liquids - Category 2
 Germ Cell Mutagenicity - Category 1B
 Reproductive Toxicity - Category 2
 Serious Eye Damage - Category 1
 Skin Irritation - Category 2
 Specific Target Organ Toxicity - Repeated Exposure - Category 1
 Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H225 - Highly flammable liquid and vapor

Hazardous Statements - Health

H303 - May be harmful if swallowed
 H304 - May be fatal if swallowed and enters airways
 H350 - May cause cancer

H340 - May cause genetic defects.
H361 - Suspected of damaging fertility or the unborn child
H318 - Causes serious eye damage
H315 - Causes skin irritation
H372 - Causes damage to organs through prolonged or repeated exposure.
H336 - May cause drowsiness or dizziness

Hazardous Statements - Environmental

H402 - Harmful to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention

P273 - Avoid release to the environment.
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242 - Use only non-sparking tools.
P243 - Take action to prevent static discharges.
P264 - Wash thoroughly after handling.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

P312 - Call a POISON CENTER/doctor if you feel unwell.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 - Do NOT induce vomiting.
P308 + P313 - IF exposed or concerned: Get medical advice/attention.
P391 - Collect spillage.
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P370 + P378 - In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P321 - For specific treatment see section 4.
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P362 + P364 - Take off contaminated clothing. And wash it before reuse.
P314 - Get Medical advice/attention if you feel unwell.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements - Storage

P405 - Store locked up.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P403 + P405 - Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Acute toxicity of 5% of the mixture is unknown

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0001333-86-4	CARBON BLACK	36% - 60%
0008052-41-3	STODDARD SOLVENT	6% - 13%
0001330-20-7	XYLENE	3% - 7%
0000110-19-0	ISO-BUTYL ACETATE	3% - 7%
0000071-36-3	N-BUTYL ALCOHOL	3% - 7%
0000078-83-1	ISOBUTYL ALCOHOL	3% - 7%
0064742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE	3% - 7%
0008032-32-4	NAPHTHA, VM&P	3% - 7%
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	3% - 7%
0000123-86-4	BUTYL ACETATE	0.1% - 1.8%
0064742-88-7	MEDIUM MINERAL SPIRITS	0.1% - 1.8%
0000067-63-0	ISOPROPYL ALCOHOL	0.1% - 1.6%
0000108-38-3	M-XYLENE	0.0% - 0.6%
0000067-64-1	ACETONE	0.0% - 0.6%
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	0.0% - 0.6%
0000106-42-3	P-XYLENE	0.0% - 0.3%
0000100-41-4	ETHYLBENZENE	0.0% - 0.3%
0000107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	0.0% - 0.2%
0000095-47-6	O-XYLENE	0.0% - 0.2%
0000057-55-6	PROPYLENE GLYCOL	Trace
0000095-63-6	1,2,4-TRIMETHYLBENZENE	Trace
0007757-82-6	SODIUM SULFATE	Trace
0000108-67-8	MESITYLENE	Trace
0000111-76-2	ETHYLENE GLYCOL MONOBUTYL ETHER	Trace
0000098-82-8	CUMENE	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed or unwell : Call a POISON CENTER/doctor

Skin Contact

Take off immediately contaminated clothing. Rinse skin with water/shower and mild soap for 5 minutes or until product is removed. Store contaminated clothing under water and wash before re-use or discard.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. If you feel unwell or are concerned : Get medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

No data available.

Indication of Any Immediate Medical Attention and Special Treatment Needed

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Unsuitable Extinguishing Media

No data available.

Specific Hazards in Case of Fire

Vapors are heavier than air and may travel along the ground to ignition sources at locations distant from material handling point.

Vapor accumulations and spray mist may flash or explode if ignited.

Closed containers may rupture due to pressure buildup when exposed to extreme heat.

Dried solids can burn.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Positive pressure, full-face piece self-contained breathing apparatus SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Absorb spill with inert absorbent.

Dike area to contain spill.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.
Do not get in eyes, on skin or on clothing.
Do not breathe vapors or mists.
Use good personal hygiene practices.
Eating, drinking and smoking in work areas is prohibited.
Remove contaminated clothing and protective equipment before entering eating areas.
Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.
Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.
Ground and bond containers and receiving equipment. Avoid static electricity by grounding.

SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

A suitable, NIOSH-approved respirator and goggles should be worn when standing or grinding objects coated with this paint.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	ACGIH TWA (ppm)
ACETONE	1000	2400			1			250
ALIPHATIC, LIGHT HYDROCARBON SOLVENT	500	2000			1			(L)[N159](L)[N800]
AROMATIC HYDROCARBON MIXTURE >C9	500	2000			1			(L)[N159](L)[N800]
BUTYL ACETATE	150	710			1			50
CARBON BLACK		3.5			1			
CUMENE	50	245			1		1	50

ETHYLBENZENE	100	435			1		20
ETHYLENE GLYCOL MONOBUTYL ETHER	50	240			1	1	20
ISO-BUTYL ACETATE	150	700			1		50
ISOBUTYL ALCOHOL	100	300			1		50
ISOPARAFFINIC PETROLEUM DISTILLATE	500	2000			1		(L)[N159](L)[N800]
ISOPROPYL ALCOHOL	400	980			1		200
MEDIUM MINERAL SPIRITS							(L)[N159](L)[N800]
M-XYLENE	100	435			1		100
NAPHTHA, VM&P							(L)
N-BUTYL ALCOHOL	100	300			1		20
O-XYLENE	100	435			1		100
PROPYLENE GLYCOL MONOMETHYL ETHER							50
P-XYLENE	100	435			1		100
STODDARD SOLVENT	500	2900			1		100
XYLENE	100	435			1		100

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
ACETONE		500		A4	A4; BEI	URT & eye irr; CNS impair
ALIPHATIC, LIGHT HYDROCARBON SOLVENT	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]
AROMATIC HYDROCARBON MIXTURE >C9	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]
BUTYL ACETATE		150				Eye & URT irr
CARBON BLACK	3 (I)			A3	A3	Bronchitis
CUMENE						Eye, skin, & URT irr; CNS impair
ETHYLBENZENE				A3	A3; BEI	URT irr; Kidney dam (nephropathy); Cochlear impair
ETHYLENE GLYCOL MONOBUTYL ETHER				A3	A3; BEI	Eye & URT irr
ISO-BUTYL		150				Eye &

ACETATE						URT irr
ISOBUTYL ALCOHOL						Skin & eye irr
ISOPARAFFINIC PETROLEUM DISTILLATE	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]
ISOPROPYL ALCOHOL		400		A4	A4; BEI	Eye & URT irr; CNS impair
MEDIUM MINERAL SPIRITS	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]
M-XYLENE		150		A4	A4; BEI	URT & eye irr; CNS impair
NAPHTHA, VM&P	[(L)]; [5 (I)];			[A2]; [A4];	[A2]; [A4];	URT irr
N-BUTYL ALCOHOL						Eye & URT irr
O-XYLENE		150		A4	A4; BEI	URT & eye irr; CNS impair
PROPYLENE GLYCOL MONOMETHYL ETHER		100		A4	A4	Eye & URT irr
P-XYLENE		150		A4	A4; BEI	URT & eye irr; CNS impair
STODDARD SOLVENT	[(L)]; [5 (I)];			[A2]; [A4];	[A2]; [A4];	Eye, skin, & kidney dam; nausea; CNS impair
XYLENE		150		A4	A4; BEI	URT & eye irr; CNS impair

(C) - Ceiling limit, (I) - Inhalable fraction, (L) - Exposure by all routes should be carefully controlled to levels as low as possible, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, dam - Damage, impair - Impairment, irr - Irritation, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	8.23521 lb/gal
% Solids By Weight	68.05480%
% VOC	31.89190%
Density VOC	2.62637 lb/gal
VOC Regulatory	3.74106 lb/gal
VOC Regulatory	448.29200 g/l

Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	N/A
Flash Point Symbol	N/A
Flash Point	N/A

Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Excessive heat.

Hazardous Reactions/Polymerization

No data available.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

May produce fumes when heated to decomposition.

Fumes may contain carbon monoxide and carbon dioxide.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely route of exposure

Ingestion, Inhalation, Skin absorption

Skin Corrosion/Irritation

Causes skin irritation

0000057-55-6 PROPYLENE GLYCOL

Contact can irritate the skin.

0000067-63-0 ISOPROPYL ALCOHOL

Contact can irritate and burn the skin. Prolonged or repeated contact can cause a skin rash, itching, dryness and redness.

0000067-64-1 ACETONE

Can cause skin irritation.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate and burn the skin.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the skin.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

Can irritate the skin.

May affect the central nervous system, blood, kidneys and liver. Exposure can cause headache, dizziness and lightheadedness.

0000123-86-4 BUTYL ACETATE

May cause effects on the central nervous system.

Serious Eye Damage/Irritation

Causes serious eye damage

0000057-55-6 PROPYLENE GLYCOL

Contact can irritate the eyes.

0000067-63-0 ISOPROPYL ALCOHOL

Liquid irritates eyes and may cause injury.

0000067-64-1 ACETONE

Exposure can irritate the eyes.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate and burn the eyes.

0000078-83-1 ISOBUTYL ALCOHOL

Contact with eyes is extremely irritating and may cause burns.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the eyes.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

Can irritate the eyes.

Can irritate the skin.

0000123-86-4 BUTYL ACETATE

Can severely irritate and burn the skin.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

The vapour is mildly irritating to the eyes.

Respiratory/Skin Sensitization

0000057-55-6 PROPYLENE GLYCOL

Prolonged or repeated contact can cause a skin rash dryness and redness.

0000067-64-1 ACETONE

Can irritate the nose and throat causing coughing and wheezing.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate the nose, throat and lungs. May cause dryness or cracking.

0000078-83-1 ISOBUTYL ALCOHOL

Can irritate the skin causing a rash. Breathing can irritate the nose, mouth and throat causing coughing and wheezing.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the respiratory tract.

0000110-19-0 ISO-BUTYL ACETATE

The substance defats the skin, which may cause dryness or cracking.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

Can irritate the eyes.

Can irritate the respiratory tract.

0000123-86-4 BUTYL ACETATE

Can severely irritate and burn the eyes.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

The substance defats the skin, which may cause dryness or cracking.

Germ Cell Mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer

Reproductive Toxicity

Suspected of damaging fertility or the unborn child

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The NOAEL for paternal toxicity is 300 ppm and for offspring toxicity is 1000 ppm. The NOAEL for maternal and fetotoxicity was considered to be 1500 ppm. Effects appear secondary to parental weight loss.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

Can irritate the respiratory tract.

0000123-86-4 BUTYL ACETATE

Can irritate the respiratory tract.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

0000057-55-6 PROPYLENE GLYCOL

Exposure can cause headache, dizziness, lightheadedness, and passing out.

0000067-63-0 ISOPROPYL ALCOHOL

Vapors cause mild irritation of upper respiratory tract; high concentrations may be anesthetic.

0000067-64-1 ACETONE

May affect the kidneys and liver.

0000071-36-3 N-BUTYL ALCOHOL

Exposure can cause headache, dizziness, nausea and vomiting. Can damage the liver and kidneys.

0000078-83-1 ISOBUTYL ALCOHOL

Exposure can cause headache, dizziness, drowsiness, confusion and loss of coordination. It may affect the liver.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Exposure to very high concentrations could cause depression of the central nervous system.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

May affect the central nervous system, blood, kidneys and liver. Exposure can cause headache, dizziness and lightheadedness.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

May cause effects on the central nervous system.

Specific Target Organ Toxicity - Repeated Exposure

Causes damage to organs through prolonged or repeated exposure.

0000057-55-6 PROPYLENE GLYCOL

Repeated high exposure may affect the kidneys.

0000067-63-0 ISOPROPYL ALCOHOL

Repeated high exposure can cause headache, dizziness, confusion, loss of coordination, unconsciousness and even death.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance defats the skin, which may cause dryness or cracking. Prolonged exposure to vapors may cause coughing, shortness of breath, dizziness and intoxication.

0000110-19-0 ISO-BUTYL ACETATE

The vapour is mildly irritating to the eyes and respiratory tract. The substance may cause effects on the central nervous system. Exposure far above the OEL could cause lowering of consciousness.

Aspiration Hazard

May be fatal if swallowed and enters airways

0000078-83-1 ISOBUTYL ALCOHOL

If swallowed, aspiration into the lungs may result in chemical pneumonitis.

Acute Toxicity

May be harmful if swallowed

0000067-63-0 ISOPROPYL ALCOHOL

If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

LC50 (Rat, Inhalation) = 16,000 ppm/8H Reference : Registry of Toxic Effects of Chemical Substances If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

LC50 (Rat, Inhalation) = 16,000 ppm/8H Reference : Registry of Toxic Effects of Chemical Substances If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

0000078-83-1 ISOBUTYL ALCOHOL

If swallowed, aspiration into the lungs may result in chemical pneumonitis.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

If swallowed, can easily enter the airways and could result in aspiration pneumonitis.

If swallowed, can easily enter the airways and could result in aspiration pneumonitis. Inhalation of high concentrations may cause dizziness, anesthesia, unconsciousness.

Potential Health Effects - Miscellaneous

0000067-63-0 ISOPROPYL ALCOHOL

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

0000071-36-3 N-BUTYL ALCOHOL

May cause abnormal blood forming function with anemia. Liquid splashes in the eye may result in chemical burns.

0000078-83-1 ISOBUTYL ALCOHOL

Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. May cause irritation of the mucous membranes. May cause abnormal liver function. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: bone marrow, liver. Prolonged skin contact may cause chemical burns. Liquid splashes in the eye may result in chemical burns.

0000100-41-4 ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Tests in laboratory animals have shown effects on any of the following organs/systems: kidneys, liver. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

Can be absorbed through the skin in harmful amounts. May cause injury to the kidneys, liver, blood and/or bone marrow. Repeated overexposure may result in damage to the blood. Eye contact may cause corneal injury. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

0000123-86-4 BUTYL ACETATE

May cause abnormal liver function. The following medical conditions may be aggravated by exposure: respiratory system. Tests for embryotoxic activity in animals has been inconclusive. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

0001330-20-7 XYLENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

0001333-86-4 CARBON BLACK

Is an IARC, NTP or OSHA carcinogen. Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. The following medical conditions may be aggravated by exposure: asthma, respiratory disease. WARNING: This chemical is known to the State of California to cause cancer.

0064742-88-7 MEDIUM MINERAL SPIRITS

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. This substance may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, lungs, reproductive system, skin. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-89-8 ALIPHATIC, LIGHT HYDROCARBON SOLVENT

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-95-6 AROMATIC HYDROCARBON MIXTURE >C9

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

Likely Routes of Exposure

0000067-63-0 ISOPROPYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapour.

0000067-64-1 ACETONE

Substance can be absorbed into the body by inhalation.

0000071-36-3 N-BUTYL ALCOHOL

Can be absorbed into the body by inhalation of its vapour and by ingestion.

0000078-83-1 ISOBUTYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance can be absorbed into the body by inhalation of its aerosol or vapour, through the skin and by ingestion.

0000110-19-0 ISO-BUTYL ACETATE

The substance can be absorbed into the body by inhalation of its vapour.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

The substance can be absorbed into the body by inhalation, through the skin and by ingestion.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

Chronic Exposure

0000098-82-8 CUMENE

TERATOGENIC EFFECTS: Cumene has been Classified as POSSIBLE for humans.

0000100-41-4 ETHYLBENZENE

CARCINOGENIC EFFECTS: Ethyl Benzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans.

TERATOGENIC EFFECTS: Ethyl Benzene has been Classified as POSSIBLE for humans.

0001330-20-7 XYLENE

High exposure to Xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus.

Xylene in high concentrations has caused embryotoxic effects in laboratory animals.

0001333-86-4 CARBON BLACK

CARCINOGENIC EFFECTS: In 1996, the IARC reevaluated Carbon Black as a Group 2B carcinogen. This evaluation is given to carbon black for which there is inadequate human evidence, but sufficient animal evidence.

Prolonged inhalation of Carbon black can result in lung disease. Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.

0000067-63-0 ISOPROPYL ALCOHOL

LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)

LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)

LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)

LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m3 (4-hour exposure) (29)
LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m3 (4-hour exposure) (29)
LD50 (oral, female rat): 5800 mg/kg (24)
LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)
LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)
LD50 (oral, mouse): 3000 mg/kg (32,unconfirmed)
LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

0000071-36-3 N-BUTYL ALCOHOL

LC50 (rat): greater than 8000 ppm (4-hour exposure) (14)
LD50 (oral, rat): 2510 mg/kg (15)
LD50 (oral, male rat): 790 mg/kg (16)*
LD50 (oral, female rat): 2020 mg/kg (16)* *(Note: the rats used in this study appear to have been very young (60-100 grams).)
LD50 (oral, hamster): 1200 mg/kg (11, original)

0000078-83-1 ISOBUTYL ALCOHOL

LD50 (oral, rat): 2460 mg/kg.(7)
LD50 (oral, rabbit): 3000 mg/kg (reported as 41 mmol/kg) (8)
LD50 (dermal, rabbit): 3400 mg/kg (reported as 4.24 mL/kg).(7)

0000095-47-6 O-XYLENE

LC50 (rat): 5300 ppm (4-hour exposure); cited as 4330 ppm (6-hour exposure) (3)
LC50 (mouse): 5630 ppm (4-hour exposure); cited as 4595 ppm (6-hour exposure) (3,4)
LD50 (oral, rat): 3608 mg/kg (3,16)
LD50 (dermal, rabbit): 20000 mg/kg (3)

0000095-63-6 1,2,4-TRIMETHYLBENZENE

LC50 (rat): 18 g/m3 (4-hour exposure) (1)
LD50 (oral, rat): 5 g/kg (1)

0000098-82-8 CUMENE

LC50 (inhalation, mouse): 10 mg/L; (2000 ppm); 7-hr exposure (1,3)
LC50 (inhalation, rat): 39 mg/L (8000 ppm); 4-hr exposure (1,3,6)
LD50 (oral, rat): Reported as 1.4 g/kg and 2.26 g/kg (1,3,4)
LD50 (skin, rabbit): 10627 mg/kg (4)

0000100-41-4 ETHYLBENZENE

LC50 (inhalation, rat): 4000 ppm; 4-hour exposure (3)
LD50 (oral, rat): 3.5 g/kg (1,3,5,10)
LD50 (oral, rat): 4.72 g/kg (3,5,7,8)
LD50 (dermal, rabbit): 17.8 g/kg (11)

0000106-42-3 P-XYLENE

LC50 (rat): 4740 ppm (4-hour exposure) (3)
LC50 (mouse): 4800 ppm (4-hour exposure); cited as 3900 ppm (6-hour exposure) (1,4,6)
LD50 (oral, rat): 4030 mg/kg (3); 4550 mg/kg (10)

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

LC50 (rat): 15000 ppm; 4-hr exposure (2)
LC50 (guinea pig): 15000 ppm; 10-hr exposure (2)
LD50 (oral, rat): 6.6 g/kg (5.2-7.5 g/kg) (10)
LD50 (oral, mouse): 10.7-10.8 g/kg (2,12)
LD50 (oral, dog): 4.6-5.5 g/kg (2); approximately 9.2 g/kg (2)
LD50 (oral, rabbit): 5.2-5.3 g/kg (2,12)
LD50 (dermal, rabbit): 13-14 g/kg (10)

0000108-38-3 M-XYLENE

LC50 (rat): 7330 ppm (4-hour exposure); cited as 5984 ppm (6-hour exposure) (3,17)
LC50 (mouse): 6450 ppm (4-hour exposure); cited as 5267 ppm (6-hour exposure) (3)
LD50 (oral, rat): 5011 mg/kg (3); 6660 mg/kg (3)
LD50 (dermal, rabbit): 12180 mg/kg (3,17)

0000108-67-8 MESITYLENE

LC50 (rat): 24 g/m3 (4-hour exposure) (2)

0000110-19-0 ISO-BUTYL ACETATE

LC50 (rat): approximately 8000 ppm (4-hour exposure); 4 out of 6 rats died (3)
LD50 (oral, rat): 13400 mg/kg (cited as 15.4 mL/kg) (1)

LD50 (oral, rabbit): 4800 mg/kg (cited as 41 mmol/kg) (4)
LD50 (dermal, rabbit): Greater than 5000 mg/kg (1)
0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

LC50 (female rat): 450 ppm (4-hour exposure) (2)
LC50 (male rat): 486 ppm (4-hour exposure) (2)

LD50 (oral, male weanling rat): 3000 mg/kg (1)
LD50 (oral, 6-week old male rat): 2400 mg/kg (1)
LD50 (oral, yearling male rat): 560 mg/kg (1)
LD50 (oral, female rat): 530 mg/kg; 2500 mg/kg (1) LD50 (oral, male mouse): 1230 mg/kg (1)
LD50 (oral, rabbit): 320 mg/kg (1)
LD50 (dermal, male rabbit): 406 mg/kg (cited as 0.45 mL/kg) (1)

0000123-86-4 BUTYL ACETATE

LC50 (rat): 1802 mg/m3; 4-hour exposure (aerosol)(9) Note: A lower LC50 (aerosol) value of 760 mg/m3 (160 ppm); 4-hour exposure has been reported.(11,27) Extensive research has failed to confirm this value.

LD50 (oral, rat): 10770 mg/kg (12, unconfirmed)
LD50 (oral, mouse): 7100 mg/kg (5)
LD50 (oral, rabbit): 7400 mg/kg (cited as 64 millimols/kg) (13)
LD50 (dermal, rabbit): Greater than 5000 mg/kg (3, unconfirmed)

0001330-20-7 XYLENE

LC50 (rat): 6350 ppm (4-hour exposure) (unspecified isomers and ethylbenzene) (1) LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2) ethylbenzene) (1)
LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene)(2)

LD50 (oral, rat): 5400 mg/kg (52% m-, 19% o-, 24% p-) (1) LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)
LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

0001333-86-4 CARBON BLACK

LC50 (rat): 6750 mg/m3 (4-hour exposure); cited as 27000 mg/m3 (27 mg/L) (1-hour exposure) (3)

0008052-41-3 STODDARD SOLVENT

LC50 (rat): greater than 5500 mg/m3 (880 ppm) (whole body exposure for 4 hours) (1)
LC50 (rat): greater than 8200 mg/m3 (1300 ppm) (2)

LD50 (oral, rat): greater than 5 g/kg (1)
LD50 (dermal, rabbit): greater than 3 g/kg (1)

SECTION 12) ECOLOGICAL INFORMATION

Bio-accumulative Potential

0000067-63-0 ISOPROPYL ALCOHOL

Substance is not expected to bioaccumulate.

0000110-19-0 ISO-BUTYL ACETATE

No potential for bioaccumulation.

Persistence and Degradability

0000067-63-0 ISOPROPYL ALCOHOL

Readily biodegradable

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Readily biodegradable.

0000071-36-3 N-BUTYL ALCOHOL

Readily biodegradable.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Readily biodegradable in water. Half-life in air = 3.1 hours.

0000110-19-0 ISO-BUTYL ACETATE

Readily biodegradable.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

Readily biodegradable.

Readily biodegradable

0000123-86-4 BUTYL ACETATE

Readily biodegradable

0001330-20-7 XYLENE

50% of applied radiolabelled o-xylene was mineralised in 23 days, and 50% p-xylene was mineralised in 13 days.

0001333-86-4 CARBON BLACK

Carbon Black's insolubility in water results in it not being biodegradable in any medium or by biota. It is considered persistent in the natural environment.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Expected to be inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.

Mobility in Soil

0000067-64-1 ACETONE

The substance is not PBT / vPvB

The substance is not PBT / vPvB.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Floats on water. Contains volatile constituents. Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater.

Toxicity

Harmful to aquatic life

Toxic to aquatic life with long lasting effects

0000123-86-4 BUTYL ACETATE

Readily biodegradable

Other adverse effects

No data available.

Results of the PBT and vPvB assessment

0000067-63-0 ISOPROPYL ALCOHOL

Substance is readily biodegradable and therefore not considered to be persistent. It is not expected to bioaccumulate as it has a Log Kow < 4.5 and aquatic acute toxicity greatly exceeds the screening criteria of EC50 < 0.1 mg/l.

0000071-36-3 N-BUTYL ALCOHOL

The substance is not PBT/vPvB

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance is not PBT / vPvB.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

The substance is not PBT / vPvB

The substance is not PBT / vPvB.

0000123-86-4 BUTYL ACETATE

The substance is not PBT / vPvB

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

IMDG Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II
Marine Pollutant : No data available

IATA Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

SECTION 15) REGULATORY INFORMATION

REGULATORY INFORMATION

TSCA Inventory: All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List: All components of this product are listed on the Domestic Substances List

CAS	Chemical Name	% By Weight	Regulation List
0001333-86-4	CARBON BLACK	36% - 60%	DSL,SARA312,CA_Carcinogen,WI_N R438 - WI_N R438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0008052-41-3	STODDARD SOLVENT	6% - 13%	Canada_NPRI,DSL,SARA312,WI_N R438 - WI_N R438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0001330-20-7	XYLENE	3% - 7%	SARA313, Canada_NPRI,DSL,HAPS,SARA312, WI_N R438 - WI_N R438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000110-19-0	ISO-BUTYL ACETATE	3% - 7%	Canada_NPRI,DSL,SARA312,WI_N R438 - WI_N R438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000071-36-3	N-BUTYL ALCOHOL	3% - 7%	SARA313, Canada_NPRI,DSL,SARA312,WI_N R438 - WI_N R438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000078-83-1	ISOBUTYL ALCOHOL	3% - 7%	Canada_NPRI,DSL,SARA312,WI_N R438 - WI_N R438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0064742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE	3% - 7%	Canada_NPRI,DSL,SARA312
0008032-32-4	NAPHTHA, VM&P	3% - 7%	Canada_NPRI,DSL,SARA312
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	3% - 7%	Canada_NPRI,DSL,SARA312
0000123-86-4	BUTYL ACETATE	0.1% - 1.8%	Canada_NPRI,DSL,SARA312,WI_N

			R438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0064742-88-7	MEDIUM MINERAL SPIRITS	0.1% - 1.8%	Canada_NPRI,DSL,SARA312
0000067-63-0	ISOPROPYL ALCOHOL	0.1% - 1.6%	Canada_NPRI,DSL,SARA312
0000108-38-3	M-XYLENE	0.0% - 0.6%	SARA313, Canada_NPRI,DSL,HAPS,SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000067-64-1	ACETONE	0.0% - 0.6%	DSL,SARA312,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	0.0% - 0.6%	Canada_NPRI,DSL,SARA312
0000106-42-3	P-XYLENE	0.0% - 0.3%	SARA313, Canada_NPRI,DSL,HAPS,SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000100-41-4	ETHYLBENZENE	0.0% - 0.3%	SARA313, Canada_NPRI,DSL,HAPS,SARA312, CA_Carcinogen,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	0.0% - 0.2%	Canada_NPRI,DSL,SARA312,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000095-47-6	O-XYLENE	0.0% - 0.2%	SARA313, Canada_NPRI,DSL,HAPS,SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000057-55-6	PROPYLENE GLYCOL	Trace	DSL,SARA312
0000095-63-6	1,2,4-TRIMETHYLBENZENE	Trace	Canada_NPRI,DSL,SARA312
0007757-82-6	SODIUM SULFATE	Trace	DSL,SARA312
0000108-67-8	MESITYLENE	Trace	Canada_NPRI,DSL,SARA312
0000111-76-2	ETHYLENE GLYCOL MONOBUTYL ETHER	Trace	Canada_NPRI,DSL,SARA312,CA_TAC_Carcinogen,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000098-82-8	CUMENE	Trace	Canada_NPRI,DSL,HAPS,SARA312, CA_Carcinogen,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS

The information in this Section does not list components that might have relevant SARA312 regulatory values, if they are present at less than 25%. Please contact manufacturer for more information.

SECTION 16) OTHER INFORMATION

General

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-

HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 2
FLAMMABILITY	3
Physical Hazard	0
Personal Protection	X

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 2.0:

Revision Date: Jul 22, 2019

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.