

## SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

**Product ID:** #8610

**Product Name:** BLANC TULLE BASE

**Revision Date:** Feb 11, 2020 **Date Printed:** Feb 11, 2020

**Version:** 1.0 **Supersedes Date:** N.A.

**Manufacturer's Name:** Repolite Paints, Inc.

**Address:** 473 West 17th Street Holland, MI, US, 49423

**Emergency Phone:** 800-535-5053

**Information Phone Number:** 616-396-1275

**Fax:** 616-396-9654

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Chronic aquatic toxicity - Category 3

Eye Irritation - Category 2A

Skin Irritation - Category 3

### Pictograms



### Signal Word

Warning

### Hazardous Statements - Health

H319 - Causes serious eye irritation

H316 - Causes mild skin irritation

### Hazardous Statements - Environmental

H412 - Harmful to aquatic life with long lasting effects

### Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

### Precautionary Statements - Prevention

P273 - Avoid release to the environment.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

### Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

### Precautionary Statements - Storage

No precautionary statement available.

### Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

**Acute toxicity of 20.8% of the mixture is unknown**

## SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

| CAS          | Chemical Name  | % By Weight |
|--------------|--|-------------|
| 0013463-67-7 | TITANIUM DIOXIDE                                       | 12% - 28%   |
| 0066402-68-4 | CERAMIC FIBERS (AIRBORNE PARTICLES OF RESPIRABLE SIZE) | 2% - 5%     |
| 0025265-77-4 | 2,2,4-TRIMETHYL PENTANEDIOL 1,3-MONOSOBUTYRAT          | 1.2% - 3%   |
| 0007631-86-9 | SILICA, AMORPHOUS                                      | 0.2% - 1.7% |
| 0001314-23-4 | ZIRCONIA OXIDE   | 0.0% - 0.2% |
| 0000124-68-5 | 2-AMINO-2-METHYL-1-PROPANOL                            | 0.0% - 0.2% |
| 0000577-11-7 | DI-2-ETHYLHEXYL SODIUM SULFOSUCCINATE                  | Trace       |
| 0000112-34-5 | DIETHYLENE GLYCOL MONOBUTYL ETHER                      | Trace       |
| 0002634-33-5 | 1,2-BENZISOTHIAZOL-3(2H)-ONE                           | Trace       |
| 0055406-53-6 | 3-iodo-2-propynyl butylcarbamate                       | Trace       |
| 0000064-17-5 | ETHYL ALCOHOL  | Trace       |
| 0005567-15-7 | PIGMENT YELLOW 83                                      | Trace       |
| 0000095-63-6 | 1,2,4-TRIMETHYLBENZENE                                 | Trace       |
| 0000104-76-7 | 2-ETHYL-1-HEXANOL                                      | Trace       |
| 0000109-60-4 | N-PROPYL ACETATE                                       | Trace       |
| 0001333-86-4 | CARBON BLACK   | Trace       |
| 0000108-67-8 | MESITYLENE   | Trace       |
| 0000091-20-3 | NAPHTHALENE  | Trace       |
| 0025340-17-4 | DIETHYLBENZENE   | Trace       |
| 0007631-90-5 | SODIUM BISULFITE                                       | Trace       |

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## SECTION 4) FIRST-AID MEASURES

### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

Get medical advice/attention if you feel unwell or are concerned.

### Skin Contact

Rinse/wash with lukewarm, gently flowing water (and mild soap) for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

### Eye Contact

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

If you feel unwell or if concerned: Get medical advice/attention.

### **Ingestion**

Rinse mouth. If you feel unwell or are concerned : Get medical advice/attention.

## **SECTION 5) FIRE-FIGHTING MEASURES**

### **Suitable Extinguishing Media**

Dry chemical, foam, or carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### **Unsuitable Extinguishing Media**

No data available.

### **Specific Hazards in Case of Fire**

Product will not burn but may spatter if temperature exceeds the boiling point of water.  
Dried solids can burn.

### **Fire-fighting Procedures**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### **Special Protective Actions**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## **SECTION 6) ACCIDENTAL RELEASE MEASURES**

### **Emergency Procedure**

Keep unnecessary people away; Do not touch or walk through spilled material. Clean up immediately. Evacuate area and ventilate. Flammable/combustible material.

### **Recommended Equipment**

Positive pressure, full-face piece self-contained breathing apparatus SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

### **Personal Precautions**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### **Environmental Precautions**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### **Methods and Materials for Containment and Cleaning up**

Dike area to contain spill.

Absorb spill with inert absorbent.

## **SECTION 7) HANDLING AND STORAGE**

### **General**

Wash hands after use.  
Do not get in eyes, on skin or on clothing.  
Do not breathe vapors or mists.  
Use good personal hygiene practices.  
Eating, drinking and smoking in work areas is prohibited.  
Remove contaminated clothing and protective equipment before entering eating areas.

### **Ventilation Requirements**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

## Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Keep from freezing.

## SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

### Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

### Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

### Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

| Chemical Name  | OSHA TWA (ppm) | OSHA TWA (mg/m3)        | OSHA STEL (ppm) | OSHA STEL (mg/m3) | OSHA Tables (Z1, Z2, Z3) | OSHA Carcinogen | OSHA Skin designation | ACGIH TWA (ppm) |
|--|----------------|-------------------------|-----------------|-------------------|--------------------------|-----------------|-----------------------|-----------------|
| CARBON BLACK   |                | 3.5                     |                 |                   | 1                        |                 |                       |                 |
| CERAMIC FIBERS (AIRBORNE PARTICLES OF RESPIRABLE SIZE) |                |                         |                 |                   |                          |                 |                       |                 |
| DIETHYLENE GLYCOL MONOBUTYL ETHER                      |                |                         |                 |                   |                          |                 |                       | 10(IFV)         |
| ETHYL ALCOHOL  | 1000           | 1900                    |                 |                   | 1                        |                 |                       |                 |
| NAPHTHALENE  | 10             | 50                      |                 |                   | 1                        |                 |                       | 10              |
| N-PROPYL ACETATE                                       | 200            | 840                     |                 |                   | 1                        |                 |                       | 100             |
| SILICA, AMORPHOUS                                      | 20 (b)         | 80 mg/m3 percent SiO2+2 |                 |                   | 1,3                      |                 |                       |                 |
| SODIUM BISULFITE                                       |                |                         |                 |                   |                          |                 |                       |                 |
| TITANIUM DIOXIDE                                       |                | 15                      |                 |                   | 1                        |                 |                       |                 |
| ZIRCONIA OXIDE   |                | 5                       |                 |                   | 1                        |                 |                       |                 |

| Chemical Name | ACGIH TWA (mg/m3) | ACGIH STEL (ppm) | ACGIH STEL (mg/m3) | ACGIH Carcinogen | ACGIH Notations | ACGIH TLV Basis |
|---------------|-------------------|------------------|--------------------|------------------|-----------------|-----------------|
| CARBON        | 3 (I)             |                  |                    | A3               | A3              | Bronchitis      |

|  |     |      |    |    |               |                                      |
|--|-----|------|----|----|---------------|--------------------------------------|
| BLACK  |     |      |    |    |               |                                      |
| CERAMIC FIBERS (AIRBORNE PARTICLES OF RESPIRABLE SIZE) | 0.5 |      |    | A4 | A4            | Skin & URT irr                       |
| DIETHYLENE GLYCOL MONOBUTYL ETHER                      |     |      |    |    |               | Hematologic, liver & kidney eff      |
| ETHYL ALCOHOL  |     | 1000 |    | A3 | A3            | URT irr                              |
| NAPHTHALENE  |     |      |    | A3 | Skin; A3; BEI | URT irr; cataracts; hemolytic anemia |
| N-PROPYL ACETATE                                       |     | 150  |    |    |               | Eye & URT irr; CNS impair            |
| SILICA, AMORPHOUS                                      |     |      |    |    |               |                                      |
| SODIUM BISULFITE                                       | 5   |      |    | A4 | A4            | Skin; eye, & URT irr                 |
| TITANIUM DIOXIDE                                       | 10  |      |    | A4 | A4            | LRT irr                              |
| ZIRCONIA OXIDE   | 5   |      | 10 | A4 | A4            | Resp irr                             |

(C) - Ceiling limit, (I) - Inhalable fraction, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, eff - Effects, impair - Impairment, irr - Irritation, LRT - Lower respiratory tract, resp - respiratory, URT - Upper respiratory tract

The information in this Section does not list components that might have relevant ACGIH TWA (mg/m3), ACGIH STEL (ppm), ACGIH Carcinogen, ACGIH Notations, ACGIH TLV Basis, OSHA TWA (ppm), OSHA TWA (mg/m3), OSHA Tables (Z1, Z2, Z3), ACGIH TWA (ppm) regulatory values, if they are present at less than 10%. Please contact manufacturer for more information.

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

|                    |                 |
|--------------------|-----------------|
| Density            | 10.65550 lb/gal |
| % Solids By Weight | 48.10290%       |
| % VOC              | 5.33381%        |
| Density VOC        | 0.56834 lb/gal  |
| VOC Regulatory     | 1.31763 lb/gal  |
| VOC Regulatory     | 157.89200 g/l   |

|                       |     |
|-----------------------|-----|
| Appearance            | N/A |
| Odor Threshold        | N/A |
| Odor Description      | N/A |
| pH                    | N/A |
| Water Solubility      | N/A |
| Flammability          | N/A |
| Flash Point Symbol    | N/A |
| Flash Point           | N/A |
| Viscosity             | N/A |
| Lower Explosion Level | N/A |
| Upper Explosion Level | N/A |
| Vapor Pressure        | N/A |

|                       |        |
|-----------------------|--------|
| Vapor Density         | NA     |
| Freezing Point        | 32 °F  |
| Melting Point         | N/A    |
| Low Boiling Point     | 212 °F |
| High Boiling Point    | N/A    |
| Auto Ignition Temp    | N/A    |
| Decomposition Pt      | N/A    |
| Evaporation Rate      | N/A    |
| Coefficient Water/Oil | N/A    |

## SECTION 10) STABILITY AND REACTIVITY

### Stability

Stable.

### Conditions to Avoid

Prevent from freezing.

### Hazardous Reactions/Polymerization

No data available.

### Incompatible Materials

Strong oxidizers.

### Hazardous Decomposition Products

Burning of dried solids may give off oxides of carbon and nitrogen.

## SECTION 11) TOXICOLOGICAL INFORMATION

### Skin Corrosion/Irritation

Prolonged contact may produce temporary reddening of skin.

Causes mild skin irritation

0000064-17-5 ETHYL ALCOHOL

Contact can irritate the skin. Prolonged or repeated exposure can cause drying and cracking of the skin with peeling, redness and itching.

0000109-60-4 N-PROPYL ACETATE

Contact can irritate the skin.

### Serious Eye Damage/Irritation

Direct contact may cause eye irritation.

Causes serious eye irritation

0000109-60-4 N-PROPYL ACETATE

Contact can irritate the eyes.

0000112-34-5 DIETHYLENE GLYCOL MONOBUTYL ETHER

Can be irritating to the eyes.

### Respiratory/Skin Sensitization

May contain products that will irritate mucous membrane and respiratory tract.

0000109-60-4 N-PROPYL ACETATE

The vapour is mildly irritating to the respiratory tract.

0000112-34-5 DIETHYLENE GLYCOL MONOBUTYL ETHER

May cause dryness and cracking.

### Germ Cell Mutagenicity

No data available.

## Carcinogenicity

No data available.

## Reproductive Toxicity

0000064-17-5 ETHYL ALCOHOL

High concentration may damage the fetus.

## Specific Target Organ Toxicity - Single Exposure

0000064-17-5 ETHYL ALCOHOL

Exposure can cause headache, drowsiness, nausea and vomiting, and unconsciousness. It can also affect concentration and vision.

0000109-60-4 N-PROPYL ACETATE

May cause effects on the central nervous system and the liver. Exposure can cause headache, dizziness, lightheadedness and loss of consciousness.

## Specific Target Organ Toxicity - Repeated Exposure

0000064-17-5 ETHYL ALCOHOL

Repeated high exposure may affect the liver and the nervous system. Chronic ingestion of ethanol may cause liver cirrhosis.

## Aspiration Hazard

No data available.

## Acute Toxicity

Inhalation may produce symptoms of headache and nausea in poorly ventilated areas.

0000064-17-5 ETHYL ALCOHOL

Inhalation can irritate the nose, throat and lungs.

0000109-60-4 N-PROPYL ACETATE

Inhaling can irritate the nose and throat causing coughing and wheezing.

## Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0000064-17-5 ETHYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapor or by ingestion.

## Potential Health Effects - Miscellaneous

0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

0000091-20-3 NAPHTHALENE

Is an IARC, NTP or OSHA carcinogen. Tests in some laboratory animals demonstrate carcinogenic activity. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: kidneys, liver. Recurrent overexposure may result in liver and kidney injury. WARNING: This chemical is known to the State of California to cause cancer.

0001333-86-4 CARBON BLACK

Is an IARC, NTP or OSHA carcinogen. Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. The following medical conditions may be aggravated by exposure: asthma, respiratory disease. WARNING: This chemical is known to the State of California to cause cancer.

0013463-67-7 TITANIUM DIOXIDE

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m<sup>3</sup> respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m<sup>3</sup> level are not relevant to the workplace. Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.

## Chronic Exposure

0001333-86-4 CARBON BLACK

CARCINOGENIC EFFECTS: In 1996, the IARC reevaluated Carbon Black as a Group 2B carcinogen. This evaluation is given to carbon black for which there is inadequate human evidence, but sufficient animal evidence.

Prolonged inhalation of Carbon black can result in lung disease. Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.

0000064-17-5 ETHYL ALCOHOL

LC50 (mouse): Approximately 21000 ppm (4-hour exposure); cited as 39 g/m3 (4-hour exposure) (1, unconfirmed)

LD50 (oral, rat): 7060 mg/kg (41); 10600 mg/kg (41); 13660 mg/kg (37)

LD50 (oral, mouse): 3450 mg/kg (1, unconfirmed)

LD50 (oral, guinea pig): 5560 mg/kg (37)

0000091-20-3 NAPHTHALENE

LC50: Insufficient data

LD50 (oral, mouse): 533 mg/kg (male); 710 mg/kg (female) (1)

LD50 (oral, rat): 1780 mg/kg (2)

0000095-63-6 1,2,4-TRIMETHYLBENZENE

LC50 (rat): 18 g/m3 (4-hour exposure) (1)

LD50 (oral, rat): 5 g/kg (1)

0000108-67-8 MESITYLENE

LC50 (rat): 24 g/m3 (4-hour exposure) (2)

0000109-60-4 N-PROPYL ACETATE

LD50 (oral, rat): 8700 mg/kg; cited as 9.8 mL/kg (4)

LD50 (oral, mouse): 8300 mg/kg (5)

LD50 (oral, rabbit): 6600 mg/kg; cited as 65 mmols/kg (6)

LD50 (dermal, rabbit): Greater than 17700 mg/kg; cited as 20 mL/kg (4)

0001333-86-4 CARBON BLACK

LC50 (rat): 6750 mg/m3 (4-hour exposure); cited as 27000 mg/m3 (27 mg/L) (1-hour exposure) (3)

## SECTION 12) ECOLOGICAL INFORMATION

### Bio-accumulative Potential

0000064-17-5 ETHYL ALCOHOL

Substance has a low potential for bioaccumulation (log Kow3),

### Persistence and Degradability

0000064-17-5 ETHYL ALCOHOL

Readily biodegradable. Half-life in air = 38 h

0000109-60-4 N-PROPYL ACETATE

Readily biodegradable.

0000112-34-5 DIETHYLENE GLYCOL MONOBUTYL ETHER

Readily biodegradable.

0001333-86-4 CARBON BLACK

Carbon Black's insolubility in water results in it not being biodegradable in any medium or by biota. It is considered persistent in the natural environment.

### Mobility in Soil

0000109-60-4 N-PROPYL ACETATE

The substance is not PBT / vPvB

The substance is not PBT / vPvB.

### Toxicity

Harmful to aquatic life with long lasting effects

0000064-17-5 ETHYL ALCOHOL

S gairdneri: 13.0g/l (96hr LC50) Nauplii : 858 g/l (48hr EC50) Ceriodaphnia dubia : 9.6mg/l (10 day NOEC) Freshwater Fish 250mg/l (NOEC) Reference: REACH registration Dossier.

### Other adverse effects

No data available.

### Results of the PBT and vPvB assessment

**SECTION 13) DISPOSAL CONSIDERATIONS****Waste Disposal**

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

**SECTION 14) TRANSPORT INFORMATION****U.S. DOT Information**

Not regulated by the US Department of Transportation.

**IMDG Information**

No data available.

**IATA Information**

No data available.

**SECTION 15) REGULATORY INFORMATION**

| CAS          | Chemical Name  | % By Weight | Regulation List   |
|--------------|--|-------------|---|
| 0007732-18-5 | WATER  | 34% - 57%   | TSCA  |
| 0013463-67-7 | TITANIUM DIOXIDE                                       | 12% - 28%   | SARA312,TSCA,CA_Carcinogen,CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer                           |
| proprietary  | resin solids   | 10% - 23%   | SARA312   |
| 0066402-68-4 | CERAMIC FIBERS (AIRBORNE PARTICLES OF RESPIRABLE SIZE) | 2% - 5%     | SARA313, Canada_NPRI,HAPS,SARA312,TSCA,CA_Carcinogen,CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer |
| 0025265-77-4 | 2,2,4-TRIMETHYL PENTANEDIOL 1,3-MONOISOBUTYRAT         | 1.2% - 3%   | SARA312,VOC,TSCA  |
| 0007631-86-9 | SILICA, AMORPHOUS                                      | 0.2% - 1.7% | SARA312,TSCA  |
| 0001314-23-4 | ZIRCONIA OXIDE   | 0.0% - 0.2% | SARA312,TSCA  |
| 0000124-68-5 | 2-AMINO-2-METHYL-1-PROPANOL                            | 0.0% - 0.2% | SARA312,VOC,VOC_exempt,TSCA   |
| 0000577-11-7 | DI-2-ETHYLHEXYL SODIUM SULFOSUCCINATE                  | Trace       | SARA312,TSCA  |
| 0001336-21-6 | AMMONIUM HYDROXIDE                                     | Trace       | SARA313, Canada_NPRI,SARA312,TSCA   |
| 0000112-34-5 | DIETHYLENE GLYCOL MONOBUTYL ETHER                      | Trace       | SARA313, Canada_NPRI,HAPS,SARA312,VHAPS,VOC,TSCA,CA_TAC_Carcinogen  |
| 0002634-33-5 | 1,2-BENZISOTHIAZOL-3(2H)-ONE                           | Trace       | SARA312,TSCA  |
| 0055406-53-6 | 3-iodo-2-propynyl butylcarbamate                       | Trace       | SARA313, SARA312,TSCA   |
| 0000064-17-5 | ETHYL ALCOHOL  | Trace       | Canada_NPRI,SARA312,VOC,TSCA  |

|              |                        |       |   |
|--------------|------------------------|-------|---|
| 0005567-15-7 | PIGMENT YELLOW 83      | Trace | SARA312,TSCA  |
| 0000095-63-6 | 1,2,4-TRIMETHYLBENZENE | Trace | SARA313,<br>Canada_NPRI,SARA312,VOC,TSCA  |
| 0000104-76-7 | 2-ETHYL-1-HEXANOL      | Trace | SARA312,VOC,TSCA  |
| 0000121-44-8 | TRIETHYLAMINE          | Trace | SARA313,<br>Canada_NPRI,HAPS,SARA312,VHA<br>PS,VOC,TSCA   |
| 0000109-60-4 | N-PROPYL ACETATE       | Trace | Canada_NPRI,SARA312,VOC,TSCA  |
| 0001333-86-4 | CARBON BLACK           | Trace | SARA312,TSCA,CA_Carcinogen,CA<br>_Prop65_Type_Toxicity_Cancer -<br>CA_Proposition65_Type_Toxicity_Ca<br>ncer  |
| 0000108-67-8 | MESITYLENE             | Trace | Canada_NPRI,SARA312,VOC,TSCA  |
| 0000091-20-3 | NAPHTHALENE            | Trace | SARA313,<br>Canada_NPRI,HAPS,SARA312,VHA<br>PS,VOC,TSCA,CA_Carcinogen,CA<br>_Prop65_Type_Toxicity_Cancer -<br>CA_Proposition65_Type_Toxicity_Ca<br>ncer |
| 0025340-17-4 | DIETHYLBENZENE         | Trace | SARA312,VOC,TSCA  |
| 0007631-90-5 | SODIUM BISULFITE       | Trace | SARA312,TSCA  |

The information in this Section does not list components that might have relevant Canada\_NPRI, SARA312, TSCA, VOC regulatory values, if they are present at less than 10%. Please contact manufacturer for more information.

## SECTION 16) OTHER INFORMATION

### General

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

### HMIS

|                     |     |
|---------------------|-----|
| Health              | / 1 |
| FLAMMABILITY        | 0   |
| Physical Hazard     | 0   |
| Personal Protection | X   |

( \* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

## DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.