

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: #979
Product Name: SABLE ON WALNUT DYE
Revision Date: Mar 17, 2020
Version: 1.0
Manufacturer's Name: Repolite Paints, Inc.
Address: 473 West 17th Street Holland, MI, US, 49423
Emergency Phone: 800-535-5053
Information Phone Number: 616-396-1275
Fax: 616-396-9654

Date Printed: Mar 17, 2020
Supersedes Date: N.A.

SECTION 2) HAZARDS IDENTIFICATION

Classification

Acute toxicity Oral - Category 5
Carcinogenicity - Category 1B
Eye Irritation - Category 2A
Flammable Liquids - Category 2
Flammables solids - Category 1
Germ Cell Mutagenicity - Category 1B
Skin Irritation - Category 3
Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H225 - Highly flammable liquid and vapor
H228 - Flammable solid

Hazardous Statements - Health

H303 - May be harmful if swallowed
H350 - May cause cancer
H319 - Causes serious eye irritation
H340 - May cause genetic defects.
H316 - Causes mild skin irritation
H336 - May cause drowsiness or dizziness

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P264 - Wash thoroughly after handling.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 - Use only non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 - Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

P312 - Call a POISON CENTER/doctor if you feel unwell.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P370 + P378 - In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements - Storage

P405 - Store locked up.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P403 + P405 - Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Acute toxicity of 1.5% of the mixture is unknown

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000064-17-5	ETHYL ALCOHOL	36% - 61%
0000067-64-1	ACETONE	27% - 45%
0000108-65-6	PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	3% - 6%
0000107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	2% - 5%
0000109-60-4	N-PROPYL ACETATE	0.1% - 2%

0000067-63-0	ISOPROPYL ALCOHOL	0.1% - 2.0%
0000141-78-6	ETHYL ACETATE	0.1% - 1.5%
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	0.0% - 0.6%
0000123-86-4	BUTYL ACETATE	Trace
0000108-88-3	TOLUENE	Trace
0009004-70-0	NITROCELLULOSE	Trace
0000078-83-1	ISOBUTYL ALCOHOL	Trace
0000071-36-3	N-BUTYL ALCOHOL	Trace
0007631-86-9	SILICA, AMORPHOUS	Trace
0001330-20-7	XYLENE	Trace
0000100-41-4	ETHYLBENZENE	Trace
0000062-53-3	ANILINE	Trace
0000050-00-0	FORMALDEHYDE	Trace
0000108-95-2	PHENOL	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed or unwell : Call a POISON CENTER/doctor

Skin Contact

Take off immediately contaminated clothing. Rinse skin with water/shower and mild soap for 5 minutes or until product is removed. Store contaminated clothing under water and wash before re-use or discard.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. If you feel unwell or are concerned : Get medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

No data available.

Indication of Any Immediate Medical Attention and Special Treatment Needed

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Unsuitable Extinguishing Media

No data available.

Specific Hazards in Case of Fire

Vapors are heavier than air and may travel along the ground to ignition sources at locations distant from material handling point.

Vapor accumulations and spray mist may flash or explode if ignited.

Closed containers may rupture due to pressure buildup when exposed to extreme heat.

Dried solids can burn.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged

containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Absorb spill with inert absorbent.

Dike area to contain spill.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Ground and bond containers and receiving equipment. Avoid static electricity by grounding.

SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

A suitable, NIOSH-approved respirator and goggles should be worn when standing or grinding objects coated with this paint.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	ACGIH TWA (ppm)
ACETONE	1000	2400			1			250
ALIPHATIC, LIGHT HYDROCARBON SOLVENT	500	2000			1			(L)[N159](L)[N800]
ANILINE	5	19			1		1	2
BUTYL ACETATE	150	710			1			50
ETHYL ACETATE	400	1400			1			400
ETHYL ALCOHOL	1000	1900			1			
ETHYLBENZENE	100	435			1			20
FORMALDEHYDE	0.75 (a)		2 / 15minutes		1,2	1		0.1
ISOBUTYL ALCOHOL	100	300			1			50
ISOPROPYL ALCOHOL	400	980			1			200
N-BUTYL ALCOHOL	100	300			1			20
N-PROPYL ACETATE	200	840			1			100
PHENOL	5	19			1		1	5
PROPYLENE GLYCOL MONOMETHYL ETHER								50
SILICA, AMORPHOUS	20 (b)	80 mg/m3 percent SiO2+2			1,3			
TOLUENE	200 (a)/ 300 ceiling	0.2	500ppm /10 minutes (a)		1,2			20
XYLENE	100	435			1			100

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
ACETONE		500		A4	A4; BEI	URT & eye irr; CNS impair
ALIPHATIC, LIGHT HYDROCARBON SOLVENT	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]

ANILINE			A3	Skin; A3; BEI	MeHb-emia
BUTYL ACETATE	150				Eye & URT irr
ETHYL ACETATE					URT & eye irr
ETHYL ALCOHOL	1000		A3	A3	URT irr
ETHYLBENZENE			A3	A3; BEI	URT irr; Kidney dam (nephropathy); Cochlear impair
FORMALDEHYDE	0.3		A1	DSEN; RSEN; A1	URT & eye irr; URT cancer
ISOBUTYL ALCOHOL					Skin & eye irr
ISOPROPYL ALCOHOL	400		A4	A4; BEI	Eye & URT irr; CNS impair
N-BUTYL ALCOHOL					Eye & URT irr
N-PROPYL ACETATE	150				Eye & URT irr; CNS impair
PHENOL			A4	Skin; A4; BEI	URT irr; lung dam; CNS impair
PROPYLENE GLYCOL MONOMETHYL ETHER	100		A4	A4	Eye & URT irr
SILICA, AMORPHOUS					
TOLUENE			A4	A4; BEI	Visual impair; female repro; pregnancy loss
XYLENE	150		A4	A4; BEI	URT & eye irr; CNS imapir

(C) - Ceiling limit, A1 - Confirmed Human Carcinogen, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, dam - Damage, DSEN - Dermal sensitization, impair - Impairment, irr - Irritation, MeHb-emia - Methemoglobinemia, repro - reproductive, RSEN - Respiratory sensitization, URT - Upper respiratory tract

The information in this Section does not list components that might have relevant ACGIH TWA (mg/m3), ACGIH TLV Basis, OSHA TWA (mg/m3), OSHA Tables (Z1, Z2, Z3) regulatory values, if they are present at less than 10%. Please contact manufacturer for more information.

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	6.80939 lb/gal
% Solids By Weight	1.60340%
% VOC	60.72590%
Density VOC	4.13506 lb/gal
VOC Regulatory	6.67278 lb/gal
VOC Regulatory	799.60000 g/l

Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A
pH	N/A

Water Solubility	N/A
Flammability	N/A
Flash Point Symbol	N/A
Flash Point	N/A
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Excessive heat.

Hazardous Reactions/Polymerization

No data available.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

May produce fumes when heated to decomposition.

Fumes may contain carbon monoxide and carbon dioxide.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely route of exposure

Ingestion, Inhalation, Skin absorption

Skin Corrosion/Irritation

Causes mild skin irritation

0000064-17-5 ETHYL ALCOHOL

Contact can irritate the skin. Prolonged or repeated exposure can cause drying and cracking of the skin with peeling, redness and itching.

0000067-63-0 ISOPROPYL ALCOHOL

Contact can irritate and burn the skin. Prolonged or repeated contact can cause a skin rash, itching, dryness and redness.

0000067-64-1 ACETONE

Can cause skin irritation.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate and burn the skin.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the skin.

0000108-88-3 TOLUENE

Contact can irritate the skin.

0000108-95-2 PHENOL

Can be corrosive to skin.

0000109-60-4 N-PROPYL ACETATE

Contact can irritate the skin.

0000123-86-4 BUTYL ACETATE

May cause effects on the central nervous system.

0000141-78-6 ETHYL ACETATE

Exposure to high levels can cause dizziness and lightheadedness.

Serious Eye Damage/Irritation

Causes serious eye irritation

0000050-00-0 FORMALDEHYDE

Contact can severely irritate and burn the skin and eyes with possible eye damage.

0000067-63-0 ISOPROPYL ALCOHOL

Liquid irritates eyes and may cause injury.

0000067-64-1 ACETONE

Exposure can irritate the eyes.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate and burn the eyes.

0000078-83-1 ISOBUTYL ALCOHOL

Contact with eyes is extremely irritating and may cause burns.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the eyes.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Can irritate the eyes.

0000108-88-3 TOLUENE

Contact can irritate the eyes.

0000108-95-2 PHENOL

Can be corrosive to eyes.

0000109-60-4 N-PROPYL ACETATE

Contact can irritate the eyes.

0000123-86-4 BUTYL ACETATE

Can severely irritate and burn the skin.

Respiratory/Skin Sensitization

0000050-00-0 FORMALDEHYDE

Inhaling can irritate the lungs. May cause a skin allergy and an asthma-like allergy.

0000067-64-1 ACETONE

Can irritate the nose and throat causing coughing and wheezing.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate the nose, throat and lungs. May cause dryness or cracking.

0000078-83-1 ISOBUTYL ALCOHOL

Can irritate the skin causing a rash. Breathing can irritate the nose, mouth and throat causing coughing and wheezing.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the respiratory tract.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Can irritate the respiratory tract.

0000108-88-3 TOLUENE

Inhaling can irritate the nose and throat.

0000109-60-4 N-PROPYL ACETATE

The vapour is mildly irritating to the respiratory tract.

0000123-86-4 BUTYL ACETATE

Can severely irritate and burn the eyes.

Germ Cell Mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer

Reproductive Toxicity

0000064-17-5 ETHYL ALCOHOL

High concentration may damage the fetus.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The NOAEL for paternal toxicity is 300 ppm and for offspring toxicity is 1000 ppm. The NOAEL for maternal and fetotoxicity was considered to be 1500 ppm. Effects appear secondary to parental weight loss.

0000123-86-4 BUTYL ACETATE

Can irritate the respiratory tract.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

0000050-00-0 FORMALDEHYDE

Exposure can irritate the nose, mouth and throat.

0000064-17-5 ETHYL ALCOHOL

Exposure can cause headache, drowsiness, nausea and vomiting, and unconsciousness. It can also affect concentration and vision.

0000067-63-0 ISOPROPYL ALCOHOL

Vapors cause mild irritation of upper respiratory tract; high concentrations may be anesthetic.

0000067-64-1 ACETONE

May affect the kidneys and liver.

0000071-36-3 N-BUTYL ALCOHOL

Exposure can cause headache, dizziness, nausea and vomiting. Can damage the liver and kidneys.

0000078-83-1 ISOBUTYL ALCOHOL

Exposure can cause headache, dizziness, drowsiness, confusion and loss of coordination. It may affect the liver.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Exposure to very high concentrations could cause depression of the central nervous system.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Exposure at high levels could cause depression of the central nervous system. (Short-term exposure).

0000108-88-3 TOLUENE

May affect the nervous system causing headache, dizziness and passing out.

0000109-60-4 N-PROPYL ACETATE

May cause effects on the central nervous system and the liver. Exposure can cause headache, dizziness, lightheadedness and loss of consciousness.

0000141-78-6 ETHYL ACETATE

Can affect the liver and kidneys.

Specific Target Organ Toxicity - Repeated Exposure

0000064-17-5 ETHYL ALCOHOL

Repeated high exposure may affect the liver and the nervous system. Chronic ingestion of ethanol may cause liver cirrhosis.

0000067-63-0 ISOPROPYL ALCOHOL

Repeated high exposure can cause headache, dizziness, confusion, loss of coordination, unconsciousness and even death.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance defats the skin, which may cause dryness or cracking. Prolonged exposure to vapors may cause coughing, shortness of breath, dizziness and intoxication.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance defats the skin, which may cause dryness or cracking (Repeated exposure).

0000108-88-3 TOLUENE

Repeated exposure may cause liver, kidney and brain damage.

0000108-95-2 PHENOL

High or repeated exposure can damage the liver, kidneys, and nervous system.

Aspiration Hazard

0000078-83-1 ISOBUTYL ALCOHOL

If swallowed, aspiration into the lungs may result in chemical pneumonitis.

Acute Toxicity

May be harmful if swallowed

0000064-17-5 ETHYL ALCOHOL

Inhalation can irritate the nose, throat and lungs.

0000067-63-0 ISOPROPYL ALCOHOL

If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

LC50 (Rat, Inhalation) = 16,000 ppm/8H Reference : Registry of Toxic Effects of Chemical Substances If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

LC50 (Rat, Inhalation) = 16,000 ppm/8H Reference : Registry of Toxic Effects of Chemical Substances If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

0000078-83-1 ISOBUTYL ALCOHOL

If swallowed, aspiration into the lungs may result in chemical pneumonitis.

0000108-95-2 PHENOL

Can be corrosive to respiratory tract.

0000109-60-4 N-PROPYL ACETATE

Inhaling can irritate the nose and throat causing coughing and wheezing.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0000050-00-0 FORMALDEHYDE

The substance can be absorbed into the body by inhalation.

0000064-17-5 ETHYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapor or by ingestion.

0000067-63-0 ISOPROPYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapour.

0000067-64-1 ACETONE

Substance can be absorbed into the body by inhalation.

0000071-36-3 N-BUTYL ALCOHOL

Can be absorbed into the body by inhalation of its vapour and by ingestion.

0000078-83-1 ISOBUTYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance can be absorbed into the body by inhalation of its aerosol or vapour, through the skin and by ingestion.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance can be absorbed into the body by inhalation of its aerosol or vapour and by ingestion.

0000108-88-3 TOLUENE

The substance can be absorbed into the body by inhalation, through the skin and by ingestion.

0000108-95-2 PHENOL

Serious local effects by all routes of exposure.

Chronic Exposure

0000050-00-0 FORMALDEHYDE

Formaldehyde has caused cancer in test animals at high concentrations (5-15ppm).

Formaldehyde is classified as a Suspected Human Carcinogen (A2) by ACGIH, and as Probably Carcinogenic to Humans (Group 2A) by IARC. Formaldehyde has caused cancer in test animals.

0000100-41-4 ETHYLBENZENE

CARCINOGENIC EFFECTS: Ethyl Benzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans.

TERATOGENIC EFFECTS: Ethyl Benzene has been Classified as POSSIBLE for humans.

0000108-88-3 TOLUENE

TERATOGENIC EFFECTS:Toluene has been Classified as POSSIBLE for humans.

0001330-20-7 XYLENE

High exposure to Xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus.

Xylene in high concentrations has caused embryotoxic effects in laboratory animals.

Potential Health Effects - Miscellaneous

0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

0000067-63-0 ISOPROPYL ALCOHOL

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

0000071-36-3 N-BUTYL ALCOHOL

May cause abnormal blood forming function with anemia. Liquid splashes in the eye may result in chemical burns.

0000078-83-1 ISOBUTYL ALCOHOL

Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. May cause irritation of the mucous membranes. May cause abnormal liver function. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: bone marrow, liver. Prolonged skin contact may cause chemical burns. Liquid splashes in the eye may result in chemical burns.

0000100-41-4 ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Tests in laboratory animals have shown effects on any of the following organs/systems: kidneys, liver. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Recurrent overexposure may result in liver and kidney injury.

0000108-88-3 TOLUENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. Can be absorbed through the skin in harmful amounts. Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heart beats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

0000123-86-4 BUTYL ACETATE

May cause abnormal liver function. The following medical conditions may be aggravated by exposure: respiratory system. Tests for embryotoxic activity in animals has been inconclusive. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

0000141-78-6 ETHYL ACETATE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver.

0001330-20-7 XYLENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

0009004-70-0 NITROCELLULOSE

The following medical conditions may be aggravated by overexposure: liver disease, kidney disorders.

0064742-89-8 ALIPHATIC, LIGHT HYDROCARBON SOLVENT

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0000050-00-0 FORMALDEHYDE

LC50 (rat): 8000 ppm (4-hour exposure) (24)

LD50 (oral, male rat): 2500 mg/kg (25)

LD50 (oral, rat): 2920 mg/kg (26)

LD50 (dermal, guinea pig): greater than 15000 mg/kg (cited as greater than 0.94 mL/kg) (27)

LD50 (dermal, rat): 5070 mg/kg (28, unconfirmed)

0000062-53-3 ANILINE

LC50 (rat): approximately 250 ppm (4-hour exposure) (35)

LC50 (mouse): 232 ppm (4-hour exposure); cited as 175 ppm (7-hour exposure)(2)

LD50 (oral, rat): 250 mg/kg (30); 440 mg/kg (1,3)

LD50 (oral, mouse): 464 mg/kg (2,3)

LD50 (dermal, rabbit): 840 mg/kg (34)

LD50 (dermal, guinea pig): 1320 mg/kg (34)

0000064-17-5 ETHYL ALCOHOL

LC50 (mouse): Approximately 21000 ppm (4-hour exposure); cited as 39 g/m3 (4-hour exposure) (1, unconfirmed)

LD50 (oral, rat): 7060 mg/kg (41); 10600 mg/kg (41); 13660 mg/kg (37)

LD50 (oral, mouse): 3450 mg/kg (1, unconfirmed)

LD50 (oral, guinea pig): 5560 mg/kg (37)

0000067-63-0 ISOPROPYL ALCOHOL

LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)

LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)

LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)

LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m3 (4-hour exposure) (29)

LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m3 (4-hour exposure) (29)

LD50 (oral, female rat): 5800 mg/kg (24)

LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)

LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)

LD50 (oral, mouse): 3000 mg/kg (32, unconfirmed)

LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

0000071-36-3 N-BUTYL ALCOHOL

LC50 (rat): greater than 8000 ppm (4-hour exposure) (14)

LD50 (oral, rat): 2510 mg/kg (15)

LD50 (oral, male rat): 790 mg/kg (16)*

LD50 (oral, female rat): 2020 mg/kg (16)* *(Note: the rats used in this study appear to have been very young (60-100 grams).)

LD50 (oral, hamster): 1200 mg/kg (11, original)

0000078-83-1 ISOBUTYL ALCOHOL

LD50 (oral, rat): 2460 mg/kg.(7)
LD50 (oral, rabbit): 3000 mg/kg (reported as 41 mmol/kg) (8)
LD50 (dermal, rabbit): 3400 mg/kg (reported as 4.24 mL/kg).(7)

0000100-41-4 ETHYLBENZENE

LC50 (inhalation, rat): 4000 ppm; 4-hour exposure (3)

LD50 (oral, rat): 3.5 g/kg (1,3,5,10)
LD50 (oral, rat): 4.72 g/kg (3,5,7,8)
LD50 (dermal, rabbit): 17.8 g/kg (11)

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

LC50 (rat): 15000 ppm; 4-hr exposure (2)
LC50 (guinea pig): 15000 ppm; 10-hr exposure (2)
LD50 (oral, rat): 6.6 g/kg (5.2-7.5 g/kg) (10)
LD50 (oral, mouse): 10.7-10.8 g/kg (2,12)
LD50 (oral, dog): 4.6-5.5 g/kg (2); approximately 9.2 g/kg (2)
LD50 (oral, rabbit): 5.2-5.3 g/kg (2,12)
LD50 (dermal, rabbit): 13-14 g/kg (10)

0000108-88-3 TOLUENE

LC50 (rat): 8800 ppm (4-hour exposure) (2)
LC50 (rat): 6000 ppm (6-hour exposure) (3)
LD50 (oral, rat): 2600 to 7500 mg/kg (3,5,11,17)
LD50 (oral, neonatal rat): less than 870 mg/kg (3)
LD50 (dermal, rabbit): 12,225 mg/kg (reported as 14.1 ml/kg) (1)

0000108-95-2 PHENOL

LD50 (oral, rat): 340 mg/kg (20% solution) (16)
LD50 (oral, rat): 530 mg/kg (2 and 5% solutions) (16)
LD50 (oral, rat): 320 mg/kg (cited as 0.30 cc/kg) (17)
LD50 (dermal, pig): 500 mg/kg (liquefied phenol (45 deg C)) (2/3 animals died) (18)
LD50 (dermal, rabbit): 850 mg/kg (19)
LD50 (dermal, female rat): 670 mg/kg (cited as 625 mL/kg) (liquefied phenol (40 deg C)) (20)

0000109-60-4 N-PROPYL ACETATE

LD50 (oral, rat): 8700 mg/kg; cited as 9.8 mL/kg (4)
LD50 (oral, mouse): 8300 mg/kg (5)
LD50 (oral, rabbit): 6600 mg/kg; cited as 65 mmols/kg (6)
LD50 (dermal, rabbit): Greater than 17700 mg/kg; cited as 20 mL/kg (4)

0000123-86-4 BUTYL ACETATE

LC50 (rat): 1802 mg/m³; 4-hour exposure (aerosol)(9) Note: A lower LC50 (aerosol) value of 760 mg/m³ (160 ppm); 4-hour exposure has been reported.(11,27) Extensive research has failed to confirm this value.
LD50 (oral, rat): 10770 mg/kg (12, unconfirmed)
LD50 (oral, mouse): 7100 mg/kg (5)
LD50 (oral, rabbit): 7400 mg/kg (cited as 64 millimols/kg) (13)
LD50 (dermal, rabbit): Greater than 5000 mg/kg (3, unconfirmed)

0000141-78-6 ETHYL ACETATE

LC50 (rat): 19600 ppm (4-hour exposure); cited as 16000 ppm (6-hour exposure) (10)
LC50 (mouse): 10600 ppm (38100 mg/m³) (4-hour exposure); cited as 44000 mg/m³ (3-hour exposure) (8)
LD50 (oral, rat): 10200 mg/kg (cited as 11.3 mL/kg) (7); 5600 mg/kg (5,13)
LD50 (oral, mouse): 4100 mg/kg (11)
LD50 (oral, rabbit): 4900 mg/kg (9)
LD50 (oral, guinea pig): 5500 mg/kg (11)
LD50 (dermal, rabbit): Greater than 18000 mg/kg (cited as 20 mL/kg) (7)

0001330-20-7 XYLENE

LC50 (rat): 6350 ppm (4-hour exposure) (unspecified isomers and ethylbenzene) (1)LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2) ethylbenzene) (1)
LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene)(2)
LD50 (oral, rat): 5400 mg/kg (52% m-, 19% o-, 24% p-) (1)LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)
LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

Bio-accumulative Potential

0000064-17-5 ETHYL ALCOHOL

Substance has a low potential for bioaccumulation (log Kow3),

0000067-63-0 ISOPROPYL ALCOHOL

Substance is not expected to bioaccumulate.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Substance has a low potential for bioaccumulation, Log Kow < 1.

Substance has a low potential for bioaccumulation, Log Kow = 1.2.

Persistence and Degradability

0000064-17-5 ETHYL ALCOHOL

Readily biodegradable. Half-life in air = 38 h

0000067-63-0 ISOPROPYL ALCOHOL

Readily biodegradable

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Readily biodegradable.

0000071-36-3 N-BUTYL ALCOHOL

Readily biodegradable.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Readily biodegradable in water. Half-life in air = 3.1 hours.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Readily biodegradable.

0000109-60-4 N-PROPYL ACETATE

Readily biodegradable.

0000123-86-4 BUTYL ACETATE

Readily biodegradable

0001330-20-7 XYLENE

50% of applied radiolabelled o-xylene was mineralised in 23 days, and 50% p-xylene was mineralised in 13 days.

Mobility in Soil

0000067-64-1 ACETONE

The substance is not PBT / vPvB

The substance is not PBT / vPvB.

0000109-60-4 N-PROPYL ACETATE

The substance is not PBT / vPvB

The substance is not PBT / vPvB.

Toxicity

0000064-17-5 ETHYL ALCOHOL

S gairdneri: 13.0g/l (96hr LC50) Nauplii : 858 g/l (48hr EC50) Ceriodaphnia dubia : 9.6mg/l (10 day NOEC) Freshwater Fish 250mg/l (NOEC) Reference: REACH registration Dossier.

0000123-86-4 BUTYL ACETATE

Readily biodegradable

Other adverse effects

No data available.

Results of the PBT and vPvB assessment

0000067-63-0 ISOPROPYL ALCOHOL

Substance is readily biodegradable and therefore not considered to be persistent. It is not expected to bioaccumulate as it has a Log Kow

< 4.5 and aquatic acute toxicity greatly exceeds the screening criteria of EC50 < 0.1 mg/l.

0000071-36-3 N-BUTYL ALCOHOL

The substance is not PBT/vPvB

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance is not PBT / vPvB.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance is not PBT / vPvB.

0000123-86-4 BUTYL ACETATE

The substance is not PBT / vPvB

0000141-78-6 ETHYL ACETATE

The substance is not PBT / vPvB

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

IMDG Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II
Marine Pollutant : No data available

IATA Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

SECTION 15) REGULATORY INFORMATION

REGULATORY INFORMATION

TSCA Inventory: All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List: All components of this product are listed on the Domestic Substances List

CAS	Chemical Name	% By Weight	Regulation List
0000064-17-5	ETHYL ALCOHOL	36% - 61%	Canada_NPRI,DSL,SARA312
0000067-64-1	ACETONE	27% - 45%	DSL,SARA312,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000108-65-6	PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	3% - 6%	Canada_NPRI,DSL,SARA312

0000107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	2% - 5%	Canada_NPRI,DSL,SARA312,WI_N R438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000109-60-4	N-PROPYL ACETATE	0.1% - 2%	Canada_NPRI,DSL,SARA312
0000067-63-0	ISOPROPYL ALCOHOL	0.1% - 2.0%	SARA313, Canada_NPRI,DSL,SARA312
0000141-78-6	ETHYL ACETATE	0.1% - 1.5%	Canada_NPRI,DSL,SARA312,WI_N R438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	0.0% - 0.6%	Canada_NPRI,DSL,SARA312
0007440-47-3	CHROMIUM	Trace	SARA313, Canada_NPRI,DSL,HAPS,SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000123-86-4	BUTYL ACETATE	Trace	Canada_NPRI,DSL,SARA312,WI_N R438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000108-88-3	TOLUENE	Trace	SARA313, Canada_NPRI,DSL,HAPS,SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0009004-70-0	NITROCELLULOSE	Trace	DSL,SARA312
0000078-83-1	ISOBUTYL ALCOHOL	Trace	Canada_NPRI,DSL,SARA312,WI_N R438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000071-36-3	N-BUTYL ALCOHOL	Trace	SARA313, Canada_NPRI,DSL,SARA312,WI_N R438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0007631-86-9	SILICA, AMORPHOUS	Trace	DSL,SARA312
0001330-20-7	XYLENE	Trace	SARA313, Canada_NPRI,DSL,HAPS,SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000100-41-4	ETHYLBENZENE	Trace	SARA313, Canada_NPRI,DSL,HAPS,SARA312, CA_Carcinogen,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000062-53-3	ANILINE	Trace	SARA313, Canada_NPRI,DSL,HAPS,SARA312, CA_TAC_Carcinogen,CA_Carcinoge n,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000050-00-0	FORMALDEHYDE	Trace	SARA313, Canada_NPRI,DSL,HAPS,SARA312, CA_TAC_Carcinogen,CA_Carcinoge n,WI_NR438 - WI_NR438 - AIR

			CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000108-95-2	PHENOL	Trace	SARA313, Canada_NPRI,DSL,HAPS,SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS

The information in this Section does not list components that might have relevant Canada_NPRI, DSL, SARA312 regulatory values, if they are present at less than 10%. Please contact manufacturer for more information.

SECTION 16) OTHER INFORMATION

General

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 2
FLAMMABILITY	3
Physical Hazard	0
Personal Protection	X

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 1.0:

Revision Date: Mar 17, 2020

Version 1.0

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.