

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: #12550
Product Name: TAMARIN GLAZE
Revision Date: Jul 24, 2024 **Date Printed:** Jul 24, 2024
Version: 1.0 **Supersedes Date:** N.A.
Manufacturer's Name: Repolite Paints, Inc.
Address: 473 West 17th Street Holland, MI, US, 49423
Emergency Phone: 800-535-5053
Information Phone Number: 616-396-1275
Fax: 616-396-9654

SECTION 2) HAZARDS IDENTIFICATION

Classification

Flammable Liquids - Category 3
 Aspiration Hazard - Category 1
 Carcinogenicity - Category 1A
 Eye Irritation - Category 2
 Germ Cell Mutagenicity - Category 1B
 Skin Irritation - Category 3
 Skin Sensitizer - Category 1
 Specific Target Organ Toxicity - Repeated Exposure - Category 1

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H226 - Flammable liquid and vapor

Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways
 H350 - May cause cancer
 H319 - Causes serious eye irritation
 H340 - May cause genetic defects.
 H316 - Causes mild skin irritation

H317 - May cause an allergic skin reaction

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing, eye protection/face protection.

P264 - Wash thoroughly after handling.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take action to prevent static discharges.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P270 - Do not eat, drink or smoke when using this product.

Precautionary Statements - Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P370 + P378 - In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.

P321 - For specific treatment see section 4.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P314 - Get Medical advice/attention if you feel unwell.

Precautionary Statements - Storage

P405 - Store locked up.

P403 + P235 - Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Acute toxicity of 21.6% of the mixture is unknown

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0064742-48-9	NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	33% - 56%
0064742-88-7	MEDIUM MINERAL SPIRITS	3% - 6%
0000108-65-6	PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	1.8% - 4%
0013463-67-7	TITANIUM DIOXIDE	0.2% - 4%
0014808-60-7	SILICA, CRYSTALLINE	0.1% - 1.7%
0000123-86-4	BUTYL ACETATE	0.1% - 1.3%
0000096-29-7	2-BUTANONE OXIME	0.0% - 0.5%
0000097-85-8	ISOBUTYL ISOBUTYRATE	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed or unwell : Call a POISON CENTER/doctor

Skin Contact

Take off immediately contaminated clothing. Rinse skin with water/shower and mild soap for 5 minutes or until product is removed. Store contaminated clothing under water and wash before re-use or discard.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. If you feel unwell or are concerned : Get medical advice/attention.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Unsuitable Extinguishing Media

No data available.

Specific Hazards Arising from the Chemical

Vapors are heavier than air and may travel along the ground to ignition sources at locations distant from material handling point.

Vapor accumulations and spray mist may flash or explode if ignited.

Closed containers may rupture due to pressure buildup when exposed to extreme heat.

Dried solids can burn.

Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Protective Equipment

Positive pressure, full-face piece self-contained breathing apparatus SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Absorb spill with inert absorbent.

Dike area to contain spill.

SECTION 7) HANDLING AND STORAGE

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Ground and bond containers and receiving equipment. Avoid static electricity by grounding.

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

A suitable, NIOSH-approved respirator and goggles should be worn when standing or grinding objects coated with this paint.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	ACGIH TWA (ppm)
BUTYL ACETATE	150	710			1			50
MEDIUM MINERAL SPIRITS								(L)[N159](L)[N800]
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	500	2000			1			(L)[N159](L)[N800]
SILICA, CRYSTALLINE	a	[10 mg/m3 percent SiO2+2 / 250 percent SiO2+5 mppcf]; [30 mg/m3 percent SiO2+2];			[1,3]; [3];			
TITANIUM DIOXIDE		15			1			

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
BUTYL ACETATE		150				Eye & URT irr
MEDIUM MINERAL SPIRITS	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]]; [A4 [N159]A4 [N800]]; [A2[N159]A2 [N800]]; [A4 [N159]A4 [N800]]; [A2[N159]A2 [N800]]; [A4 [N159]A4 [N800]]; [A2[N159]A2 [N800]]; [A4 [N159]A4 [N800]];					URT irr [N159]URT irr [N800]
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]]; [A4 [N159]A4 [N800]]; [A2[N159]A2 [N800]]; [A4 [N159]A4 [N800]]; [A2[N159]A2 [N800]]; [A4 [N159]A4 [N800]];					URT irr [N159]URT irr [N800]
SILICA, CRYSTALLINE	0.025 (R)			A2	A2	Pulmonary fibrosis; lung cancer
TITANIUM DIOXIDE	0.2 (R)(Nano), 2.5 (R)			A3		LRT irr; pneumoconiosis

(R) - Respirable fraction, A2 - Suspected Human Carcinogen, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, irr - Irritation, LRT - Lower respiratory tract, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	8.74142 lb/gal
% Solids By Weight	52.66750%
% VOC	45.86150%
Density VOC	4.00895 lb/gal
VOC Regulatory	4.63182 lb/gal
VOC Regulatory	555.03100 g/l

Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	N/A
Flash Point Symbol	N/A
Flash Point	N/A
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

SECTION 10) STABILITY AND REACTIVITY

Chemical Stability

Stable.

Possibility of Hazardous Reactions/Polymerization

No data available.

Conditions To Avoid

Excessive heat.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

May produce fumes when heated to decomposition.

Fumes may contain carbon monoxide and carbon dioxide.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely route of exposure

Ingestion, Inhalation, Skin absorption

Skin Corrosion/Irritation

Causes mild skin irritation

0000123-86-4 BUTYL ACETATE

May cause effects on the central nervous system.

Serious Eye Damage/Irritation

Causes serious eye irritation

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Can irritate the eyes.

0000123-86-4 BUTYL ACETATE

Can severely irritate and burn the skin.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Vapor is a mild eye irritant.

Respiratory/Skin Sensitization

May cause an allergic skin reaction

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Can irritate the respiratory tract.

0000123-86-4 BUTYL ACETATE

Can severely irritate and burn the eyes.

Germ Cell Mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer

Reproductive Toxicity

0000123-86-4 BUTYL ACETATE

Can irritate the respiratory tract.

Specific Target Organ Toxicity - Single Exposure

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Exposure at high levels could cause depression of the central nervous system. (Short-term exposure).

Specific Target Organ Toxicity - Repeated Exposure

Causes damage to organs through prolonged or repeated exposure.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance defats the skin, which may cause dryness or cracking (Repeated exposure).

Chronic Exposure

0014808-60-7 SILICA, CRYSTALLINE

Prolonged inhalation of respirable crystalline silica dust can result in lung disease (i.e. silicosis and/or lung cancer). Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.

Aspiration Hazard

May be fatal if swallowed and enters airways

Potential Health Effects - Miscellaneous

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Recurrent overexposure may result in liver and kidney injury.

0000123-86-4 BUTYL ACETATE

May cause abnormal liver function. The following medical conditions may be aggravated by exposure: respiratory system. Tests for embryotoxic activity in animals has been inconclusive. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

0013463-67-7 TITANIUM DIOXIDE

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was

overwhelmed and that the results at the massive 250 mg/m3 level are not relevant to the workplace. 'Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.'

0014808-60-7 SILICA, CRYSTALLINE

Is an IARC, NTP or OSHA carcinogen. Repeated overexposure to crystalline silica may lead to x-ray changes and chronic lung disease. Inhalation of high dust concentrations may cause: breathing difficulties, lung injury. WARNING: This chemical is known to the State of California to cause cancer.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-88-7 MEDIUM MINERAL SPIRITS

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. This substance may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, lungs, reproductive system, skin. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

Acute Toxicity

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Inhalation of high concentrations can cause CNS depression; Ingestion can cause aspiration into the lungs.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance can be absorbed into the body by inhalation of its aerosol or vapour and by ingestion.

0000123-86-4 BUTYL ACETATE

LC50 (rat): 1802 mg/m3; 4-hour exposure (aerosol)(9) Note: A lower LC50 (aerosol) value of 760 mg/m3 (160 ppm); 4-hour exposure has been reported.(11,27) Extensive research has failed to confirm this value.

LD50 (oral, rat): 10770 mg/kg (12, unconfirmed)

LD50 (oral, mouse): 7100 mg/kg (5)

LD50 (oral, rabbit): 7400 mg/kg (cited as 64 millimols/kg) (13)

LD50 (dermal, rabbit): Greater than 5000 mg/kg (3, unconfirmed)

0013463-67-7 TITANIUM DIOXIDE

LC50 (inhalation, Rat): >5.09 mg/L ; 4-hr exposure

Test atmosphere: dust/mist

No mortality observed at this dose.

LD50 Rat: > 5000 mg/kg

LD50 Hamster: > 10000 mg/kg

SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

0000123-86-4 BUTYL ACETATE

Readily biodegradable

Persistence and Degradability

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Readily biodegradable.

0000123-86-4 BUTYL ACETATE

Readily biodegradable

Bioaccumulative Potential

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Substance has a low potential for bioaccumulation, Log Kow < 1.

Substance has a low potential for bioaccumulation, Log Kow = 1.2.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance is not PBT / vPvB.

0000123-86-4 BUTYL ACETATE

The substance is not PBT / vPvB.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

IATA Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

U.S. DOT Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

IMDG Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II
Marine Pollutant : No data available

SECTION 15) REGULATORY INFORMATION

REGULATORY INFORMATION

TSCA Inventory: All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List: All components of this product are listed on the Domestic Substances List

CAS	Chemical Name	% By Weight	Regulation List
0064742-48-9	NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	33% - 56%	DSL - Domestic Substance List, SARA312
0008001-26-1	LINSEED OIL	17% - 28%	DSL - Domestic Substance List, SARA312
PROPRIETARY	PROPRIETARY MIXTURE OF SUBSTANCES	16% - 27%	SARA312
0064742-88-7	MEDIUM MINERAL SPIRITS	3% - 6%	DSL - Domestic Substance List, SARA312
0000108-65-6	PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	1.8% - 4%	DSL - Domestic Substance List, SARA312
0013463-67-7	TITANIUM DIOXIDE	0.2% - 4%	DSL - Domestic Substance List, SARA312, CA_Carcinogen, CA_Prop65 - California Proposition 65, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0014808-60-7	SILICA, CRYSTALLINE	0.1% - 1.7%	DSL - Domestic Substance List, SARA312, CA_Carcinogen, CA_Prop65 - California Proposition 65, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0000123-86-4	BUTYL ACETATE	0.1% - 1.3%	DSL - Domestic Substance List, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000096-29-7	2-BUTANONE OXIME	0.0% - 0.5%	DSL - Domestic Substance List, SARA312
0000097-85-8	ISOBUTYL ISOBUTYRATE	Trace	DSL - Domestic Substance List, SARA312

The information in this Section does not list non-hazardous components that might have relevant SARA312, DSL - Domestic Substance List, SARA312 regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.



WARNING: This product can expose you to chemicals including TITANIUM DIOXIDE, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16) OTHER INFORMATION

General

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	1 3
FLAMMABILITY	3
Physical Hazard	0
Personal Protection	X

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.