

# TR SERIES UP TO 24 ACRES

The Keeton Industries TR series of lake bed aeration systems are the ideal choice for ponds and lakes up to 24 surface acres in size. The TR series superior design is unmatched in energy efficiency, effectiveness and sound reduction. These systems feature 1/2HP Gast Rocking Piston compressors, high volume cooling blowers, programmable digital timers and fully adjustable aluminum manifolds housed in attractive, 100% recycled plastic cabinets. The TR series can operate up to 12 self-cleaning, nonclogging Duraplate™ membrane diffusers. Duraplate diffusers emit millions of tiny bubbles that increase dissolved oxygen levels while eliminating stratification, improving water quality and clarity. Like all of our aeration systems, the TR series are backed by a full 2 year warranty.



Model	Features	Acres
TR-6DP	6 Diffuser and 3 Compressors	6 - 12 Acres
TR-9DP	9 Diffusers and 3 Compressors	9 - 18 Acres
TR-12DP	12 Diffusers and 3 Compressors	12 - 24 Acres



#### The Cabinet

- 100% recycled plastic cabinet
- 20"W x 36"L x 27" T
- 275 cfm cooling blower
- Sound reduction package
- 1" ASTM certified Acoustical Foam
- · Programmable digital timer
- (3) 4-valve adjustable aluminum manifold
- 8' grounded plug



#### **The Compressors**

- 1/2 HP Rocking Piston
- 15.9 cfm air flow
- 40psi max pressure
- 115V 15.9A max, 7.8A average
- Thermal overload protection
- Pressure relief valve
- Intake filter
- Pressure Gauge



#### The Tubing

- Self-weighted
- 1/2" I.D. with 1/4" sidewalls
- Fishhook resistant
- · Will not kink or break
- Available in 100' and 500' lengths
- 15 year warranty




### The Diffuser

- Self-cleaning
- Non-clogging
- Self-weighted
- Fishhook resistant
- High Oxygen transfer
- Lifetime warranty



## **TR SERIES UP TO 24 ACRES**






37.50"

**FRONT VIEW** 

NOT TO SCALE



MODEL FFP-546-4 ALL ALUMINUM MANIFOLD WITH PRESSURE RELIEF VALVE, LIQUID-FILLED STAINLESS STEEL PRESSURE GAUGE (0-30 PSI RATED) AND 4-VALVE MANIFOLD WITH BRASS BARB OUTLETS.

TR QUIET LINE AERATION SYSTEM CABINET MADE OF 100% RECYCLED PLASTIC WITH THE DIMENSIONS OF 21.50" (L) X 37.50" (W) X 18.50" (H).
HIGH-FLOW SQUIRREL CAGE BLOWER, RATED AT 275 CFM FOR CABINET COOLING, FAN COMES WITH OILABLE BEARINGS AND SCREENED INLET


AND OUTLET OPENING(S). AIR FILTER ASSEMBLY (AC432) AND FILTER ELEMENT (AC393)

- CONTROLS 24 HOUR/ 7 DAY DIGITAL TIMESWITCH. 120V, SPST AND SPDT SWITCHING, 1 CHANNEL, 6.3MM X 0.8MM TAB TERMINAL(S) CONNECTION(S) (COMPLIES WITH DIN 46244). 120V OUTLET

INTERIOR OF CABINET, FITTED AND GLUED WITH ACOUSTICAL CONVOLUTED FOAM INSULATION. 1" ASTM RATED C 423-90A, TO THE NEAREST 0.05 SABINS/FT\* WITH A NOISE REDUCTION COEFFICIENT OF 0.40. OSHA APPROVED SOUNDPROOFING AND UL-94 RATING.

\$\frac{1}{4}\$ HP GAST (MODEL 75R640) ROCKING PISTON COMPRESSOR WITH AIR OUTPUT OF 13.35 CFM AT 0 PSI, 40 PSI MAXIMUM CONTINUOUS DUTY OPERATION. COMPRESSOR DRAWS A MAXIMUM OF 15.9 AMPS @ 115V. COMPRESSOR DRAWS A MAXIMUM OF 15.9 AMPS @ 115V. COMPRESSOR SWIRED FOR 115V AND IS FITTED WITH A DUPLEX WIRING BOX/ PLUG, SERVICING THE COMPRESSOR AND COOLING FAN.

## TOP VIEW (SEE SHEET #2)



TR QUIET LINE AERATION SYSTEM CABINET MADE OF 100% RECYCLED PLASTIC WITH THE DIMENSIONS OF 21.50° (L) X 37.50° (W) X 18.50° (H), CABINET LID COVER SECURED WITH PIANO HINGE (BACK) AND LOCKABLE HASP (FRONT).

13/-8) AIR OUTLET LINES FROM COMPRESSOR THROUGH CABINET WITH! 220 PSI RATED FLEXIBLE BRAIDED VINYL TUBING, EACH FLEXIBLE TUBING OUTLET SHALL BE 4'-0" LONG AND FITTED WITH ½" ID BARB CONNECTS. ALL AERATION SYSTEMS SHALL BE FURNISHED WITH STAINLESS STEEL  $^{1/2}$  " WORMDRIVE CLAMPS TO FIT  $^6_1$  " -  $^5_2$  " HOSE, MODEL 67-06-1 TO CONNECT ON SHORE AND TO DURAPLATE(S) (DDP-9) IN LAKE.

CABINET IS CONSTRUCTED WITH (4) LEGS THAT CAN BE BOLTED TO A CONCRETE SLAB (39" (L) X 39" (W) X 4" (H)).



llington, Colorado 80549 O: (970) 568-7754 TF: (800) 493-4831

QUIET LINE AERATION SYSTEM TR SERIES - MULTI VIEW

DATE: 7-30-13 SHEET:

1