

QR SERIES UP TO 32 ACRES

The Keeton Industries OR series of lake bed aeration systems are the ideal choice for ponds and lakes up to 32 surface acres in size. The QR series superior design is unmatched in energy efficiency, effectiveness and sound reduction. These systems feature 1/2HP Gast Rocking Piston compressors, high volume cooling blowers, programmable digital timers and fully adjustable aluminum manifolds housed in attractive, 100% recycled plastic cabinets. The QR series can operate up to 16 self-cleaning, non-clogging Duraplate[™] membrane diffusers. Duraplate diffusers emit millions of tiny bubbles that increase dissolved oxygen levels while eliminating stratification, improving water quality and clarity. Like all of our aeration systems, the QR series are backed by a full 2 year warranty.



Model	Features	Acres
QR-12DP	12 Diffusers and 4 Compressors	12 - 24 Acres
QR-16DP	16 Diffusers and 4 Compressors	16 - 32 Acres



The Cabinet

- 100% recycled plastic cabinet
- 20"W x 36"L x 27" T
- 275 cfm cooling blower
- Sound reduction package
- 1" ASTM certified Acoustical Foam
- Programmable digital timer
- (4) 4-valve adjustable aluminum manifold
- 8' grounded plug



The Compressors

- 1/2 HP Rocking Piston
- 21.2 cfm air flow
- 40psi max pressure
- 115V 21.2A max, 10.4A average
- Thermal overload protection
- Pressure relief valve
- Intake filter
- Pressure Gauge



The TubingSelf-weighted

- 1/2" I.D. with 1/4" sidewalls
- Fishhook resistant
- Will not kink or break
- Available in 100' and 500' lengths
- 15 year warranty



The Diffuser


- Self-cleaning
- Non-clogging
- Self-weighted
- Fishhook resistant
- High Oxygen transfer
- Lifetime warranty


OTHER PONDS AND LAKES ARE GREEN WITH ENVY® keetonaquatics.com | 800.493.4831 | 970.568.7754



QR SERIES UP TO 32 ACRES







39.50°

NOT TO SCALE

TOP VIEW (SEE SHEET #2) NOT-TQ SCALF 24.25" 21.50"

, og et all and a second secon

MODEL FFP-546-4 ALL ALUMINUM MANIFOLD WITH PRESSURE RELIEF VALVE, LIQUID-FILLED STAINLESS STEEL PRESSURE GAUGE (0-30 PSI RATED) AND 4-VALVE MANIFOLD WITH BRASS BARB OUTLETS.

, OR QUIET LINE AERATION SYSTEM CABINET MADE OF 100% RECYCLED PLASTIC WITH THE DIMENSIONS OF 21.50° (L) X 37.50° (W) X 18.50° (H). HIGH-LOW SOURREL CAGE BLOWER, RATED AT 275 CFM FOR CABINET COOLING. FAN COMES WITH OILABLE BEARINGS AND SCREENED INLET AND OUTLET OPENING(S).

AIR FILTER ASSEMBLY (AC432) AND FILTER ELEMENT (AC393)

/ CONTROLS 24 HOUR/ 7 DAY DIGITAL TIMESWITCH. 1200, SPST AND SPDT SWITCHING, 1 CHANNEL, 6.3MM X 0.8MM TAB TERMINAL(S) CONNECTION(S) (COMPLIES WITH DIN 46244). _120V OUTLET

, INTERIOR OF CABINET, FITTED AND GLUED WITH ACOUSTICAL CONVOLUTED FOAM INSULATION. 1⁴ ASTM RATED C 423-90A, TO THE NEAREST 10 SABINSFIT[®] WITH A NOISE REDUCTION COEFFICIENT OF 0.40. OSHA APPROVED SOUNDPROOFING AND UL-94 RATING.

I PIP GAST (MODEL 73R540) ROCKING PISTON COMPRESSOR WITH AIR OUTPUT OF 178 CFM AT 0 PSI, 40 PSI MAXIMUM CONTINUOUS DUTY OPERATION. COMPRESSOR DRAWS A MAXIMUM OF 212 AMPS @ 115V. COMPRESSOR IS WIRED FOR 115V AND IS FITTED WITH A DUPLEX WIRING BOX PLUG, SERVICING THE COMPRESSOR AND COOLING FAN.

DR QUIET LINE AERATION SYSTEM CABINET MADE OF 100% RECYCLED PLASTIC WITH THE DIMENSIONS OF 21:50° (L) X 37:50° (W) X 18:50° (H), CABINET LID COVER SECURED WITH PIANO HINGE (BACK) AND LOCKABLE HASP (FRONT).

(4-8) AIR OUTLET LINES FROM COMPRESSOR THROUGH CABINET (16) # 220 PSI RATED FLEXIBLE BRADED VINYL TUBING: EACH FLEXIBLE TUBING OUTLET SHALL BE 4''O' LONS MO FITTED WITH #' ID BARE CONNECTS. ALL AERATION SYSTEMS SHALL BE FURNISHED WITH STANLESS STELE! # VORDRIVE CLAMPS TO FIT # #''. # HOSE, MODEL 67-06-1 TO CONNECT ON SHORE AND TO DURAPLATE(S) (DDP-9) IN LAKE.

CABINET IS CONSTRUCTED WITH (4) LEGS THAT CAN BE BOLTED TO A CONCRETE SLAB (39" (L) X 39" (W) X 4" (H)).

SYSTEM COMES WITH 8 120V (14-3) HEAVY DUTY WIRING CORD WITH PLUG END.

1520 Aquatic Drive Wellington, Colorado 80 O: (970) 568-7754 TF: (800) 493-4831 www.keetonaguatics.cc



DATE: 7-30-13



