


High Performance Façade Subsystems

“Build What is Designed, Easily”



Learning Objectives

- Discuss macro-forces at work emphasizing ventilated rainscreen facades.
- Explain system choices. Why 'systems' thinking is so important. From Simple, to High Performance to Innovative.
- Explain Bespoke System Design, and the system for the exact location on the exact building.
- How early Design Precision and value engineering cuts costs and avoids failure.
- How sloppy specification can lead to failure and what to do about it.
- What to expect in review, shop, and installation drawings.
- Review case studies.

Achieving High Performance Facades Should Not Be Left to Chance

Alexander Mirilenko
U-kon Façade Systems Ltd.
(250) 419-2417
a.mirilenko@u-konsystems.ca



General Manager
U-kon Façade Systems Ltd.

Blair Davies, P.Eng.
Façade Systems Inc.
(647)923-8967
blair@facadesystemsinc.com




Agent for Facades and Building Systems that are innovative, aesthetic, sustainable, constructible, affordable and proven.




- Labour availability and skill
- >6” insulation application



- GHG impact
- >6” insulation application



- Long term resilience – gaskets.
- Thermal performance now
- % fenestration going down.
- Curtain wall exceptions (office, high performance spandrels)



Façade – everything outside of Sheathing

Insulation & AVB

Thermally Broken Substructure 'System'

Cladding; Skin, Light to Heavy, All types of finishes; Resilient; All budgets; Sustainable; Replaceable.



- **Built ≠ Design**
- Trade-offs; performance vs cost
- Specification pitfalls
- Constructability
- Independence of cladding.
- Best **value engineering** opportunities.
- Initial and Lifecycle costs.
- **Sustainability**

System Choices*

Simple




FSI
FACADE SYSTEMS INC.

High Performance



Innovative (slab-to-slab)



*And Everything Between

Design Precision

**Best accomplishments are at the beginning;
Greatest Failures Avoided are too.**

- Design review.
- Cladding layout review.
- Initial system recommendation.
- Initial structural engineering and resulting thermal performance.
- Comprehensive value engineering.
- Cladding fabrication recommendations.
- Document creation; details, specifications.
- Budgeting.





You Should Ask for This.




A façade is modelled for structural requirements and thereby thermal results.

Initial **budgeting** and value engineering opportunities identified.

Problems revealed early.




Location of wall brackets; based on structural analysis




Slab to Slab
Higher loads / Wall Bracket
Faster Install

Distributed System
Lighter gauge wall brackets
Slower Install



*and accounted for building deflection.

That is a spec!



Sole accountability

Years in business

Site Launch meeting

Effective R value

Thermal movements

Excellent Details Lead to Excellent Review Drawings Post Award

THE WILDS
400 NEWCASTLE ST, WA
WA

CLADDING LAYOUT
SCALE: 1:50
PROJECT NO: 2019-0001
DATE: 10/10/2019
DRAWN BY: [Name]
CHECKED BY: [Name]
REVISIONS: [Table]

CLIP LAYOUT
SCALE: 1:50
PROJECT NO: 2019-0001
DATE: 10/10/2019
DRAWN BY: [Name]
CHECKED BY: [Name]
REVISIONS: [Table]

VERTICAL & ENLARGED PANEL SECTIONS
SCALE: 1:10
PROJECT NO: 2019-0001
DATE: 10/10/2019
DRAWN BY: [Name]
CHECKED BY: [Name]
REVISIONS: [Table]

TYPES OF CLADDING INSTALLATION
SCALE: 1:50
PROJECT NO: 2019-0001
DATE: 10/10/2019
DRAWN BY: [Name]
CHECKED BY: [Name]
REVISIONS: [Table]

LEGEND

- 1 WALL CLIP AND INSULATION
- 2 WALL CLIP AND INSULATION
- 3 WALL CLIP AND INSULATION
- 4 WALL CLIP AND INSULATION
- 5 WALL CLIP AND INSULATION
- 6 WALL CLIP AND INSULATION
- 7 WALL CLIP AND INSULATION
- 8 WALL CLIP AND INSULATION
- 9 WALL CLIP AND INSULATION
- 10 WALL CLIP AND INSULATION
- 11 WALL CLIP AND INSULATION
- 12 WALL CLIP AND INSULATION
- 13 WALL CLIP AND INSULATION
- 14 WALL CLIP AND INSULATION
- 15 WALL CLIP AND INSULATION
- 16 WALL CLIP AND INSULATION

LEGEND

- 1 WALL CLIP AND INSULATION
- 2 WALL CLIP AND INSULATION
- 3 WALL CLIP AND INSULATION
- 4 WALL CLIP AND INSULATION
- 5 WALL CLIP AND INSULATION
- 6 WALL CLIP AND INSULATION
- 7 WALL CLIP AND INSULATION
- 8 WALL CLIP AND INSULATION
- 9 WALL CLIP AND INSULATION
- 10 WALL CLIP AND INSULATION
- 11 WALL CLIP AND INSULATION
- 12 WALL CLIP AND INSULATION
- 13 WALL CLIP AND INSULATION
- 14 WALL CLIP AND INSULATION
- 15 WALL CLIP AND INSULATION
- 16 WALL CLIP AND INSULATION

LEGEND

- 1 WALL CLIP AND INSULATION
- 2 WALL CLIP AND INSULATION
- 3 WALL CLIP AND INSULATION
- 4 WALL CLIP AND INSULATION
- 5 WALL CLIP AND INSULATION
- 6 WALL CLIP AND INSULATION
- 7 WALL CLIP AND INSULATION
- 8 WALL CLIP AND INSULATION
- 9 WALL CLIP AND INSULATION
- 10 WALL CLIP AND INSULATION
- 11 WALL CLIP AND INSULATION
- 12 WALL CLIP AND INSULATION
- 13 WALL CLIP AND INSULATION
- 14 WALL CLIP AND INSULATION
- 15 WALL CLIP AND INSULATION
- 16 WALL CLIP AND INSULATION

Bespoke Systems

#1 Wall Brackets

#2 Profiles

#3 Cladding Attachments



Note: Often different systems are used on the same building, depending on cladding and loads

If you just want
Simple*




Wall Brackets that offer Options – High Performance

Different brackets, extenders, materials provides unique flexibility

Adjustable in three directions: higher quality, faster install


WALL BRACKETS “U” SHAPE




WALL BRACKETS “U” SHAPE WITH EXTENSION




WALL BRACKETS “L” SHAPE



WALL BRACKETS “L” SHAPE WITH EXTENSION



Innovations Reducing Wall Brackets





Wall Brackets Adjustable in Three Directions

Uneven wall not an issue, e.g. recladding.

Install: attach then adjust, reducing error and rework.



Reduce compromises on site,
“Build What Is Designed, Easily”



WITHOUT EXTENSION



WITH EXTENSION



Victoria BC Stone Install


- 3" out of true ground to roof
- Adjusted with U-Kon Subsystem.



Thermal Performance Explained

Aluminum Bracket

Stainless Steel Bracket




Vertical Spacing in	Exterior Insulation Thickness in	Exterior Insulation Nominal R-Value	Assembly Effective R-Value	Assembly Effective R-Value	Assembly Effective R-Value (Stainless steel Bracket HIGH)*
24	4	R-16.8	R-14.3	R-17.7 (20%)	
24	5	R-21.0	R-16.0	R-21.1 (25%)	
24	6	R-25.2	R-17.7	R-24.8 (29%)	
36	4	R-16.8	R-15.8	R-18.3 (14%)	
36	5	R-21.0	R-18.0	R-21.9 (18%)	
36	6	R-25.2	R-20.2	R-25.8 (22%)	
48	4	R-16.8	R-16.7	R-18.7 (11%)	
48	5	R-21.0	R-19.3	R-22.4 (14%)	
48	6	R-25.2	R-21.8	R-26.3 (18%)	
120	4	R-16.8			18.2*
120	5	R-21.0			21.9*
120	6	R-25.2			25.8*



THERMAL ANALYSIS PERFORMED BY MORRISON & HERSHFIELD

* - Bracket is mounted to the intermediate floor slab, thermal bridging of the concrete slab must be included in the analysis. As a result, a linear transmittance value, Ψ , is provided to account for the thermal bridging effect of the intermediate floor.



cool, temperate climate

phA

CERTIFIED COMPONENT

Passive House Institute

arctic climate

CERTIFIED COMPONENT

Passive House Institute

cold climate

CERTIFIED COMPONENT

Passive House Institute

cool, temperate climate

CERTIFIED COMPONENT

Passive House Institute

warm, temperate climate

CERTIFIED COMPONENT

Passive House Institute

warm climate

CERTIFIED COMPONENT

Passive House Institute

hot climate

CERTIFIED COMPONENT

Passive House Institute

very hot climate



CERTIFIED COMPONENT

Passive House Institute



Innovative System: Slab-To-Slab

Reduce wall brackets, easy alignment, unload studs.



Back wall can be anything: studs, concrete, block or existing wall




IDEAL SOLUTION FOR RENOVATION

- WHEN WE DO NOT HAVE GOOD/STRONG BACKUP WALL
- WHEN WE NEED MINIMIZE THERMAL BRIDGING
- WHEN WE NEED TO PROVIDE FAST INSTALLATION






Slab to Slab attachment methods

WEAK POINT – EXISTING SLAB CONNECTION
SLAB THICKNESS MORE THEN 200 mm






Slab to Slab attachment methods

WEAK POINT – EXISTING SLAB CONNECTION
SLAB THICKNESS LESS THEN 200 mm






HOW CAN WE INSTALL SLAB TO SLAB SYSTEM
WHEN WE HAVE WINDOWS IN A MIDDLE?






Value Engineering: Replace HSS




Proposed design
– (plan view)

Concealed Fasteners



BIPV



Building Block #3 Cladding Attachments



Simple Front Fastened




Specialized; Kerf for Stone



Systems independent of choices in:

- Cladding
- Insulation
- Backup wall
- Time of year
- Location
-



U-kon[®]
SYSTEMS



FSi
FACADE SYSTEMS INC.










Undercut Anchors System



Innovative Configuration: Building Integrated PV (BIPV)









Terra Cotta Systems for all Manufacturers





FS
FACADE SYSTEM



Visible Fasteners








SMART KLINKER

What Else Do You Need??

Achieving High Performance Facades Should Not Be Left To Chance


We assist you to design great facades, suggest products and systems, and develop great relationships.




What is next?

- Tells us your woes, challenges, and curiosities about high performance facades. You can help us help you or guide us on our next webinar.
- Under no obligation, let's review a project at any stage and discuss some ideas.
- or just give us a call. We love learning.

We hope we have set expectations about how you should proceed on thermal and structural aspects of high-performance facades... and taught you a bit about us, wink wink.




Simple System: Visible Fasteners





The system is a simple, economical and frequently used system for visible fixing of flat facade material like aluminum composite panels, sheets, HPL, fiber cement corrugated and standing seam metal panels.

fischer 

KEIL 



Location of under
cut anchor, typical
2' spacing



The system is designed for invisible fixing of ceramic, porcelain, HPL and fiber cement panels using special undercut technology.

The system is designed for concealed way of fastening the natural stone.



The cladding is fixed to the system of vertical and horizontal profiles.

Stone panels are installed on horizontal girts, for which in the lower and upper ends of the panel the cut is made, where installing special horizontal profiles is set.







Innovative Configuration: Glass/ Building Integrated PV (BIPV) Facades

This system is designed for invisible fixing of glass, ceramic, and photovoltaic solar panels. The system can withstand a large format of panels that have a thickness between 3.5 mm to 8 mm. The cladding panel is glued into the frame of aluminum profiles. Special stainless steel safety clips are installed around the perimeter of the cladding panel.



This system is designed for invisible fixing of thin brick. The brick veneer can be installed with or without grouting. Brick veneer without grouting: Cladding panels are installed on horizontal rails, the shelves of which engage with grooves in the horizontal ends of the panels. Horizontal and vertical seams overlap shelves of plates.





Systems are designed for invisible fixing of terracotta panels with different thicknesses from 8,5 mm to 40 mm for vertical and horizontal layout.

We provide a system for following brand of terracotta panels:

- **AgGeTon**
- Agrob Buchtal
- Ceramics Terracotta
- CN-ceramic
- Faveton
- Frontek
- Moeding
- NBK
- Tempio
- Terreal