

2 mW 632.8nm (RED) HELIUM NEON LASER MODEL: 05-LHP-121

OUTPUT SPECIFICATIONS	
CW Power Output (mW)	> 2.0
Wavelength (nm)	632.8
Transverse Mode	> 90% TEM ₀₀
Polarization	Linear >500:1
Beam Diameter at 1/e ² Points	0.59 ± 5%
Beam Divergence (mrad)	1.35 ± 5%
Longitudinal Mode Spacing (MHz)	687
Mode Sweeping	< 5%
Long Term Power Drift (8 hrs)	< 5%
Amplitude Noise, 30 Hz to 30 MHz (peak-to-peak)	< 2.8%
Warmup to > 95% of Maximum Power (minutes)	< 15
Beam Concentricity with Respect to Housing (mm)	± 0.1
Beam Parallelism with Respect to Housing (mrad)	< 0.5
ELECTRICAL SPECIFICATIONS	
Start Voltage (kVdc)	< 10
Recommended Operating Current (mA)	6.5 ± 0.2
Operating Voltage (VDC)	1790 ± 100

Recommended Power Supply Laboratory OEM (AC) OEM (DC) 05-LPL-911-065 05-LPM-911-065 05-LPM-830-065

ENVIRONMENTAL SPECIFICATIONS	OPERATING	NON-OPERATING
Temperature (°C)	-20 to +60	-40 to +80
Altitude (meters)	0 to 3000	0 to ∞
Relative Humidity (%, non-condensing)	0 to 99%	0 to 99%
Mechanical Shock (g)	< 1 for < 11 msec	< 25 for < 11 msec < 100 for < 1 msec

Please contact factory for other options. Specifications are subject to change without notice.

