

2026 M40 Xtreme Stock Rules

Body

1. The minimum base weight of car and driver for entire class is 2250# race ready.
2. Any 4-cylinder rwd carbureted car.
3. Any 4,5-,or 6-cylinder fwd car with factory automatic or manual transmission.

Exceptions – No convertibles, No turbo or super charged engines, No multi carbs, No rotary engines, No mid or rear engine cars and No Cosworth engines. Factory stock fuel injection

only.

4. All rear and side glass must be removed, all windshields to be stock or Lexan. All cars must have a full windshield. Side and rear windows can be replaced with clear Lexan.
5. All exterior chrome, trim, molding, mirrors, and lights must be removed.
6. All door panels, carpet, headliner, plastic, upholstery, and any other flammable materials must be removed. All springs and latches must be removed. Dash pad can be replaced with a homemade style dash.
7. Aluminum sheeting will be allowed for bodies and the body must have stock or aftermarket stock nose and tail piece. No wedge style nose. Max. 4" splitter.
8. NO Late Model Look-alike cars.
9. A fully charged and properly mounted fire extinguisher is mandatory; 2lbs minimum, within drivers reach.
10. Spoilers 5" centered on the car or a rear sport wing, 50" max height measured from the ground.

Spoiler/wing clarification: -Spoiler to be a conventional circle track style, clear and no more than 5" tall. Can not be wider than the car body.

-Wing to be a rear deck/hatch mounted raised type (sport wing) that is no taller, at its highest point, than 50" from the ground. Can not be wider than the car body.

Engine/Drivetrain

1. You may remove excess wiring and sensors at your discretion. Aftermarket header is OK.

2. Batteries must be securely tied down and/or relocated and mounting tray reinforced.

Batteries may be relocated; however, they must be securely fastened and within a completely enclosed battery box, preferably metal with metal retaining bar. Box and battery

must be installed in a safe and responsible manner.

3. Stock Style Transmission and Transaxle Only. Must have working forward and reverse

gears. No made for racing style Transmission (Bert, Brinn, Falcon, etc.), No quick shift style

transmission.

4. A complete exhaust system with a maximum size of 3 1/2" O.D. mandatory. Exhaust must exit behind driver.

5. Any radiator allowed which will fit in stock brackets. 180-degree fan shroud required. An

overflow container mounted in the engine compartment. Water only in radiator; no anti freeze. **Cars caught with Antifreeze will be subject to a possible fine, loss of points, disqualification, or suspension**

6. Cars without the fuel pump mounted in the tank must use a cell or marine type tank mounted in the trunk. Stock tanks are allowed if mounted in the front of rear axle. Cells are

recommended and can be mounted to the trunk floor or in a built cage. Bottom feed cells

are OK only if mounted to stock floor pan. Tanks must be securely fastened to the trunk floor with a minimum of two, 1" x 1 1/16" straps in each direction, bolted through the floor

using double plates or installed in a safely constructed frame. Tanks shall be mounted 10"

from rear of the back panel and 8" off the ground or beyond the frame rails. (cell required

on wagons). Cars equipped with electrical fuel pumps must install a shut off switch clearly marked accessible from outside the car by race personnel.

7. Adjust coil over sleeves with stock type strut only. No adjustable coil over shocks.

8. Any fuel allowed except alcohol.

9. RWD cars must lock differential by means of a locking device or welded spider gears. No

open differentials or limited slip differentials allowed. Factory style rear axles only. **No**

Independent Style Rear End, Quick Change or 9" allowed. If it didn't come stock in these cars, it is not allowed Spring and Suspension components to mount in stock location.

10. RWD cars to be Steel Head only. No Aluminum heads

11. Steering and suspension shall be stock appearing and in stock location for year make and model of car.

11a. No sway bar rule.

11b. Cutting springs down or using progressive aftermarket stock style springs are OK.

11c. Must have stock style struts and non-adjustable shocks. Shock or struts with threads permanently made in their bodies are prohibited. Only slip on coil sleeves are allowed

12. Spring rubbers are OK.

13. Cambering of front wheels is allowed. Aftermarket OEM replacement struts that have

the camber adjustment already built in are OK. Open camber rule. .

Interior/Cage

1. Roll bar over driver's head required. Cages or bars shall be installed and constructed so

the B hoop is higher than drivers and passenger's head. Cage or bar must be mounted to

the floor pan. A 12"x12" (Approx.) steel plate should be used at hoop mounting points, gussets at main intersections recommended.

2. Minimum 3 driver's door bars are mandatory.

3. Front/rear bars – You are allowed to run up to 1 3/4" dia x .090 bars down to the rear struts on the back of the main cage as well as between the rear struts. You are allowed to run up to 1 3/4" diameter support bar between the two front strut towers. Maximum or any tubing size will be 1 3/4" round or square; there will be no 3" or 4" channel. The rear bars may

extend rearward from the top of the cage behind the driver, angling down towards the rear

trunk area. You are allowed to have one 1 3/4" x .090 piece of tubing run between the two

front frame horns of your car. This bar will be back from the front edge of the frame horn, so

it won't be mistaken as a support bar for your bumper. This bar is intended to keep the frame horns in place and to assist with the mounting of your radiator.

4. We suggest having a piece of tubing welded flat on the trunk floor, back near the kick-up

of the very rear of the trunk area. This is the material that your rear bars will attach to, no

bars of any kind will extend out through the rear of your trunk area; any bars out past this

point will need to be cut before racing. You may have an X in between your diagonal bars.

5. 5-point aftermarket full race harness is mandatory!
6. Aluminum racing seat is mandatory, it must be mounted properly. No fiberglass seats allowed.
7. Window nets are required.
8. **Front and Rear Tow Hooks are MANDATORY for quick hookup.**
9. Two-way radios are not allowed. No mirrors of any kind allowed.

Tires/Wheels

1. Hoosier 790 or 795 tires or Stock DOT type tires with 200 min. tread wear.
2. Buffing, Shaving, or Grooving is acceptable. **NO CHEMICAL ALTERATION OR SOAKING**
WILL BE ALLOWED!! We will be testing random tires. Penalties for altered tires can result in a Disqualification, Fine, Loss of points for event, or Suspension
3. Rims shall be 15" diameter or smaller but must all be the same size rim. Maximum 7" wide.
4. Oversized 1" lug nuts required.
5. Right front racing type safely wheels are mandatory, the other wheels can be racing wheels or stock.

Russell's M40 Speedway reserves the right to change, delete or add to rules throughout the

racing season. The management reserves the right of interpretation of all rules and the right to inspect and reject any car and/or driver, crew member, etc. during the racing program.

ANY INTERPRETATION OR CHANGING OF THESE RULES IS AT THE DISCRETION OF THE OFFICIALS. THEIR DECISION IS FINAL! ANY MAJOR INFRACTION OF

RULES WILL BE ASSESSED AS A FORFEITURE OF POINTS AND MONEY'S EARNED FOR NIGHT.

HEAD AND NECK RESTRAINT SYSTEMS HIGHLY RECOMMENDED!