

More Cutting Torque for Tough, Dense Growth

SRM-261T

For tough regional grasses and dense brush, Echo introduces the SRM-261T with 50% more cutting torque to make these jobs easier.

- 50% more cutting torque than standard SRM-261.
- Higher performance in thick regional grasses and brush applications.
- 25.4 cc commercial duty engine with Power Boost Tornado™ technology.
- Extra heavy-duty engine vibration reduction mount with padded handles to increase operator comfort.
- 59 in. flexible cable drive shaft.
- Echomatic® trimmer head.



25.4 cc commercial-duty engine with Power Boost Tornado™ technology.



50% higher cutting torque gear case powers through tough, dense growth.

Trimmer Specifications

Model	SRM-261T
Engine Displacement (cc)	25.4
Carburetor	Rotary w/Purge Pump
Pro-Fire® Electronic Ignition	Standard
Fuel Capacity (fl oz)	19.6
See-Through Fuel Tank	Standard
Dry Weight (lb.)	11.7* / 10.9**
Shield	Std. SRM
Cutting Swath (in.)	17
Nylon Line (in.)	.095 Cross-Fire®
Drive Shaft	Flexible
Shaft Length (in.)	59
Shaft Type	Straight
Starting System	Standard
Arbor Size (mm)	opt. 20
Cutting Head	Echomatic®

* Includes cutting head; excludes harness. ** w/o cutting head; excludes harness.
2 year consumer, 1 year commercial and 90 day rental warranty.

ECHO
Ask Any Pro!™

Performance... what else needs to be said about the world's finest commercial-grade trimmer? Echo's easy-to-use custom ergonomic controls, lightweight design and super powerful Power Boost Tornado™ technology give you the tools to enhance your productivity.



GT-200R/GT-200i (CARB: GT-201R/GT-201i)

Echo's best value, curved shaft trimmer includes either our new reduced effort i-30™ (GT-200R) or i-start™ (GT-200i) starting technology.

- Powerful and smooth-running, commercial-grade 21.2 cc Power Boost Tornado™ engine.
- i-30™ technology provides a 30% reduction in starting effort and i-start™ reduces effort 75%.
- Equipped with world's easiest loading 2-line Rapid-Loader™ trimmer head.
- High volume air filter provides outstanding engine protection.
- Heavy-duty, die-cast bearing housing provides optimum power transfer.

GT-230 (CARB: GT-231)

Echo's top-of-the-line curved shaft trimmer features a 52" shaft length and plenty of commercial-grade features.

- Powerful and smooth-running, commercial-grade 22.8 cc Power Boost Tornado™ engine.
- Die-cast fan cover with heavy-duty engine vibration reduction system.
- Cushioned throttle grip and foam-covered front D-handle provide added comfort.
- Heavy-duty, die-cast bearing housing provides optimum power transfer.

SRM-210/210i (CARB: SRM-211/211i)

Echo's lightest 21.2 cc straight shaft trimmer is perfect for medium-duty commercial applications.

- Powerful and smooth-running, commercial-grade 21.2 cc Power Boost Tornado™ engine.
- i-30 technology provides a 30% reduction in starting effort (SRM-210) and i-start reduces effort 75% (SRM-210i).
- High volume air filter provides outstanding engine protection.
- Edging-style left handle provides comfort and control.
- 15.2 fl oz see-through fuel tank extends run times.
- SRM-210i is equipped with world's easiest loading 2-line Rapid-Loader™ trimmer head.

SRM-210SB

A split boom design enables this trimmer to accommodate all Pro Attachment Series™ attachments.

- Powerful and smooth-running, commercial-grade 21.2 cc Power Boost Tornado™ engine.
- i-30 technology provides a 30% reduction in starting effort.
- Edging-style left handle provides comfort and control.
- 15.2 fl oz see-through fuel tank extends run times.
- Positive placement coupler accommodates multi-position attachments.

SRM-230/230S (CARB: SRM-231/231S)

Step up to the SRM-230 for increased power and performance.

- Powerful and smooth-running, commercial-grade 22.8 cc Power Boost Tornado™ engine.
- High volume air filter provides outstanding engine protection.
- Edging-style left handle provides comfort and control.
- Handle vibration reduction system consists of foam-covered right and left hand grips.
- 59" 4-layer, flex cable drive provides strength to handle tough applications (SRM-230).
- 59", 7mm steel drive shaft mounted in high quality oilite bearings for smooth, quick acceleration (SRM-230S).

SRM-260/260S (CARB: SRM-261/261S)

State-of-the-art 25.4 cc commercial-duty engine provides outstanding performance in a light, compact package.

- Hard-chromed cylinder, fully-caged needle bearings and forged connecting rod provide maximum engine durability.
- Extra heavy-duty engine vibration reduction mount and padded handles increase operator comfort.
- 59" 4-layer, flex cable drive provides strength to handle tough applications (SRM-260).
- 59", 7mm steel drive shaft mounted in high quality oilite bearings for smooth, quick acceleration (SRM-260S).
- Echomatic Pro™ trimmer head.

SRM-261T

For tough regional grasses and dense brush, Echo introduces the SRM-261T with 50% more cutting torque to make these jobs easier.

- 50% more cutting torque than standard SRM-261.
- Higher performance in thick regional grasses and brush applications.
- 25.4 cc commercial duty engine with Power Boost Tornado™ technology.
- Extra heavy-duty engine vibration reduction mount with padded handles to increase operator comfort.
- 59 in. flexible cable drive shaft.
- Echomatic® trimmer head.

SRM-311/311S

A powerful, 30.5 cc Power Boost engine makes the SRM-311 an all-around choice for tough trimming applications.

- Hard-chromed cylinder, fully-caged needle bearings and forged connecting rod provide maximum engine durability.
- Commercial-grade air filtration provides outstanding engine protection.
- 30.4 fl oz see-through fuel tank extends run times.
- 59", 7mm steel drive shaft mounted in high quality oilite bearings for smooth, quick acceleration (SRM-311S).

SRM-340

Reach for the SRM-340 for top-of-the-line trimming and cutting performance.

- 34 cc Power Boost™ engine provides back-up power for trimming thick brush and undergrowth.
- Hard-chromed cylinder, fully-caged needle bearings and forged connecting rod provide maximum engine durability.
- Commercial-grade air filtration provides outstanding engine protection.
- 27.1 fl oz see-through fuel tank extends run times.
- Heavy-duty, 60.2" shaft housing and rugged 8mm solid steel drive shaft.
- Shaft-mounted stop switch adds engine-stopping convenience.
- Includes blade conversion kit as standard equipment.

Trimmer Specifications

Model	GT-200R/201R	GT-200i/201i	GT-230/231	SRM-210/211	SRM-210i/211i	SRM-210SB	SRM-230/231
Engine Displacement (cc)	21.2	21.2	22.8	21.2	21.2	21.2	22.8
Carburetor (w/Purge Pump)	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
Pro-Fire® Electronic Ignition	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Starting System	i-30™	i-start™	Standard	i-30™	i-start™	i-30™	Standard
Fuel Capacity (oz)	15.2	15.2	19.6	15.2	15.2	15.2	19.6
See-through Fuel Tank	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Dry Weight (lb)*	9.3/9.6	9.6/9.9	11/11.2	11.4/11.6	11.6/11.8	11.9	12.2/12.4
Cutting Swath (in)	16	16	16	17	17	17	17
Nylon Line (in)	.080 Cross-Fire®	.080 Cross-Fire®	.080 Cross-Fire®	.095 Cross-Fire®	.095 Cross-Fire®	.095 Cross-Fire®	.095 Cross-Fire®
Drive Shaft	4-Layer Cable	4-Layer Cable	4-Layer Cable	4-Layer Cable	4-Layer Cable	4-Layer Cable	4-Layer Cable
Shaft Length (in)	48	48	52	59	59	59	59
Shaft Type	Curved	Curved	Curved	Straight	Straight	Split Shaft	Straight
Cutting Head	Rapid-Loader™	Rapid-Loader™	Semi-Auto	Semi-Auto	Rapid-Loader™	Semi-Auto	Semi-Auto
Model	SRM-230S/231S	SRM-260/261	SRM-260S/261S	SRM-261T	SRM-311	SRM-311S	SRM-340
Engine Displacement (cc)	22.8	25.4	25.4	25.4	30.5	30.5	34
Carburetor (w/Purge Pump)	Rotary	Rotary	Rotary	Rotary	Diaphragm	Diaphragm	Diaphragm
Pro-Fire® Electronic Ignition	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Starting System	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Fuel Capacity (oz)	19.6	19.6	19.6	19.6	30.4	30.4	27.1
See-through Fuel Tank	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Dry Weight (lb)*	12/12.2	11.9/12.1	11.5/11.7	11.7	14.5	15.5	16
Cutting Swath (in)	17	17	17	17	17	17	17
Nylon Line (in)	.095 Cross-Fire®	.095 Cross-Fire®	.095 Cross-Fire®	.095 Cross-Fire®	.095 Cross-Fire®	.105 Cross-Fire®	.105 Cross-Fire®
Drive Shaft	Rigid Steel	4-Layer Cable	Rigid Steel	Flexible	4-Layer Cable	Solid Steel	Solid Steel
Shaft Length (in)	59	59	59	59	59	59	60.2
Shaft Type	Straight	Straight	Straight	Straight	Straight	Straight	Straight
Cutting Head	Semi-Auto	Echomatic Pro™	Echomatic Pro™	Echomatic®	Echomatic®	High Capacity Semi-Auto	High Capacity Semi-Auto

* Includes cutting head; excludes harness.

2 year consumer, 1 year commercial and 90 day rental warranty.