



DRIVEN WITH TRUST

STEEL & ALUMINIUM WHEELS
COMMERCIAL TIRE


USA WHOLESALE DISTRIBUTORS



ADVANTAGES OF O'GREEN FORGED ALUMINIUM WHEELS

O'GREEN aluminum wheels are strong, stylish, durable and most importantly lightweight which when compared to conventional steel wheels offer better freight efficiencies through higher pay loads resulting in higher profits!

1 / LIGHT WEIGHT

- Up to 50% weight reduction compared to conventional steel wheels
- Increased load capacity resulting in increased profits
- Improved vehicle ride

2 / ENHANCED STRENGTH

- O'GREEN aluminum forging offer superior strength
- Up to 4 times the strength of conventional steel wheels
- 3 years unlimited mileage warranty

3 / COST SAVING

- Improved fuel economy (up to 7%)
- Faster heat dissipation (up to 3 times)
- Better dynamic balance (up to 5 times)
- Improved tyre and break life (up to 20%)
- Improved durability (up to 20 years)
- Lower maintenance costs

4 / ENVIRONMENTAL SUSTAINABILITY

- Aluminum is 100% recyclable
- Light weight and improved fuel efficiency resulting in lower greenhouse gas emissions

5 / APPEARANCE

- O'GREEN offers more appearance options (Machine, Mirror Polish & Chrome)
- Enhanced vehicle appearance and improved company image

ADVANCED PRODUCTION EQUIPMENT



PATTERN DISPLAY

	Long-Distance Transport + National & Regional Transport 	Mine Service 	Mine & Construction Site 
STEER/ALL POSITION 	 AG150 AG168 AG198 AG286 AG299  AG398S AG399 AG516 AG566 AG735	 AG298 AG958	 AG668
DRIVER 	 AG199 AG580  AG677 AG688 AG699	 AG219 AG288 AG450 AG816  AG828 AG835 AG868 AG896  AG898 AG969 AG738	 AG678 AG768  AG918 AG928
TRALLER 	 AG125 AG198 AG299 AG399		

TRUCK & BUS TIRE



TRUCK & BUS TIRE

AG150

TRUCK & BUS TIRE STRENGTHEN DESIGN

Excellent durability, Good ground grasping capacity, Low heat generation, Suitable for medium and long mileage vehicles running on the paved road with a standard load.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
295/80R22.5	18	M	9.00	152 149	900	3550	3250	298	1044	16
315/80R22.5	20	M	9.00	156 150	850	4000	3350	312	1076	18

TRUCK & BUS TIRE

AG168

mixed pattern for steering, outstanding performance, anti-sideslip, low noise, suitable for all kinds of road use and rural areas.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
6.50R16	12	L	5.50F	110 105	670	1060	925	185	750	12
7.00R16	14	L	5.50F	118 114	770	1320	1180	200	775	12
7.50R16LT	14	K	6.00G	122 118	770	1500	1320	215	805	13
8.25R16LT	16	K	6.50H	128 124	770	1800	1600	235	855	14
9.00R20	16	J	7.0	144 142	900	2800	2650	259	1019	15.5
10.00R20	18	J	7.5	149 146	930	3250	3000	278	1054	16
11R22.5	16	J	8.25	146 143	830	3000	2725	279	1054	16
11.00R20	18	J	8.0	152 149	930	3550	3250	293	1085	16.5
12.00R20	20	J	8.5	156 153	900	4000	3650	315	1125	17
12.00R24	20	K	8.5	160 157	900	4500	4125	315	1226	14
12R22.5	18	L	9.00	152 149	930	3550	3250	300	1085	16.5
13R22.5	18	L	9.75	154 151	830	3750	3450	320	1124	16.5
315/80R22.5	20	L	9.00	156 150	850	4000	3350	312	1076	15

TRUCK & BUS TIRE

AG198

High durability, high heat resistance, excellent wear resistance, excellent resistance to eccentric wear, good control stability, excellent noise. Suitable for short and middle distance high-speed buses, trucks, the airport bus, etc. suitable for the front wheel.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
9.5R17.5	18	M	6.75	143 141	875	2725	2575	240	842	13.5
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	15
12R22.5	16	M	9.00	150 147	830	3350	3075	300	1085	14.5
12R22.5	18	M	9.00	152 149	930	3550	3250	300	1085	14.5
215/75R17.5	16	J	6.00	135 133	850	2180	2060	211	767	13
235/75R17.5	16	M	6.75	132 129	850	2000	1850	233	797	12.5
255/70R22.5	16	M	7.50	140 137	830	2500	2300	255	930	14.5
275/70R19.5	18	M	8.25	148 145	900	2150	2900	276	958	14.5
295/75R22.5	14	L	9.00	144 141	760	2800	2575	298	1014	15
295/80R22.5	18	M	9.00	152 149	900	3550	3250	298	1044	15
315/80R22.5	20	M	9.00	156 150	850	4000	3350	312	1020	15

TRUCK & BUS TIRE

AG219

High wear-resisting performance, loading quantity, anti-stung ability, suitable for all the road situations.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1065	21
12R22.5	18	L	9.00	152 149	930	3550	3250	300	1085	22
265/70R19.5	18	J	7.50	143 141	850	2725	2575	262	8267	20
295/80R22.5	18	M	9.00	152 149	900	3550	3250	298	1050	20
305/70R19.5	16	M	9.00	148 145	850	3150	2900	305	923	20

TRUCK & BUS TIRE

AG199

High speed, high load, excellent traction, braking, resistance performance, applicable to the drive wheels.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	21

TRUCK & BUS TIRE

AG286

Apply to paved and high-speed roads, long-distance vehicles. High-speed stability, strong resistance, super wear resistance, good heat resistance.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
385/65R22.5	20	K	11.75	160	900	4500	—	389	1072	17
425/65R22.5	20	J	12.25	164	830	5000	—	422	1124	18

TRUCK & BUS TIRE

AG288

Extra deep tread depth offer excellent traction
Heavy bead design to support heavy load
Suitable for mining&mountain road

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
12.00R24	20	K	8.50	160 157	900	4500	4125	315	1226	17



TRUCK & BUS TIRE

AG299

High speed, high load, lateral spreads, wet resistance, small rolling resistance, Suitable for the front wheel or the all positions.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	15
12R22.5	16	M	9.00	150 147	830	3350	3075	300	1085	14
12R22.5	18	M	9.00	152 149	930	3550	3250	300	1085	14
295/75R22.5	14	L	8.25	144 141	760	2800	2575	298	1014	15

TRUCK & BUS TIRE

AG298

High-performance mixed pattern, suitable for all kinds of complicated road and all position.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
10.00R20	18	L	7.5	149 146	930	3250	3000	278	1054	16
11.00R20	18	L	8	152 149	930	3550	3250	293	1085	16.5
12.00R20	18	L	8.5	154 151	830	3750	3450	315	1125	17
12.00R20	20	L	8.5	156 153	900	4000	3650	315	1125	17
12.00R24	20	K	8.5	160 157	900	4500	4125	315	1226	17

TRUCK & BUS TIRE

AG398S

High speed, high load, lateral spreads, wet resistance, small rolling resistance, Suitable for the front wheel or the all positions.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	14	M	8.25	144 142	720	2800	2650	279	1054	17
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	17

TRUCK & BUS TIRE

AG399

High speed .Excellent load.
Excellent sideslip and mud slip resistance.
Suitable for medium and short mileage vehicles running on paved road



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
315/80R22.5	20	M	9.00	156 150	850	4000	3350	312	1076	15

TRUCK & BUS TIRE

AG516

Apply to good paved road surface with high speed road., long-distance vehicles.High speed driving stability, super wear resistance, low noise, good heat resistance, good drainage, good load capacity.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
9.5R17.5	18	M	6.75	143 141	875	2725	2575	240	842	13.5
215/75R17.5	16	J	6.00	135 133	850	2180	2060	211	767	12.5
235/75R17.5	16	M	6.75	132 129	830	2000	1850	233	797	12.5
255/70R22.5	16	M	7.50	140 137	830	2500	2300	255	930	14.5
265/70R19.5	16	M	7.50	140 138	775	2500	2360	262	867	14.5
265/70R19.5	18	J	7.50	143 141	850	2725	2575	262	867	14.5
275/70R22.5	18	M	8.25	148 145	900	3150	2900	276	958	14.5

TRUCK & BUS TIRE

AG450TRUCK & BUS TIRE **STRENGTHEN DESIGN**

Excellent durability,Good ground prasing capacity, Low heat generation, Suitable for medium and long mileage vehicles running on the paved road with a standard load.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
12R22.5	18	L	9.00	152 149	930	3550	3250	300	1096	21.5
315/80R22.5	20	L	9.00	156 150	850	4000	3350	312	1076	18

AG566

High wear-resisting performance, loading quantity, anti-stung ability, suitable for dive wheels.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
385/65R22.5	20	K	11.75	160	900	4500	—	389	1072	16.5

TRUCK & BUS TIRE

AG580



Excellent durability, Good ground grasping capacity, Low heat generation, Suitable for medium and long mileage vehicles running on the paved road with a standard load.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
12.00R24	20	K	8.5	160 157	900	4500	4125	315	1226	14

TRUCK & BUS TIRE

AG677



Ultra drive and brake ability, tearing resistance, cutting resistance, abrasion resistance, good load capacity, mixed road surface and generally topdress, medium and short vehicles use, suitable for driving wheel, drag wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	22

TRUCK & BUS TIRE

AG668



Generous tread pattern blocks, ultra deep pattern design, provide the strong power. Tire adopts super structure, excellent bearing capacity. Long life, wear-resisting, resistance, Suitable for mining, mountain road.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
10.00R20	16	F	7.5	149 146	930	3250	3000	278	1065	25
11.00R20	18	F	8.0	152 149	930	3550	3250	293	1085	25
12.00R20	20	F	8.5	156 153	900	4000	3650	315	1125	25

TRUCK & BUS TIRE

AG678



Generous tread pattern blocks, ultra deep pattern design, provide the strong power. Tire adopts super structure, excellent bearing capacity. Long life, wear-resisting, resistance, Suitable for mining, mountain road.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
7.50R16LT	14	F	6.00G	122 118	770	1500	1320	215	805	18
8.25R16LT	16	F	6.50H	128 124	770	1800	1600	235	855	18
11.00R20	18	F	8.0	152 149	930	3550	3250	293	1085	25
12.00R20	20	F	8.5	156 153	900	4000	3650	315	1125	25

TRUCK & BUS TIRE

AG688

High wear-resisting performance, loading quantity, anti-stung ability, suitable for drive wheels.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			

315/80R22.5	20	L	9.00	156 150	850	4000	3350	312	1076	20
-------------	----	---	------	---------	-----	------	------	-----	------	----

TRUCK & BUS TIRE

AG768

Suitable for off the road with extra deep tread depth; Excellent structure ensures wear resistance and heavy loads; Long mileage with strong traction.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			

9.00R20	16	F	7.00	144 142	900	2800	2650	259	1030	25
11.00R20	18	F	8.00	152 149	930	3550	3250	293	1096	25
12.00R20	18	F	8.50	154 151	830	3750	3450	315	1136	25

TRUCK & BUS TIRE

AG738

Suitable for driving wheel position and short/middle distance market; Directional mixed pattern design provide extremely good traction and prevent hydroplaning.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			

12R22.5	18	L	9.00	152 149	930	3550	3250	300	1096	21.5
---------	----	---	------	---------	-----	------	------	-----	------	------

TRUCK & BUS TIRE

AG816

High wear-resisting performance, loading quantity, anti-stung ability, suitable for drive wheels.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			

11R24.5	14	M	8.25	146 143	720	3000	2725	279	1116	22
11R24.5	16	M	8.25	149 146	830	3250	3000	279	1116	22

TRUCK & BUS TIRE

AG828



Ultra drive and brake ability, tearing resistance, cutting resistance, abrasion resistance, good load capacity, mixed road surface and generally topdress, medium and short vehicles use, suitable for driving wheel, drag wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
9.5R17.5	18	M	6.75	143 141	875	2725	2575	240	842	14.5
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1065	22
215/75R17.5	16	J	6.00	135 133	850	2180	2060	211	767	14.5
235/75R17.5	16	M	6.75	132 129	830	2000	1850	233	803	14
275/70R22.5	18	L	8.25	148 145	900	3150	2900	276	958	21

TRUCK & BUS TIRE

AG868



Excellent traction , Long service life ,
On the non-paved roads have better resistance to tearing and cutting ability.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
315/80R22.5	20	L	9.00	156 150	850	4000	3350	312	1082	22

TRUCK & BUS TIRE

AG896



Ultra drive and brake ability, tearing resistance, cutting resistance, abrasion resistance, good load capacity, mixed road surface and generally topdress, medium and short vehicles use, suitable for driving wheel, drag wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
6.50R16	12	J	5.50F	110 105	670	1060	925	185	750	15
7.00R16LT	14	K	5.50F	118 114	770	1320	1180	200	775	15
7.50R16LT	14	K	6.00G	122 118	770	1500	1320	215	815	15.5
8.25R16LT	16	K	6.50H	128 124	770	1800	1600	235	865	17.5
8.25R20	16	J	6.5	139 137	930	2430	2300	236	974	17.5
9.00R20	16	J	7.0	144 142	900	2800	2650	259	1030	18.5
10.00R20	18	J	7.5	149 146	930	3250	3000	278	1065	19
11R22.5	16	J	8.25	146 143	830	3000	2725	279	1065	21
11.00R20	18	J	8.0	152 149	930	3550	3250	293	1085	19.5
12.00R20	20	J	8.5	156 153	900	4000	3650	315	1125	20.5

TRUCK & BUS TIRE

AG898



Suitable for driving wheel position; Designed for short&middle distance market;
Open shoulder design provides excellent traction in wet&dry Conditions; Full-depth siping provides excellent performance throughout the life of the tread; Heavy duty casing for stability and promotion of retreading;

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
12R22.5	18	L	9.00	152 149	930	3550	3250	300	1096	21.5

TRUCK & BUS TIRE

AG918



Excellent load; Impact-resistance; Durability;
Pick-resistance on bad road

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
10.00R20	18	F	7.50	149 146	930	3250	3000	278	1065	19
11.00R20	18	F	8.00	152 149	930	3550	3250	293	1096	19.5
12.00R20	20	F	8.50	156 153	900	4000	3650	315	1136	20.5



TRUCK & BUS TIRE

AG958



Long time service life with the special formula, The gutter on the tread can reduce the noise and heat dispersion.
Suitable for all kinds of position on the trucks loading for middle and long distance on the good road.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11.00R20	18	L	8.0	152 149	930	3550	3250	293	1085	16.5
12.00R20	18	L	8.5	154 151	830	3750	3450	315	1125	17
12.00R20	20	L	8.5	156 153	900	4000	3650	315	1125	17
12R22.5	16	M	9.00	150 147	830	3350	3075	300	1085	18
12R22.5	18	M	9.00	152 149	930	3550	3250	300	1085	18
13R22.5	18	L	9.75	154 151	830	3750	3450	320	1124	16.5

TRUCK & BUS TIRE

AG928



Designed for mining road; Special huge block pattern has excellent traction; Excellent durability and wearing ability with special tread formula.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
10.00R20	18	F	7.50	149 146	930	3250	3000	278	1065	24
11.00R20	18	F	8.00	152 149	930	3550	3250	293	1096	24
12.00R20	20	F	8.50	156 153	900	4000	3650	315	1136	24

TRUCK & BUS TIRE

AG969



Specially designed tread let tires grip better;
Long service life with extra deep tread depth.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
10.00R20	18	J	7.50	149 146	930	3250	3000	278	1065	19.5
11.00R20	18	J	8.00	152 149	930	3550	3250	293	1096	19.5
12.00R20	20	J	8.50	156 153	900	4000	3650	315	1136	20.5



AG125

TRUCK & BUS TIRE

High speed, high load, lateral spreads, wet resistance, small rolling resistance, Suitable for the trailer wheels.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	14	M	8.25	144 142	720	2800	2650	279	1054	10.3
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	10.3
11R24.5	14	M	8.25	146 143	720	3000	2725	279	1104	10.3
11R24.5	16	M	8.25	149 146	830	3250	3000	279	1104	10.3
285/75R24.5	14	L	8.25	144 141	760	2800	2575	283	1050	10.3
295/75R22.5	14	L	9.00	144 141	760	2800	2575	298	1014	10.3
295/75R22.5	16	M	9.00	146 143	830	3000	2725	298	1014	10.3



AG735

TRUCK & BUS TIRE

Improved formula and structure.

High speed, high load, lateral spreads, wet resistance, small rolling resistance, Suitable for the front wheel or the trailers.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	14	M	8.25	144 142	720	2800	2650	279	1054	15
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	15
11R24.5	14	M	8.25	146 143	720	3000	2725	279	1104	15
11R24.5	16	M	8.25	149 146	830	3250	3000	279	1104	15
225/70R19.5	14	M	6.75	128 126	760	1800	1700	226	811	13.4
245/70R19.5	16	J	7.5	135 133	830	2180	2060	248	839	12.7
265/70R19.5	16	M	7.5	140 138	775	2500	2360	262	867	14.5
285/75R24.5	14	L	8.25	144 141	760	2800	2575	283	1050	15
295/75R22.5	14	M	9.00	146 143	830	3000	2725	298	1014	15
305/70R19.5	16	M	9.00	148 145	850	3150	2900	305	923	14.5



AG835

TRUCK & BUS TIRE

Ultra drive and brake ability, tearing resistance, cutting resistance, abrasion resistance, good load capacity, mixed road surface and generally topdress, medium and short vehicles use, suitable for driving wheel, drag wheels.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	14	M	8.25	144 142	720	2800	2650	279	1065	22
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1065	22
11R24.5	14	M	8.25	146 143	720	3000	2725	279	1116	22
11R24.5	16	M	8.25	149 146	830	3250	3000	279	1116	22
225/70R19.5	14	M	6.75	128 126	760	1800	1700	226	811	18
245/70R19.5	16	J	7.5	135 133	830	2180	2060	248	839	18
285/75R24.5	14	L	8.25	144 141	760	2800	2575	283	1056	22
295/75R22.5	14	M	9.00	146 143	830	3000	2725	298	1020	22

FORGED ALUMINIUM WHEELS



**Chrome Finishing
Available**

17.5x6.00



FORGED ALUMINIUM WHEELS

Wheel Size	Max load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
17.5x6.00	2200	135	20.4	32.5	6	164	222.25	Stud	YES
17.5x6.00	2200	135	20.4	26	10	176	225	Hub	YES
17.5x6.00	2200	135	20.4	32.5	5	146	203.2	Stud	YES
17.5x6.00	2200	135	20.4	29	5	146	203.2	Stud	YES
17.5x6.00	2200	135	20.4	21.5	6	140	190	Stud	YES
17.5x6.00	2200	135	20.4	21.5	6	161	205	Hub	YES



**Chrome Finishing
Available**

17.5x6.75



FORGED ALUMINIUM WHEELS

Wheel Size	Max load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
17.5x6.75	2500	141	21.3	32.5	6	164	222.25	Stud	YES
17.5x6.75	2500	141	21.3	26	10	176	225	Hub	YES
17.5x6.75	2500	141	21.3	21.5	6	161	205	Hub	YES
17.5x6.75	2500	141	21.3	26	6	202	245	Hub	YES
17.5x6.75	2500	141	21.3	26	8	221	275	Hub	YES



**Chrome Finishing
Available**

19.5x6.75



FORGED ALUMINIUM WHEELS

Wheel Size	Max.load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
19.5x6.75	2500	142	22.1	32.5	6	164	222.25	Stud	YES
19.5x6.75	2500	142	22.1	26	10	176	225	Hub	YES
19.5x6.75	2500	142	22.1	26	6	202	245	Hub	YES
19.5x6.75	2500	142	22.1	26	8	221	275	Hub	YES



**Chrome Finishing
Available**

22.5x7.50



FORGED ALUMINIUM WHEELS

Wheel Size	Max.load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
22.5x7.50	3350	161.5	22	32	10	281	335	Hub	YES
22.5x7.50	3350	161.5	22	26	10	281	335	Hub	YES
22.5x7.50	3350	161.5	22	26	8	221	275	Hub	YES
22.5x7.50	3350	161.5	22	32	8	214	275	Stud	YES
22.5x7.50	3350	161.5	22	26	10	220	285.75	Hub	YES



**Chrome Finishing
Available**



22.5x8.25



FORGED ALUMINIUM WHEELS

Wheel Size	Max.load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
22.5x8.25	3650	167	24.5	32	10	281	335	Hub	YES
22.5x8.25	3650	167	24.5	26	10	281	335	Hub	YES
22.5x8.25	3650	167	24.5	32	8	221	285	Stud	YES
22.5x8.25	3650	167	24.5	26	10	220	285.75	Hub	YES
22.5x8.25	3650	167	24.5	32	10	220	285.75	Stud	YES
22.5x8.25	3650	167	24.5	32	8	214	275	Stud	YES
22.5x8.25	3650	167	24.5	26	8	221	275	Hub	YES



**Chrome Finishing
Available**



22.5x9.00



FORGED ALUMINIUM WHEELS

Wheel Size	Max load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
22.5x9.00	4535	176	24.5	32	10	281	335	Hub	YES
22.5x9.00	4535	176	24.5	26	10	281	335	Hub	YES
22.5x9.00	4535	176	24.5	26	10	220	285.75	Hub	YES
22.5x9.00	4535	176	24.5	32	10	220	285.75	Stud	YES

22.5x13.00



FORGED ALUMINIUM WHEELS

Wheel Size	Max load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
22.5x13.00	5300	0	29	26	10	281	335	Hub	NO
22.5x13.00	5300	0	29	32	10	281	335	Hub	NO

22.5x11.75



FORGED ALUMINIUM WHEELS

Wheel Size	Max load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
22.5x11.75	4500	0	23	26	10	281	335	Hub	NO
22.5x11.75	4500	0	23	32	10	281	335	Hub	NO
22.5x11.75	4500	0	23	26	8	221	275	Hub	NO
22.5x11.75	4500	0	23	21.5	8	221	275	Hub	NO
22.5x11.75	4500	0	23	26	10	220	285.75	Hub	NO
22.5x11.75	4500	ET120	25.5	26	10	281	335	Hub	NO
22.5x11.75	4500	ET120	25.5	32	10	281	335	Hub	NO
22.5x11.75	4500	ET120	25.5	26	8	221	275	Hub	NO
22.5x11.75	4500	ET120	25.5	21.5	8	221	275	Hub	NO
22.5x11.75	4500	ET120	25.5	26	10	220	285.75	Hub	NO

22.5x14.00



FORGED ALUMINIUM WHEELS

Wheel Size	Max load (Kg)	Offset (mm)	Disc Thickness	Stud Hole Dia (mm)	Number of Stud Holes	Centre Bore Dia (mm)	P.C.D (mm)	Mounting Type	Dual Mount
22.5x14.00	5800	0	31	26	10	281	335	Hub	NO
22.5x14.00	5800	0	31	32	10	281	335	Hub	NO

STEEL WHEELS

STEEL WHEEL

31



**Chrome Finishing
Available**



DEMOUNTABLE RIM

**17.5×6.00 17.5×6.75 22.5×7.50
22.5×9.00 22.5×8.25 22.5×11.75
7.50V-20**



STEEL WHEEL

**6.50-20 7.00-20 7.50-20
8.00-20 8.50-20 8.50-24**

32



**Chrome Finishing
Available**



STEEL WHEEL

Size	PCD	CBD	Offset	Bore hole			Disc thickness
				Number	Dia	Type	
17.5 × 5.25	203	133	125	5	32	SR22	10
	203.2	146	125/115/108	5	32.5/29	SR22	10
	205	161	125	6	26/21.5	1X45°	10
	208	150	115	5	32.5	SR22	10
	222.25	164	128	6	32	SR22	10
	225	176	120	10	26/27/21.5	1X45° /SR18	10
17.5 × 6.00	203.2	146	118/125/135	5	32/21.5/29	SR22/SR14	10
	205	161	0/118/125	6	21.5	SR16	10
	208	150	87/127/135	5	32/32.5	SR22	10
	222.25	164	98/125/135	6	32.5	SR22	10
	225	176	113/120/135	10	26	1X45° /SR18	10
	245	202	135	6	21.5	SR16	10
17.5 × 6.75	275	221	135	8	21.5	SR16	10
	205	161	0/135	6	21.5/27	SR16/sr18	12
	222	165	33	6	21.5	1X45°	12
	222.25	164/165.1/166	0/135	6	32.5	1X45° /SR22/	12
	225	176	113/120/135	10	26	1X45° /SR18	12
	245	202	135	6	21.5	SR16	12
	275	221	135	8	21.5	SR16	12



STEEL WHEEL

Size	PCD	CBD	Offset	Bore hole			Disc thickness
				Number	Dia	Type	
19.5 × 6.75	203.2	152.4	0	8	18	SR14	12
	205	161	0	6	21.5	SR16	12
	222.25	164	135	6	32/32.5	SR22	12
	225	176	135	10	26	1X45°	12
	275	221	140	8	24/26/32.5	1X45°	12
	285	221	145	8	32.5	SR22	12
19.5 × 7.50	203.2	152.4	38	8	17.5	—	12
	205	161	0	6	21.5	SR16	12
	225	175	138	10	26/27	1X45° /SR18	12
	275	221	0/135/145	8	21.5/24/26/27	SR16/1X45° /SR18	12
	285.75	220	152	10	26	1X45°	12
	335	281	0	10	27	SR18	12
19.5 × 8.25	205	161	0/25	6	21.5	SR16/1X45°	12
	222.25	164	0	6	32.5	SR22	12
	225	176	0/160	10	26	1X45°	12
	275	221	0/147	8	21.5/24/26	1X45° /SR16	12
19.5 × 11.75	205	161	0	6	18/21.5	SR16	12
	225	176	0	10	27	SR16	12
	250	200	30	6	32.5	SR22	12
	275	221	0	8	21.5/27	SR16/SR18	12
19.5 × 14.0	335	281	0	10	26	1X45°	12
	205	161	0	6	21.5	SR16	12
	225	176	0	10	27	SR18	12
	275	221	0/75	8	21.5/26/27	SR16/1X45° /SR18	12
	335	281	0/50/100	10	26/27	1X45° /SR18	12

NEW Chrome Finishing Available



STEEL WHEEL

5 1/2 × 16 **6.0 × 16**
12 × 4JA **13 × 4.5JB**
14 × 5.5JJ **15 × 5JJ** **15 × 6JJ**
16 × 5.5K **16 × 6JJ** **16 × 6JJ**



Chrome Finishing Available

FOR SPECIAL U.S.



STEEL WHEEL

Size	PCD	CBD	Offset	Bore hole			Disc thickness
				Number	Dia	Type	
22.5 × 6.75	222.25	164	140	6	32.5	SR22	14
	205	161	0	6	21.5	SR16	14
22.5 × 7.50	275	221	0/140	8	24/26/27	1X45° /SR18	14
	285	221	152/165	8	32/32.5	SR22	14
	285.75	220	152/168	10	27	1X45°	14
	335	281	151/160	10	26/27	1X45° /SR18	14
	203.2	152.4	38	8	16.6	—	14
22.5 × 8.25	205	161	38	6	21.5	SR16	14
	275	221	0/165	8	21.5/24/26/27	SR16/1X45°	14
	285	221	165	8	32.5	SR22	14
	285.75	220/221	165	10	26/27/32/32.5	SR16/1X45° /SR18	14
	335	281	0/120/165	10	26/27	1X45° /SR18	14
22.5 × 9.00	205	161	38	6	21.5	SR16	14
	275	221	0/165	8	21.5/24/26/27	SR16/1X45°	14
	285	221	165	8	32.5	SR22	14
	285.75	220/221	165	10	26/27/32/32.5	SR16/1X45° /SR18	14
	335	281	0/120/165	10	26/27	1X45° /SR18	14
22.5 × 11.75	203.2	152.4	38	8	16.6	—	14
	205	161	38	6	21.5	SR16	14
	275	221	0/165	8	21.5/24/26/27	SR16/1X45°	14
	285	221	165	8	32.5	SR22	14
	285.75	220/221	165	10	26/27/32/32.5	SR16/1X45° /SR18	14
22.5 × 13.00	335	281	0/120/165	10	26/27	1X45° /SR18	14
	203.2	152.4	38	8	16.6	—	14
	275	221	0/165	8	21.5/24/26/27	SR16/1X45°	14
	285.75	220	0/120	10	26	1X45°	14
	335	281	0/120	10	26/27	SR16/1X45° /SR18	14
22.5 × 14.00	225	176	0	10	27	SR18	14
	275	221	0/97	8	21.5	SR16/1X45° /SR18	14
	335	281	0/175	10	24/26/27	SR16/1X45° /SR18	14
22.5 × 16.00	205	161	0/50	6	21.5	SR16	14
	275	221	0/50	8	21.5/27	SR16/SR18	14
	335	281	0/50	10	26/27	SR16/1X45° /SR18	14
22.5 × 20.00	275	221	0/50	8	21.5/27	SR16/SR18	14
	285.75	220	0/50	10	26/27	1X45° /SR22	14
	335	281	0/50/100	10	26/27	1X45° /SR18	14



Rolling Around the World

📍 12574 Westhampton Circle
Wellington FL 33414 USA

📞 +1 305 8905386 📱 📘

✉️ salesdirector@tirenetworkusa.co 🌐 www.tirenetworkusa.co

