

# SIERRA

TRUCK TIRES

2017



## SIZE CHART

[illegible]

# TABLE OF CONTENTS

## STEER/ALL-POSITION/TRAILER

|             |   |
|-------------|---|
| SR256 ..... | 1 |
| SR803 ..... | 1 |
| SR562 ..... | 2 |

## DRIVE

|             |   |
|-------------|---|
| SR369 ..... | 2 |
| SR366 ..... | 3 |
| SR349 ..... | 3 |
| SR378 ..... | 4 |
| SR377 ..... | 4 |

## MIXED SERVICE

|             |   |
|-------------|---|
| SR568 ..... | 5 |
| SR518 ..... | 5 |
| SR301 ..... | 6 |

## WIDE BASE

|             |   |
|-------------|---|
| SR216 ..... | 6 |
| SR306 ..... | 7 |

## TRACTION

|             |   |
|-------------|---|
| SR387 ..... | 7 |
| SR317 ..... | 8 |

## SR256 STEER

### FEATURES & BENEFITS

- DECOUPLING GROOVE TO MINIMIZE IRRGULAR WEAR
- FIVE RIB DESIGN PROMOTES EVEN WEAR AND LONG TIRE LIFE
- ENHANCED SIPING FOR WATER DISPERSION
- STONE EJECTORS TO MINIMIZE STONE RETENTION



| PRODUCT CODE | SIZE    | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|---------|-------|------|---------------------|------------|-------------|----|------------------|------|---------------|-----|----------------------------|-----------------|--------|-------|
|              |         |       |      |                     |            | 32nds       | mm | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg    |
| 97201        | 11R22.5 | H/16  | TL   | 146/143M            | 8.25       | 19          | 15 | 41.50            | 1054 | 10.98         | 279 | 6610/6005                  | 120/120         | 120.15 | 54.50 |
| 97207        | 11R24.5 | H/16  | TL   | 149/146M            | 8.25       | 19          | 15 | 43.46            | 1104 | 10.98         | 279 | 7160/6610                  | 120/120         | 131.39 | 59.60 |

## SR803 STEER / ALL-POSITION

### FEATURES & BENEFITS

- EXCELLENT STABILITY AND REISISTANCE TO IRREGULAR WEAR
- STONE EJECTORS PROVIDE GOOD SELF-CLEANING
- FOUR GROOVE DESIGN FOR ENHANCED WATER DISPERSION
- RIB SIPING FOR INCREASED TRACTION
- DEEP ORIGINAL TREAD DEPTH PROMOTES LONG TIRE LIFE



| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |      | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-------------|-------|------|---------------------|------------|-------------|------|------------------|------|---------------|-----|----------------------------|-----------------|--------|-------|
|              |             |       |      |                     |            | 32nds       | mm   | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg    |
| 97301        | 11R22.5     | H/16  | TL   | 146/143M            | 8.25       | 20          | 15.5 | 41.50            | 1054 | 10.98         | 279 | 6610/6005                  | 120/120         | 125.22 | 56.80 |
| 97305        | 12R22.5     | J/18  | TL   | 152/149M            | 9.00       | 19          | 15   | 42.72            | 1085 | 11.81         | 300 | 7830/7160                  | 135/135         | 137.13 | 62.20 |
| 97308        | 255/70R22.5 | H/16  | TL   | 140/137M            | 7.50       | 16          | 13   | 32.68            | 830  | 10.04         | 255 | 5520/5070                  | 120/120         | 97.00  | 44.00 |
| 97319        | 275/70R22.5 | H/16  | TL   | 148/145M            | 8.25       | 18          | 14   | 37.72            | 958  | 10.87         | 276 | 6940/6385                  | 130/130         | 111.33 | 50.50 |
| 97312        | 295/75R22.5 | H/16  | TL   | 146/143M            | 9.00       | 19          | 15   | 39.92            | 1014 | 11.73         | 298 | 6610/6005                  | 120/120         | 110.47 | 50.11 |
| 97304        | 285/75R24.5 | H/16  | TL   | 147/144M            | 8.25       | 19          | 15   | 41.34            | 1050 | 11.14         | 283 | 6780/6175                  | 120/120         | 120.81 | 54.80 |
| 97313        | 295/80R22.5 | J/18  | TL   | 152/149M            | 9.00       | 19          | 15   | 41.10            | 1044 | 11.73         | 298 | 7830/7160                  | 125/125         | 130.95 | 59.40 |
| 97310        | 315/80R22.5 | J/18  | TL   | 154/151M            | 9.00       | 19          | 15   | 42.36            | 1076 | 12.28         | 312 | 8270/7610                  | 120/120         | 141.09 | 64.00 |
| 97303        | 11R24.5     | H/16  | TL   | 149/146L            | 8.25       | 19          | 15   | 43.46            | 1104 | 10.98         | 279 | 7160/6610                  | 120/120         | 132.76 | 60.22 |

## SR562 ALL-POSITION/TRAILER

### FEATURES & BENEFITS

- RIB TIRE WITH FOUR CIRCUMFERENTIAL GROOVES
- SHOULDER NOTCHING AND SIPES EFFECTIVELY DISPERSE SHOULDER HEAT TO IMPROVE ENDURANCE
- CONVEX PLATFORM ON THE BOTTOM OF THE GROOVE PREVENTS GROOVE STRAIN AND CRACKING



| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |      | OVERALL DIAMETER |     | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-------------|-------|------|---------------------|------------|-------------|------|------------------|-----|---------------|-----|----------------------------|-----------------|--------|-------|
|              |             |       |      |                     |            | 32nds       | mm   | inch             | mm  | inch          | mm  |                            |                 | lbs    | kg    |
| 97005        | 6.50R16LT   | F/12  | TT   | 110/105L            | 5.50F      | 13          | 10.5 | 29.53            | 750 | 7.28          | 185 | 2340/2040                  | 95/95           | 46.96  | 21.30 |
| 97006        | 7.00R16LT   | G/14  | TT   | 118/114L            | 5.50F      | 14          | 11   | 30.51            | 775 | 7.87          | 200 | 2910/2600                  | 110/110         | 51.37  | 23.30 |
| 97007        | 7.50R16LT   | G/14  | TT   | 122/118L            | 6.00G      | 16          | 12.5 | 31.69            | 805 | 8.46          | 215 | 3305/2910                  | 110/110         | 65.70  | 29.80 |
| 97008        | 215/75R17.5 | H/16  | TL   | 135/133M            | 6.00       | 16          | 13   | 30.20            | 767 | 8.31          | 211 | 4805/4540                  | 123/123         | 58.86  | 26.70 |
| 97001        | 235/75R17.5 | H/16  | TL   | 143/141M            | 6.75       | 16          | 13   | 31.38            | 797 | 9.17          | 233 | 6005/5675                  | 120/120         | 70.55  | 32.00 |
| 97002        | 225/70R19.5 | G/14  | TL   | 128/126L            | 6.75       | 18          | 14   | 31.93            | 811 | 8.90          | 226 | 3970/3750                  | 110/110         | 70.33  | 31.90 |
| 97003        | 245/70R19.5 | G/14  | TL   | 133/131L            | 7.50       | 18          | 14   | 33.03            | 839 | 9.76          | 248 | 4540/4300                  | 110/110         | 74.96  | 34.00 |

## SR369 CLOSED-SHOULDER DRIVE

### FEATURES & BENEFITS

- DEEP, LONG LASTING TREAD
- SPECIAL GROOVE DESIGN PREVENTS STONE RETENTION TO PROTECT THE CASING
- SOLID CLOSED-SHOULDER RIB PROMOTES EVEN WEAR
- WIDE TREAD DESIGN WITH SIPING IN TREAD BLOCKS FOR INCREASED TRACTION



| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-------------|-------|------|---------------------|------------|-------------|----|------------------|------|---------------|-----|----------------------------|-----------------|--------|-------|
|              |             |       |      |                     |            | 32nds       | mm | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg    |
| 97101        | 11R22.5     | H/16  | TL   | 146/143L            | 8.25       | 29          | 23 | 41.93            | 1065 | 10.98         | 279 | 6610/6005                  | 120/120         | 129.41 | 58.70 |
| 97102        | 295/75R22.5 | H/16  | TL   | 146/143L            | 9.00       | 29          | 23 | 40.16            | 1020 | 11.73         | 298 | 6610/6005                  | 120/120         | 126.32 | 57.30 |
| 97103        | 11R24.5     | H/16  | TL   | 149/146L            | 8.25       | 29          | 23 | 43.94            | 1116 | 10.98         | 279 | 7160/6610                  | 120/120         | 141.54 | 64.20 |
| 97104        | 285/75R24.5 | H/16  | TL   | 147/144L            | 8.25       | 29          | 23 | 41.57            | 1056 | 11.14         | 283 | 6780/6175                  | 120/120         | 131.84 | 59.80 |

## SR366

## OPEN-SHOULDER DRIVE

### FEATURES & BENEFITS

- DEEP TREAD DEPTH FOR EXCELLENT TRACTION
- OPEN-SHOULDER DESIGN PROVIDES HEAT DISSIPATION TO ASSIST WITH TIRE DURABILITY
- SPECIAL TREAD COMPOUNDS TO RESIST CUTTING AND CHIPPING
- SIPING IN TREAD BLOCKS FOR ENHANCED TRACTION



| PRODUCT CODE | SIZE    | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|---------|-------|------|---------------------|------------|-------------|----|------------------|------|---------------|-----|----------------------------|-----------------|--------|-------|
|              |         |       |      |                     |            | 32nds       | mm | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg    |
| 97602        | 11R22.5 | H/16  | TL   | 146/143M            | 8.25       | 29          | 23 | 41.93            | 1065 | 10.98         | 279 | 6610/6005                  | 120/120         | 131.61 | 59.70 |
| 97604        | 11R24.5 | H/16  | TL   | 149/146M            | 8.25       | 29          | 23 | 43.94            | 1116 | 10.98         | 279 | 7160/6610                  | 120/120         | 144.62 | 65.60 |

## SR349

## DRIVE

### FEATURES & BENEFITS

- WIDE, OPEN-SHOULDER DESIGN FOR IMPROVED WEAR RESISTANCE
- ANGLED SIPING IMPROVES GRIP AND OVERALL TRACTION
- TAPERED LATERAL GROOVES FOR ALL-WEATHER PERFORMANCE
- DEEP TREAD FOR LONG ORIGINAL MILEAGE



| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-------------|-------|------|---------------------|------------|-------------|----|------------------|------|---------------|-----|----------------------------|-----------------|--------|-------|
|              |             |       |      |                     |            | 32nds       | mm | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg    |
| 97631        | 12R22.5     | J/18  | TL   | 152/149L            | 9.00       | 26          | 21 | 42.72            | 1085 | 11.81         | 300 | 7830/7160                  | 135/135         | 147.49 | 66.90 |
| 97632        | 13R22.5     | J/18  | TL   | 154/151L            | 9.75       | 26          | 21 | 44.25            | 1124 | 12.60         | 320 | 8270/7610                  | 120/120         | 166.67 | 75.60 |
| 97635        | 295/80R22.5 | J/18  | TL   | 152/149M            | 9.00       | 24          | 19 | 41.10            | 1044 | 11.73         | 298 | 7830/7160                  | 130/130         | 133.60 | 60.60 |
| 97633        | 315/80R22.5 | J/18  | TL   | 154/151K            | 9.00       | 26          | 21 | 42.36            | 1076 | 12.28         | 312 | 8270/7610                  | 120/120         | 152.34 | 69.10 |
| 97634        | 315/80R22.5 | L/20  | TL   | 157/154K            | 9.00       | 26          | 21 | 42.36            | 1076 | 12.28         | 312 | 9090/8270                  | 130/130         | 152.34 | 69.10 |

## SR378 DRIVE

### FEATURES & BENEFITS

- OPEN-SHOULDER HORIZONTAL BLOCK DESIGN
- SPECIAL COMPOUNDED BEAD AREA ENHANCES DURABILITY AND LOADING CAPACITY
- STONE EJECTORS IN THE BASE OF THE TREAD GROOVE



| PRODUCT CODE | SIZE      | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |      | OVERALL DIAMETER |     | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-----------|-------|------|---------------------|------------|-------------|------|------------------|-----|---------------|-----|----------------------------|-----------------|--------|-------|
|              |           |       |      |                     |            | 32nds       | mm   | inch             | mm  | inch          | mm  |                            |                 | lbs    | kg    |
| 97611        | 7.50R16LT | G/14  | TT   | 122/118L            | 6.00G      | 19          | 15.0 | 31.69            | 805 | 8.46          | 215 | 3310/2913                  | 110/110         | 70.11  | 31.80 |

## SR377 DRIVE

### FEATURES & BENEFITS

- HORIZONTAL BLOCK PATTERN FOR EXCELLENT TRACTION AND BRAKING ON ROUGH ROADS
- SPECIAL TREAD COMPOUNDS TO RESIST CHIPPING AND CHUNKING
- SELF-CLEANING ATTRIBUTES TO OPTIMIZE TRACTION



| PRODUCT CODE | SIZE      | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |      | OVERALL DIAMETER |     | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-----------|-------|------|---------------------|------------|-------------|------|------------------|-----|---------------|-----|----------------------------|-----------------|--------|-------|
|              |           |       |      |                     |            | 32nds       | mm   | inch             | mm  | inch          | mm  |                            |                 | lbs    | kg    |
| 97901        | 7.50R16LT | G/14  | TT   | 122/118F            | 6.00G      | 21          | 16.5 | 32.09            | 815 | 8.46          | 215 | 3310/2913                  | 110/110         | 71.43  | 32.40 |

## SR568 MIXED SERVICE ALL-POSITION



### FEATURES & BENEFITS

- FOUR-RIB TIRE DESIGN SUITABLE FOR MIXED SERVICE APPLICATIONS
- SPECIAL TREAD COMPOUNDS TO RESIST CHIPPING AND CHUNKING
- THREE CIRCUMFERENTIAL GROOVES AID IN EVEN WEAR AND A SMOOTH RIDE
- WIDE FOOTPRINT AND UNIQUE SHOULDER DESIGN ENHANCE STABILITY

| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |      | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-------------|-------|------|---------------------|------------|-------------|------|------------------|------|---------------|-----|----------------------------|-----------------|--------|-------|
|              |             |       |      |                     |            | 32nds       | mm   | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg    |
| 97938        | 7.00R16LT   | G/14  | TT   | 118/114L            | 5.00       | 14          | 11   | 30.51            | 775  | 7.90          | 200 | 2910/2600                  | 110/110         | 50.89  | 23.13 |
| 97503        | 7.50R16LT   | G/14  | TT   | 122/118L            | 6.00       | 16          | 12.5 | 31.69            | 805  | 8.46          | 215 | 3305/2910                  | 110/110         | 65.70  | 29.80 |
| 97513        | 11R22.5     | H/16  | TL   | 146/143L            | 8.25       | 20          | 16   | 41.50            | 1054 | 10.98         | 279 | 6610/6005                  | 120/120         | 123.46 | 56.00 |
| 97509        | 12R22.5     | J/18  | TL   | 152/149K            | 9.00       | 20          | 16   | 42.72            | 1085 | 11.81         | 300 | 7830/7160                  | 135/135         | 139.55 | 63.30 |
| 97511        | 315/80R22.5 | L/20  | TL   | 157/154K            | 9.00       | 20          | 16   | 42.36            | 1076 | 12.28         | 312 | 9090/8270                  | 130/130         | 141.54 | 64.20 |

## SR518 MIXED SERVICE ALL-POSITION



### FEATURES & BENEFITS

- FOUR-RIB ZIGZAG TIRE DESIGN SUITABLE FOR MIXED SERVICE APPLICATIONS
- SHOULDER DESIGN FOR INCREASED TRACTION
- SPECIAL TREAD COMPOUNDS TO RESIST CHIPPING AND CHUNKING

| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |      | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-------------|-------|------|---------------------|------------|-------------|------|------------------|------|---------------|-----|----------------------------|-----------------|--------|-------|
|              |             |       |      |                     |            | 32nds       | mm   | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg    |
| 97400        | 8.25R16LT   | H/16  | TT   | 128/124L            | 6.50H      | 16          | 13   | 33.66            | 855  | 9.25          | 235 | 3970/3525                  | 110/110         | 76.50  | 34.70 |
| 97405        | 11R22.5     | H/16  | TL   | 146/143L            | 8.25       | 20          | 16   | 41.50            | 1054 | 10.98         | 279 | 6610/6005                  | 120/120         | 123.50 | 56.02 |
| 97404        | 12R22.5     | J/18  | TL   | 152/149K            | 9.00       | 21          | 17   | 42.72            | 1085 | 11.81         | 300 | 7830/7160                  | 135/135         | 139.55 | 63.30 |
| 97408        | 315/80R22.5 | L/20  | TL   | 157/154K            | 9.00       | 21          | 16.5 | 42.36            | 1076 | 12.28         | 312 | 9090/8270                  | 130/130         | 141.54 | 64.20 |
| 97409        | 11R24.5     | H/16  | TL   | 149/146L            | 8.25       | 20          | 16   | 43.46            | 1104 | 10.98         | 279 | 7160/6610                  | 120/120         | 133.93 | 60.75 |

## SR301 MIXED SERVICE DRIVE

### FEATURES & BENEFITS

- DEEP TREAD ELEMENTS FOR IMPROVED TRACTION
- HORIZONTAL INTERLOCKING LUGS FOR IMPROVED STABILITY
- CONTINUOUS CENTER RIB FOR HIGHWAY STABILITY



| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |      |
|--------------|-------------|-------|------|---------------------|------------|-------------|----|------------------|------|---------------|-----|----------------------------|-----------------|--------|------|
|              |             |       |      |                     |            | 32nds       | mm | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg   |
| 97931        | 11R22.5     | H/16  | TL   | 148/145L            | 8.25       | 26          | 21 | 41.50            | 1054 | 11.00         | 279 | 6940/6385                  | 123/123         | 125.97 | 57   |
| 97934        | 12R22.5     | J/18  | TL   | 152/149L            | 9.00       | 26          | 21 | 42.68            | 1084 | 11.80         | 300 | 7830/7160                  | 135/135         | 139.23 | 63   |
| 97935        | 295/80R22.5 | J/18  | TL   | 152/149L            | 9.00       | 26          | 21 | 41.34            | 1050 | 11.70         | 298 | 7830/7160                  | 130/130         | 144.31 | 65.3 |

## SR216 WIDE BASE

### FEATURES & BENEFITS

- SPECIAL TREAD FORMULA DELIVERES LOWER ROLLING RESISTANCE AND BETTER FUEL ECONOMY
- VARIABLE PITCH DESIGN EFFECTIVELY REDUCES DRIVING NOISE
- FIVE CIRCUMFERENTIAL GROOVES FOR CONTROL PERFORMANCE



| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-------------|-------|------|---------------------|------------|-------------|----|------------------|------|---------------|-----|----------------------------|-----------------|--------|-------|
|              |             |       |      |                     |            | 32nds       | mm | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg    |
| 97703        | 385/65R22.5 | L/20  | TL   | 160/L               | 11.75      | 20          | 16 | 42.20            | 1072 | 15.31         | 389 | 9930/N/A                   | 130/N/A         | 164.46 | 74.60 |
| 97705        | 425/65R22.5 | L/20  | TL   | 164/K               | 12.25      | 20          | 16 | 44.25            | 1124 | 16.61         | 422 | 11000/N/A                  | 120/N/A         | 193.12 | 87.60 |

## SR306 WIDE BASE

### FEATURES & BENEFITS

- LARGE TREAD ELEMENTS FOR IMPROVED HANDLING AND TRACTION
- DEEP TREAD FOR LONG TIRE LIFE
- ENHANCED Siping FOR IMPROVED TRACTION



| PRODUCT CODE | SIZE        | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |        | SECTION WIDTH |       | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |       |
|--------------|-------------|-------|------|---------------------|------------|-------------|----|------------------|--------|---------------|-------|----------------------------|-----------------|--------|-------|
|              |             |       |      |                     |            | 32nds       | mm | inch             | mm     | inch          | mm    |                            |                 | lbs    | kg    |
| 97937        | 425/65R22.5 | L/20  | TL   | 165K                | 12.25      | 28          | 22 | 44.3             | 1124.0 | 16.60         | 422.0 | 11400/N/A                  | 120/N/A         | 209.95 | 95.00 |

## SR387 ON/OFF-ROAD TRACTION

### FEATURES & BENEFITS

- TRACTION DESIGN FOR STRONGER DRIVING FORCE
- DEEP LUGS AND HORIZONTAL PATTERN DESIGN FOR IMPROVED HANDLING
- 26/32" ORIGINAL TREAD DEPTH ALLOWS FOR EXCELLENT MILEAGE



| PRODUCT CODE | SIZE     | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS) SINGLE/DUAL | PSI SINGLE/DUAL | WEIGHT |    |
|--------------|----------|-------|------|---------------------|------------|-------------|----|------------------|------|---------------|-----|----------------------------|-----------------|--------|----|
|              |          |       |      |                     |            | 32nds       | mm | inch             | mm   | inch          | mm  |                            |                 | lbs    | kg |
| 97936        | 12.00R20 | L/20  | TT   | 156/153K            | 8.50       | 26          | 21 | 44.72            | 1136 | 12.40         | 315 | 8820/8050                  | 130/130         | 181.22 | 82 |

# SR317 ON/OFF-ROAD TRACTION



## FEATURES & BENEFITS

- OPEN-SHOULDER DESIGN FOR EXCELLENT TRACTION
- DEEP ORIGINAL TREAD DEPTH FOR LONG TIRE LIFE
- AGGRESSIVE TREAD DESIGN FOR SEVERE OFF-HIGHWAY USE

| PRODUCT CODE | SIZE    | LR/PR | TYPE | SERVICE DESCRIPTION | RIM (inch) | TREAD DEPTH |    | OVERALL DIAMETER |      | SECTION WIDTH |     | MAX LOAD (LBS)<br>SINGLE/DUAL | PSI<br>SINGLE/DUAL | WEIGHT |    |
|--------------|---------|-------|------|---------------------|------------|-------------|----|------------------|------|---------------|-----|-------------------------------|--------------------|--------|----|
|              |         |       |      |                     |            | 32nds       | mm | inch             | mm   | inch          | mm  |                               |                    | lbs    | kg |
| 97932        | 11R22.5 | H/16  | TL   | 148/145G            | 8.25       | 26          | 21 | 41.93            | 1065 | 11.00         | 279 | 6940/6385                     | 123/123            | 130.39 | 59 |
| 97933        | 12R22.5 | J/18  | TL   | 152/149G            | 9.00       | 29          | 23 | 43.15            | 1096 | 11.80         | 300 | 7830/7160                     | 135/135            | 145.86 | 66 |

# SIERRA

## TRUCK TIRES

**Distributed By:**

**TIRENetwork**  
WHOLESALE DISTRIBUTORS  
*Rolling Around the World*

**Luis E. Betancourth**  
Managing Director

12574 Westhampton Circle  
Wellington FL 33414 USA

+1 305 8905386

salesdirector@tirenetworkusa.co

www.tirenetworkusa.co

