

Lenz

P/N: Lenz

Specifications



Image for reference only

Dimensions	6.3" x 5" x 1.6"
Weight	1.5 lbs.
Display	Up to 2048 x 2732, customer device dependent
LCD Display	Up to 2048 x 2732, customer
RF	Wi-Fi /Bluetooth 2.4 GHz, 900 MHz proprietary receiver
Operating Temperature	-20°C to +50°C (-4°F to 120°F)
Long-term Storage Temperature	-40°C to +85°C (-40°F to 185°F)
Environmental Rating	Sealed enclosure, IP-65 rated
Battery	10,000 mA-hr. Li-ion 3.7V
Power input	5V-14V DC, up to 3.5A depending upon charger
Hazardous Area	Class 1 Division 2, Groups A-D, T4A, IP65
Certifications and Approvals	ISA-12.12.01; CAN/CSA C22.2 No 213-15, Class 1 Division2, UL 61010-1, FCC.



Applications Tests

Typical Use Performance

Type	70°F (Hours)
Operational Capacity*	~ 10
Charging Time**	~ 4

*Conditions of Continuous Operation

**To full capacity 100%

2023, Resonance Systems. All rights reserved.

The contents of this publication are presented for informational purposes only, and while diligent efforts have been made to ensure their accuracy, they should not be considered as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

Resonance Systems
 8609 Kingston Pike
 Ste 201
 Knoxville, TN 37923 USA
 +1-865-248-2453